

166-16 07/06/99

ACCEPTED

JAN 04 2001

the Federal Insecticide, Fungicide, and  
Fertilizer Act as amended, for the  
registered under

# Sea Hawk

## Yacht Finishes



44891-11

# PREMIUM QUALITY

Net Contents  
1 Gallon  
U.S. Measure  
3.785 Liters

**NEW NAUTICAL  
COATINGS, INC.**

2181-34th Way  
Largo, FL 33771

# SHARKSKIN

## Antifouling Paint

ACTIVE INGREDIENT Cuprous Oxide	45.2%
INERT INGREDIENTS	54.8%
TOTAL	100.00%

Copper expressed as metallic 42.21%  
CONTAINS PETROLEUM DISTILLATES

## KEEP OUT OF REACH OF CHILDREN WARNING

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

**LIMITED WARRANTY:** The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty of this product, expressed or implied.

1/4/2001

Page 122

**ACCEPTED**

JAN 04 2001

Under the Federal Insecticide, Fungicide, and  
Rodenticide Act as amended, for the  
pesticide registered under  
EPA Reg. No. 44891-11

## DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

## GENERAL DESCRIPTION

Traditional, hard, modified epoxy antifoulant that controls the attachment of barnacles, algae, seagrass, green weed and other fouling organisms in fresh and saltwater. This product is only for use on the surfaces of hulls on boats, vessels, barges, crab pots, lobster pots. SHAKE VIGOROUSLY FOR A MINIMUM OF 10 MINUTES BEFORE APPLICATION

### PRODUCT INFORMATION

Finish/Sheen: Semi-Gloss

Converter: One Pack

Copper Content: 45%

Volume Solids: 62% ± 2%

Mix Ratio: One Pack

Shipping Weight: 22-24 Lbs./Gal.

Flash Point: 80°F

Film Thickness: 5 mils wet equals 3.1 dry per coat

Recommended Coats: 2 on entire hull and 3 at waterline

Theoretical Coverage: 320 Sq. Ft./Gal. @ recommended film thickness

### APPLICATION DETAILS

Sweat-In Time: Not applicable

Thinner: 2033-2035

Cleaner: Sea Hawk Xylene 7130

### Overcoating Interval

#### Drying Time (Hrs)

Substrate Temp	Touch	Min.	Max.	Launch
73°F (23°C)	1 Hr	1 Hr	N/A	12 Hrs
95°F (35°C)	1 Hr	1 Hr	N/A	12 Hrs

### REGULATORY DATA

VOC: 332 Grams/Liter

**LIMITATIONS:** Apply in good weather when air and surface temperature are above 50°F (10°C). Surface temperature must be at least 50°F (10°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40 and 100°F (4-38°C). Prolonged atmospheric exposure of this product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating and the proper coating application procedures. As application, environmental and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of the coating.

**SURFACE PREPARATION:** Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing. (SSPC-SP1) New Construction: As yard procedures may vary, consult with your Sea Hawk Representative.

**APPLICATION:** Apply by brush, roller or spray. Apply 6 mils wet, which will yield 3.72 mils dry per coat.

### EQUIPMENT

Brush: China Bristle

Roller: Solvent Resistant Roller Cover 3/8" pile smooth to medium. Prewash Roller Cover to remove loose fibers prior to use.

Airless Spray: Minimum 28:1 ratio pump; 0.21" (5.33) 660 micron orifice up; 1/8" ID high pressure material hose; 90 PSI line pressure; 60 mesh tip filter.

**THINNING:** We do not recommend thinning. However, if thinning is necessary, thin up to a maximum of 10%, with Sea Hawk 2033-2035 only.

**CLEANUP:** Clean all equipment immediately after use with xylene. It is good practice to periodically flush out spray equipment during the course of the day. Frequency depends upon the amount sprayed, temperature, elapsed time including delay, etc.

**SAFETY:** Read and observe all precautionary statements on this label.

## PRECAUTIONARY STATEMENTS

### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**WARNING:** May be fatal if swallowed or inhaled. Causes moderate eye irritation. Harmful if absorbed through skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not breathe vapors, spray mist, or dust or chips from sanding. Avoid contact with skin, eyes or clothing. While spraying paint or sanding boat surface, wear a mask or pesticide respirator jointly approved by the Mine Safety and Health Administration and the National Institute for Occupational Safety and Health. Wear protective clothing (long-sleeved cotton shirt, long pants and hat) and gloves (such as nitrile or butyl). Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco. Remove contaminated clothing and wash before reuse. Use with adequate ventilation.

### ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply directly to water by cleaning of equipment or disposing of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

### PHYSICAL AND CHEMICAL HAZARDS

Combustible. Do not use or store near heat or open flame.

### STATEMENT OF PRACTICAL TREATMENT

**IF SWALLOWED:** Call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. If person is unconscious, do not give anything by mouth and do not induce vomiting.

**IF INHALED:** Remove victim to fresh air. If victim is not breathing give artificial respiration, preferably mouth-to-mouth. Get medical attention.

**IF IN EYES:** Flush with plenty of water. Call a physician if irritation persists.

**IF ON SKIN:** Wash with plenty of soap and water. Get medical attention.

### STORAGE AND DISPOSAL

Do not contaminate food, feed or water by storage or disposal.

**Storage:** Do not store near heat or open flame. Store in well-ventilated area.

**Pesticide Disposal:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**Container Disposal:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

E.P.A. Registration No. 44891-11 / E.P.A. Establishment No. 44891-11-1