

44891-13

4-18-2006

1/7



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, D.C. 20460

OFFICE OF  
PREVENTION, PESTICIDES AND  
TOXIC SUBSTANCES

APR 18 2006

**New Nautical Coating, Inc.**  
14805 49<sup>th</sup> Street North  
Clearwater, FL 33762

Attention: Mario Garneau

Subject: **Sea Hawk Premium Quality Tropikote Biocide Plus Slime Resistant Antifouling Coating**  
EPA Registration No. 44891-13  
Amendment Application Date: January 18, 2006  
EPA Received Date: January 23, 2006

The amendment referred to above, submitted in connection with registration under Insecticide, Fungicide, and Rodenticide Act (FIFRA), as amended, is acceptable.

- Comply with PR Notice 2001-1 (First Aid Statement)

A stamped copy of the label is enclosed for your records.

Please note that this is a time limited registration. The requested amendment can only be accepted on a time limited basis. The Agency is still in the process of completing the environmental risk assessment needed to support the antifouling use pattern. The Agency is now extending your time-limited to June 30, 2007.

2/7

If you have any question or comments concerning this letter, please contact me at (703) 308 6341 or Portia Jenkins at (703) 308-6230.

Sincerely,



Marshall Swindell  
Product Manager (33)  
Regulatory Management Branch I  
Antimicrobials Division (7510C)

Enclosure

3/7

ACCEPTED  
with COMMENTS  
EPA Letter Dated:

[FRONT PANEL]

APR 18 2006

# Sea Hawk

Yacht Finishes

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No. 44891-13

(Picture of Sea Hawk here)

PREMIUM QUALITY

## TROPIKOTE BIOCIDES PLUS SLIME RESISTANT

Antifouling Coating

[Optional proposed text appears in brackets - the final label may include some or all of the optional text]

[Paint Color and Number]

<b>ACTIVE INGREDIENT:</b>	
Cuprous Oxide .....	73.75%
N-Cyclopropyl-N'-(dimethylethyl)-6-(methylthio)- 1,3,5-triazine-2-diamine .....	2.02%
<b>OTHER INGREDIENTS:</b> .....	<u>24.23%</u>
<b>TOTAL:</b> .....	100.00%

KEEP OUT OF REACH OF CHILDREN

### WARNING

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

**LIMITED WARRANTY:** The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty for this product, expressed or implied.

4/7

[FRONT SIDE PANEL]

**Net Contents**  
**1 Gallon**  
**U.S. Measure**  
**3.785 Liters**

**NEW NAUTICAL COATINGS, INC.**  
**14805 49<sup>th</sup> Street North**  
**Clearwater, FL 33762**  
**www.seahawkpaints.com**

**ACCEPTED**  
**with COMMENTS**  
**EPA Letter Dated:**

**APR 18 2006**

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No. *44891-13*

5/7

[BACK PANEL]

**DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

**GENERAL DESCRIPTION**

Hard epoxy-based antifoulant with over 73% copper in every color. This product is designed to control barnacles, algae and other marine foulings in salt or fresh water. This product is designed for use on the surfaces of hulls on ships, boats, barges, yachts, or running gear.

Shake vigorously for several minutes with a mechanical paint shaker before use. Due to the settlement of copper in the product if this product is not properly shaken it will become ineffective.

**APPLICATION DETAILS**

Apply product generously on the surface to be coated. More coats will ensure a longer life. Do not apply product during moist conditions such as rain or high humidity. Wait at least 12 hours before submerging in water.

Sweat In Time:	Not Applicable
Thinner:	Sea Hawk 2033-2035 reducer
Cleaner:	Sea Hawk Xylene 7130

**REGULATORY DATA**

VOC: 288 Grams/Liter

**LIMITATIONS:** Apply in good weather when air and surface temperature are above 50° F (10° C). Surface temperature must be at least 50° F (10° C) above dew point. For optimum application properties, bring material to 70-80° F (21-27° C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40 and 100° F (4-38° C). Prolonged atmospheric exposure of this product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating application procedures. See published data sheets for more specific application data. As application, environment and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of the coating.

**SURFACE PREPARATION:** Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing. (SSPC-SPI)

**APPLICATION:** This product can be applied by brush, roller, or spray.

**ACCEPTED  
with COMMENTS  
EPA Letter Dated:**

APR 18 2006

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 44891-13

6/7

**[BACK PANEL CONTINUED]**

**THINNING:** We do not recommend thinning. If necessary thin no more than 10% by volume with 2033 or 2035.

**CLEANUP:** Clean all equipment immediately after using with Xylene.

**SAFETY:** Read and observe all precautionary statements on this label.

**STORAGE AND DISPOSAL**

Do not contaminate food, feed or water by storage or disposal.

**STORAGE:** Do not store near open heat or flame. Store in well ventilated area.

**PESTICIDE DISPOSAL:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by the use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**WARNING.** Causes eye irritation. Harmful if absorbed through skin. Avoid Contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Use with adequate ventilation.

**ENVIRONMENTAL HAZARDS**

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposing of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the

**ACCEPTED  
with COMMENTS  
EPA Letter Dated:**

APR 18 2006

7/7

[BACK PANEL CONTINUED]

permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

**PHYSICAL AND CHEMICAL HAZARDS**

**Combustible.** Do not use or store near open flame.

<b>FIRST AID</b>	
<b>If in eyes</b>	• Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Call a poison control center or doctor for treatment advice.
<b>If swallowed</b>	• Call poison control center or doctor immediately for treatment advice. • Have person sip a glass of water if able to swallow. • Do not induce vomiting unless told to do so by a poison control center or doctor. • Do not give anything by mouth to an unconscious person.
<b>If on skin or clothing</b>	• Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 minutes. • Call a poison control center or doctor for treatment advice.
<b>If inhaled</b>	• Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. • Call a poison control center or doctor for further treatment advice.
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-528-0997 for emergency medical treatment information.	
<b>NOTE TO PHYSICIAN:</b> Probably mucosal damage may contraindicate the use of gastric lavage.	

EPA Reg. No. 44891-13

EPA Est. No. 44891-FL-1

REVISED: 01-19-06

S:\MAJ\NEW NAUTICAL COATINGS, INC.\LABELS\SEA HAWK TROPIKOTE BIOCIDE PLUS SLIME RESISTANT

**ACCEPTED**  
**with COMMENTS**  
\* EPA Letter Dated:

Page 5

APR 18 2006

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide,

registered under EPA Reg. No. 44891-13