2014



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

November 10, 2014

Kevin Kutcel Agent for New Nautical Coatings, Inc. KRK Consulting LLC 5807 Churchill Way Medina, OH 44256

Subject:

Label Notification per PRN 98-10 – Minor label amendments Product Name: Sea Hawk Premium Quality Cukote Biocide + Slime Resistant Antifouling Coating EPA Registration Number: 44891-14 Application Date: October 7, 2014 Decision Number: 496364

Dear Mr. Kutcel:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped "Notification" and will be placed in our records.

If you have any questions, you may contact Jose Gayoso at (703) 347-8652 or via email at gayoso.jose@epa.gov.

Sincerely,

Seiichi Murasaki, Acting Product Manager 33 Regulatory Management Branch I Antimicrobials Division (7510P) Office of Pesticide Programs



PREMIUM QUALITY

BIOCIDE PLUS

Slime Resistant Antifouling Coating

ACTIVE INGREDIENT: Cuprous Oxide..... 47.57% N-Cyclopropyl-N' (1,1-dimethylethyl)-6-methylthio)-1,3,5 triazine-2-4 diamine.... 2.00% INERT INGREDIENTS: ______50.43% TOTAL ______100.00%

NOTIFICATION Date Reviewed: 11/10/14 Proviewed By: _____. G.

> > ¢

.....

....

....

ειčι

c (

.

KEEP OUT OF REACH OF CHILDREN WARNING

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

LIMITED WARRANTY: The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty of this product, expressed or implied.



Page 1 of 2

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

GENERAL DESCRIPTION

Ablative, self-polishing antifoulant. This product is designed to control barnacles, algae and other marine foulings in salt or fresh water. This product is designed for use on the surfaces of hulls on ships, boats, barges, yachts, or running gear.

Shake vigorously for several minutes with a mechanical paint shaker before use. Due to the settlement of copper in the product if this product is not properly shaken it may become ineffective.

Application Details

Apply product generously on the surface to be coated. More coats will ensure a longer life. Do not apply product during moist conditions such as rain or high humidity. Wait at least 12 hours before submerging in water.

Sweat in Time: NOT APPLICABLE Thinner: Seahawk 2033-2035

Cleaner: Seahawk Xylene 7130

Regulatory Data

VOC 288 grams/litre

Limitations: Apply in good weather when air and surface temperatures are above 50°F (10°C). Surface temperature must be at least 50°F (10°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40 and 100°F (4-38°C). Prolonged atmospheric exposure of this product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating application procedures. See published data sheets for more specific application data. As application, environmental and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of the coating.

SURFACE PREPARATION: Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing. (SSPC-SPI)

APPLICATION: This product can be applied by brush, roller or spray.

THINNING: We do not recommend thinning. If necessary thin no more than 10% by volume with 2033 or 2035.

CLEANUP: Clean all equipment immediately after using with Seahawk Xylene 7130.

SAFETY: Read and observe all precautionary statements on this label.

STORAGE AND DISPOSAL

Do not contaminate food, feed or water by storage or disposal.

Storage; Do not store near heat or open flame. Store in well-ventilated area.

Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by the use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal: Non-refillable container, do not reuse or refill this container. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING. Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Use with adequate ventilation.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposing of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sever systems without prevlously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS

Combustible. Do not use or store near open flame.

FIRST AID	
IF IN EYES:	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
IF SWALLOWED:	 Call poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.
IF ON SKIN OR CLOTHING:	 Take off contaminated clothing. Rinse skin Immediately with plenty of water for 15 – 20 minutes. Call a poison control center or doctor for treatment advice
IF INHALED:	 Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.
Call CHEMTREC Canada +1-703-	Aaterials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accider C Day or Night. Within USA and Canada 1-800-424-9300. Outside USA and 527-3887 CHEMTREC. Account #15570. Incies call New Nautical Coatings Inc., Within the USA and Canada

NOTE TO PHYSICIAN: Probably mucosal damage may contraindicate the use of gastric

E.P.A. Reg. No. 44891-14 E.P.A. Est. No. 44891-FL-1

Page 2 of 2

ιιιι

....

: c c c

с

....