

44891-15



12/3/2014

1/2

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

December 3, 2014

Kevin Kutcel  
Agent for New Nautical Coatings, Inc.  
KRK Consulting LLC  
5807 Churchill Way  
Medina, OH 44256

Subject: Label Notification per PRN 98-10 – Minor label amendments  
Product Name: Islands 77 Plus Antifouling Coating Black  
EPA Registration Number: 44891-15  
Application Date: November 10, 2014  
Decision Number: 496365

Dear Mr. Kutcel:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped "Notification" and will be placed in our records.

If you have any questions, you may contact Jose Gayoso at (703) 347-8652 or via email at [jose.gayoso@epa.gov](mailto:jose.gayoso@epa.gov).

Sincerely,

A handwritten signature in black ink, appearing to read "S. Murasaki for".

Seiichi Murasaki, Acting Product Manager 33  
Regulatory Management Branch I  
Antimicrobials Division (7510P)  
Office of Pesticide Programs



**NOTIFICATION**  
44891-15  
The applicant has certified that no changes, other than those reported to the Agency have been made to the label. This notification by letter dated 12/03/2014.

**PREMIUM QUALITY**

Islands 77 plus  
ANTIFOULING COATING

**7745 BLACK**


KEEP OUT OF REACH OF CHILDREN  
**DANGER**

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

Net Contents 1 Gallon  
U.S. Measure  
3.785 Liters



NEW NAVAL COATINGS, INC.  
Clearwater, FL 33762  
www.seahawkpaints.com



11577 01058

LIMITED WARRANTY: This product is warranted against peeling, cracking, or blistering by a defect in the material. The manufacturer is liable only under the conditions and to the extent stated in this limited warranty. No other liability or warranty of this product is expressed or implied.

**DIRECTIONS FOR USE**  
It is a violation of Federal law to use this product in a manner inconsistent with its labeling.  
**GENERAL DESCRIPTION**  
Active self-polishing surface coating designed to control barnacles, algae and other fouling in salt or fresh water. This product is designed for use on the surfaces of hulls on ships, boats, yachts, or running gear.  
Shake vigorously for several minutes with a mechanical paint shaker before use. Use in the product, if this product is not properly shaken it will become ineffective.

**PRODUCT INFORMATION**  
Semi-Gloss  
One Peak  
Converter  
Theoretical Coverage: 400 Sq. Ft./Gallon  
Dry Film Thickness: 2 mils  
Mix Ratio: 52% ± 2%  
Volume Solids: 46%  
One Peak  
Flash Point: 100°F/38°C  
Flash Point: 5 min wet equals 3.1 dry per coat

**APPLICATION DETAILS**  
Dry Film Thickness: 2 mils  
Sweat-in Time: 20-30-30-30  
Thinner: Sea Hawk 77-30  
Cleaner: Sea Hawk 77-30  
**SHAKE VIGOROUSLY FOR A MINIMUM OF 10 MINUTES BEFORE APPLICATION**  
Overcoating Interval  
Dry Time (Hr)  
Substrate Temp.: Touch Min. Max. 4-12  
52° F. 62° F. 1 Hr. N/A. 12 Hr. 24 Hr.

**REGULATORY DATA**  
VOC: 388 Grams/Liter  
LIMITATIONS: Apply in good weather when all surface temperature are above 50°F (10°C). Surface temperature must be at least 50°F (10°C) above dew point. Do not apply when surface temperature is less than 40°F (4°C) and temperature should be maintained in protected storage between 40 and 100°F (4-38°C). Prolonged atmospheric exposure of this product may detract from performance. As application, environmental and design factors can vary significantly, the user should consult the manufacturer in the selection, verification and use of the coating.

**SURFACE PREPARATION:** Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing. (SSPC-SP11) THINNING: This product can be applied by brush, roller or spray.  
**CLEANUP:** Clean all equipment immediately after use with Sea Hawk Xylene 7130.

**PRECAUTIONARY STATEMENTS**  
**HAZARD TO HUMANS AND DOMESTIC ANIMALS**  
DANGER: Causes eye pain. Harmful to aquatic life. Avoid Contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces wear a mask or a respirator only approved by the Mining Enforcement and Health Administration. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. Prolonged or frequently repeated skin contact may cause allergic reactions such as dermatitis and asthma. Adequate ventilation.

**ENVIRONMENTAL HAZARDS**  
This material is toxic to fish. Do not spray directly to water by cleaning of equipment or disposing of wastes. Do not allow chips and dust generated during application to be blown into water. Do not allow paint to be blown into water. Do not discharge effluent containing this product into lakes, streams, rivers, or bays. A National Pollutant Discharge Elimination System (NPDES) permit and the discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board.

**PHYSICAL AND CHEMICAL HAZARDS**  
Combustible. Do not use or store near open flames.  
**STORAGE AND DISPOSAL**  
Do not contaminate food, feed or water by storage or disposal. Store in a well ventilated area. Do not store near heat or open flame. Do not pour into storm drain, sink, toilet, pesticide spray, medicine, or waste. Do not reuse. Recycle if possible. Do not reuse. Do not use according to label instructions. Contact your State Pollution Control Agency for the Hazardous Waste Identification System (HWIS) number and/or for the Hazardous Waste Container Disposal. Non-refillable container, do not reuse or refill this container. Triple rinse for equivalent. Then offer for recycling or reconditioning, incineration, or by other procedures approved by state and local authorities.

**First Aid**  
IF IN EYES: Flush continuously with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes. Then continue flushing. Call a poison control center or doctor for treatment advice.  
IF SWALLOWED: Do not induce vomiting unless advised by a poison control center or doctor. Do not give anything by mouth to someone who is unconscious.  
IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water. Call a poison control center or doctor for more information.  
IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance. If breathing, give oxygen. If person is not breathing, use a rescue respirator or other appropriate respiratory protection.  
For Hazardous Materials (or Dangerous Goods) Incident: Spill, Leak, Fire, Explosion, or Accident or Release: Immediately call your local emergency response number for hazardous materials. For Non-Emergencies call New Naval Coatings Inc., Within the USA and Canada 1-800-528-5287 Outside USA and Canada 1-772-533-8353.

**NOTED TO DISTRIBUTOR: This product may vary from the use of plastic bags.**  
EPA Registration No. 44891-15 / E.P.A. Establishment No. 44891-FL-1

cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces wear a mask or a respirator only approved by the Mining Enforcement and Health Administration. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. Prolonged or frequently repeated skin contact may cause allergic reactions such as dermatitis and asthma. Adequate ventilation.

This material is toxic to fish. Do not spray directly to water by cleaning of equipment or disposing of wastes. Do not allow chips and dust generated during application to be blown into water. Do not allow paint to be blown into water. Do not discharge effluent containing this product into lakes, streams, rivers, or bays. A National Pollutant Discharge Elimination System (NPDES) permit and the discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board.

**PHYSICAL AND CHEMICAL HAZARDS**  
Combustible. Do not use or store near open flames.  
**STORAGE AND DISPOSAL**  
Do not contaminate food, feed or water by storage or disposal. Store in a well ventilated area. Do not store near heat or open flame. Do not pour into storm drain, sink, toilet, pesticide spray, medicine, or waste. Do not reuse. Recycle if possible. Do not reuse. Do not use according to label instructions. Contact your State Pollution Control Agency for the Hazardous Waste Identification System (HWIS) number and/or for the Hazardous Waste Container Disposal. Non-refillable container, do not reuse or refill this container. Triple rinse for equivalent. Then offer for recycling or reconditioning, incineration, or by other procedures approved by state and local authorities.

**First Aid**  
IF IN EYES: Flush continuously with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes. Then continue flushing. Call a poison control center or doctor for treatment advice.  
IF SWALLOWED: Do not induce vomiting unless advised by a poison control center or doctor. Do not give anything by mouth to someone who is unconscious.  
IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water. Call a poison control center or doctor for more information.  
IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance. If breathing, give oxygen. If person is not breathing, use a rescue respirator or other appropriate respiratory protection.  
For Hazardous Materials (or Dangerous Goods) Incident: Spill, Leak, Fire, Explosion, or Accident or Release: Immediately call your local emergency response number for hazardous materials. For Non-Emergencies call New Naval Coatings Inc., Within the USA and Canada 1-800-528-5287 Outside USA and Canada 1-772-533-8353.

**NOTED TO DISTRIBUTOR: This product may vary from the use of plastic bags.**  
EPA Registration No. 44891-15 / E.P.A. Establishment No. 44891-FL-1