



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

April 22, 2015

Kevin R. Kutcel
Agent for New Nautical Coatings, Inc.
KRK Consulting LLC
14805 49th Street
Clearwater, FL 33762

Subject: Notification per PRN 98-10 – ‘Minor Label Changes’
Product Name: Copper- Free Waterborne Antifouling Coating White
EPA Registration Number: 44891-17
Application Date: 4/3/15
Decision Number: 503202

Dear Kevin R. Kutcel

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

If you have any questions, you may contact Elizabeth Watkins at 703-347-0241 or via email at Watkins.elizabeth@epa.gov.

Sincerely,

A handwritten signature in blue ink that reads "Elizabeth H. Watkins for".

John Hebert, Chief
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

Sea Hawk
Yacht Finishes
PREMIUM QUALITY

NOTIFICATION

44891-17

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

04/22/2015

**Copper-Free Waterborne
Antifouling Coating White**

ACTIVE INGREDIENT: Zinc Omadine..... 4.02%
OTHER INGREDIENTS: 95.98%
TOTAL 100.00%

KEEP OUT OF REACH OF CHILDREN
DANGER

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

LIMITED WARRANTY: The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty of this product, expressed or implied.

Net Contents 1 Gallon
U.S. Measure
3.785 Liters

NEW NAUTICAL COATINGS, INC.

14805 49th Street North
Clearwater, FL 33762
www.seahawkpaints.com

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

GENERAL DESCRIPTION

Hard abrasive, multi-seasonal, water-based antifoulant. Provides protection against algae, barnacles, annelids, tunicates, bryzoa, hydroids, zebra mussels and other fouling organisms. Mission Bay CSF is abrasion resistant for scrubbing, trailering and dry storage. Reduces paint buildup. This product may only be used to treat the surfaces of hulls on boats and vessels. This product is intended for both salt and fresh water use. Product applies easily and dries quickly. It may be used over old antifouling finishes in good condition. Mission Bay CSF is an antifouling paint in a high-technology vehicle that withstands frequent trailering, beaching and launching. Shake vigorously for several minutes with a mechanical paint shaker before use. Due to the settlement in the product, if this product is not properly shaken it will become ineffective.

SHAKE VIGOROUSLY FOR A MINIMUM OF 10 MINUTES BEFORE APPLICATION

PRODUCT INFORMATION

Finish/Sheen: Semi-Gloss
Converter: One Pack
Volume Solids: 44% ± 2%
Mix Ratio: One Pack
Shipping Weight: 13-14 Lbs./Gal.
Flash Point: N/A
Film Thickness: 5 mils wet equals 2.2 dry per coat
Recommended Coats: 3
Theoretical Coverage: 320 Sq. Ft./Gal. @ recommended film thickness

APPLICATION DETAILS

Sweat-In Time: Not Applicable
Thinner: N/A
Cleaner: Water

Overcoating Interval Drying Time (Hrs)

Substrate Temp.	Touch	Min.	Max.	Launch
73°F (23°C)	2 Hrs	1 Hr	N/A	12 Hrs
95°F (35°C)	1 Hr	1 Hr	N/A	12 Hrs

REGULATORY DATA

VOC: 113 Grams/Liter

LIMITATIONS: Apply in good weather when air and surface temperature are above 50°F (10°C). Surface temperature must be at least 50°F (10°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40 and 100°F (4-38°C). Prolonged atmospheric exposure of this product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating application procedures. See published data sheets for more specific application data. As application, environment and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of the coating.

SURFACE PREPARATION: Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing. (SSPC-SPI)

APPLICATION: This product can be applied by brush or roller.

THINNING: We do not recommend thinning.

CLEANUP: Clean all equipment immediately after use with water.

SAFETY: Read and observe all precautionary statements on this label.

STORAGE AND DISPOSAL

Do not contaminate food, feed or water by storage or disposal.

Storage: Do not store near heat or open flame.

Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by the use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Non-refillable container, do not reuse or refill this container. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER-CORROSIVE. Causes irreversible eye damage. Harmful if swallowed or absorbed through the skin. May be fatal if inhaled. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not get in the eyes, on skin, or on clothing. Do not breathe vapor or spray mist. Wash thoroughly after handling with soap and water, and before eating, drinking or using tobacco. Remove contaminated clothing and wash clothing before reuse. When mixing and loading, or cleaning equipment, wear a chemical resistant apron.

Residential PPE: Residential (non-commercial) users are advised to wear chemical resistant gloves, protective eyewear (goggles, safety glasses or face shield), long-sleeved shirt and long pants, socks, and shoes. While removing existing paint by sanding or blasting, or applying new paint by brush or roller, it is advised to wear a respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (MSHANIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHANIOSH approval number TC-14G), or a NIOSH approved full face respirator with an organic vapor removing cartridge with a P-100 prefilter.

Commercial PPE: Users must wear a disposable coverall with hood, chemical resistant gloves, protective eyewear (goggles, safety glasses or face shield), long-sleeved shirt and long pants, socks, and chemical resistant footwear. While removing existing paint by sanding or blasting, or applying new paint, user must wear a respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (MSHANIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHANIOSH approval number TC-14G), or a NIOSH approved full face respirator with an organic vapor removing cartridge with a P-100 prefilter.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposing of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS

Combustible. Do not use or store near heat or open flame.

FIRST AID	
If in eyes	• Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Call a poison control center or doctor for treatment advice.
If swallowed	• Call poison control center or doctor immediately for treatment advice. • Do not give any liquid to the person. • Do not induce vomiting unless told to do so by a poison control center or doctor. • Do not give anything by mouth to an unconscious person.
If inhaled	• Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. • Call a poison control center or doctor for further treatment advice.
If on skin or clothing	• Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15 – 20 minutes. • Call a poison control center or doctor for treatment advice.
<p>For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night. Within USA and Canada 1-800-424-9300. Outside USA and Canada +1-703-527-3887 CHEMTREC. Account #15570.</p> <p>For Non Emergencies call New Nautical Coatings Inc., Within the USA and Canada 1-800-528-0997, Outside USA and Canada +1-727-523-8053.</p>	
<p>NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.</p>	

E.P.A. Registration No. 44891-17

E.P.A. Establishment No. 44891-FL-1