



#### UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

New Nautical Coatings, Inc. 14805 49<sup>th</sup> Street North Clearwater, FL 33762

SEP 13 2011

Attention: Erik Norrie

CEO

Subject:

Notification - Sea Hawk Smart Solution

EPA Reg. No. 44891-19

Application Received August 23, 2011

This will acknowledge receipt of your notification for the aforementioned product label. submitted under the provisions of Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA) Section 3© (9). Based on a review of the submitted material, the following apply:

- The Agency approves the following changes made to the label:
  - o Addition of the phrase, "causes skin irritation" to the Precautionary Statement. and
  - o Movement of the, "If on Skin" language in the First Aid Section.

The Notification is in compliance with PR Notice 98-10 and is acceptable. This information has been made a part of your file.

If you have any questions concerning this letter, please contact Abigail Downs at (703) 305-5259.

Sincerely,

Marshall Swindel

Product Manager (33)

Regulatory Management Branch I Antimicrobials Division (7510P)

Please read instructions on reverse before completin. rm.	Form Appro	oved. OMB 2070	Print Form
United States  Environmental Protection A Washington, DC 20460	Agency	Registrati × Amendme	
Application for	or Pesticide - Sect	ion I	
1. Company/Product Number 44891-19	2. ERA Product Mana	nger	3. Proposed Classification
4. Company/Product (Name) Sea Hawk Smart Solution	PM#		None Restricted
5. Name and Address of Applicant (Include ZIP Code)  New Nautical Coatings, Inc.  14805 49th Street North  Clearwater, FL 33762  Check if this is a new address			e with FIFRA Section 3(c)(3) In composition and labeling
	Section - II		
Amendment - Explain below.  Resubmission in response to Agency letter dated  Notification - Explain below.  Final printed labels in response to Agency letter dated  "Me Too" Application.  Other - Explain below.			•
Amendment to add Precautionary Statement section, Causes s First Aid section change the placement of the If On Skin box to	directly after the If In Ey		he first sentence. Also, under
	Section - III	Man Carlo	
Yes" No No If "Yes" No. par	Yes No  Yes No. per container	5. Location of Label	Metal Plastic Glass Paper Other (Specify)
Label Container		On Labeling	accompanying product
6. Manner in Which Label is Affixed to Product  Lithograph Paper glued Stenciled	Other		
S	ection - IV		
1. Contact Point	individual to be contacted,		CT C
Name Erik Norrie			27-523-8053
Certification I certify that the statements I have made on this form and all a I acknowledge that any knowingly false or misleading statement both under applicable law.  2. Signature  3. Ti	ttachments thereto are true nt may be punishable by fin itle		(Stamped)
4. typed Name 5. D			CCCCC



New Nautical Coatings, Inc.

August 12, 2011

Abigail Downs
Antimircrobials Division – 7510P
Regulatory Management Branch
2777 Crystal Drive
Room-S4900, 4th Floor
Arlington, VA 22202

Attn: Abigail Downs

Notification Team

Subject Notification of label changes

Sea Hawk Smart Solution

Dear Ms.Downs:

This submission is being made on behalf of New Nautical Coatings, Inc. Please find enclosed a notification to 1) add Causes skin irritation in Precautionary Statement 2) move If On Skin to under the If In Eyes in the First Aid section

Included with this submission, please fine the following:

1. An application for Pesticide Other (EPA Form 8570-1)

2. One (1) copy of product labeling.

Should you have any questions or need additional information please do not hesitate to contact us.

CEO

Enclosures

**Yacht Finishes** 

# PREMIUM QUALITY

**Net Contents** 1 Gallon U.S. Measure **3.785 Liters** 

**NEW NAUTICAL** COATINGS, INC. 14805 49th Street North

Clearwater, FL 33762 www.seahawkpaints.com

# OLUTION

Antifouling Coating

KEEP OUT OF REACH OF CHILDREN

DANGER
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMEN

LIMITED WARRANTY: The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty of this product, expressed or implied.

\*Contains petroleum distillates, xylene, or xylene range aromatic solvents

DIRECTIONS FOR USE: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

GENERAL DESCRIPTION: Ablative, self-polishing antifoulant. This product is designed to control barnacles, algae and other marine fouling in salt or fresh water. This product is designed for use on the surfaces of hulls on ships, boats, barges, yachts, or running gear.

Shake vigorously for several minutes with a mechanical paint shaker before use. Due to the settlement in the product, if this product is not properly shaken it will become ineffective.

### SHAKE VIGOROUSLY FOR A MINIMUM OF 10 MINUTES BEFORE APPLICATION

#### PRODUCT INFORMATION

Finish/Sheen: Semi-Gloss Converter: One Pack Volume Solids: 50% ± 2% Mix Ratio: One Pack

Shipping Weight: 12-13 lbs/gal

Flash Point: 100° F

Film Thickness: 6 mils wet equals 2.7 dry per coat

Recommended Coats: 3

Theoretical Coverage: 267 sq.ft./gal. @ recommended film thickness.

APPLICATION DETAILS

Sweat-In Time: N/A

Thinner: Sea Hawk 2033, 2035 Cleaner: Sea Hawk Xylene 7130

# OVERCOATING INTERVALS: Drying Time (Hrs):

Substrate Temperature	Touch	Min	Max	Launch
73°F (23°C)	2 Hrs	1 Hr	N/A	12 Hrs
95°F (35°C)	1 Hr	1 Hr	N/A	12 Hrs

Consult your Sea Hawk Representative for the system best suited for surfaces to be protected.

REGULATORY DATA VOC: 298 Grams/Liter

Limitations: Apply in good weather when air and surface temperature are above 50° F(10°C). Surface temperatures must be at least 50°F (10°C) above

dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40-100°F (4-38°C). Prolonged atmospheric exposure of the product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating application procedures. See published data sheets for more specific application data. As application, environment and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of coating.

SURFACE PREPARATION: Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing (SSPC-SPI).

**Application:** This product can be applied by brush, roller, or spray.

Thinning: We do not recommend thinning. If necessary thin no more than 10% by volume with 2033 or 2035.

Clean Up: Clean all equipment immediately after using with Sea Hawk Xylene 7130.

Safety: Read and observe all precautionary statements on this Label.

#### STORAGE AND DISPOSAL

Do not contaminate food, feed or water by storage or disposal. **Storage:** Do not store near open heat or flame. Store in well ventilated area.

Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by the use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

## PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Corrosive: Causes irreversible eye damage.
Causes skin irritation. May be fatal if swallowed.
Hamful if inhaled. Do not get in eyes or clothing.
Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Avoid contact with skin, eyes or clothing. Avoid breath-

ing vapor or spray. When handling, wear goggles or face shield, chemically resistant gloves, long sleeved shirt and pants, socks, chemical resistant footwear, and chemically resistant gloves (such as Barrier Laminate, Butyl Rubber, and Nitrile Rubber). When mixing, loading, or cleaning equipment, wear chemical-resistant apron. For overhead exposure wear chemical-resistant headgear. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco. Pemove and wash contaminated clothing before reuse.

#### **ENVIRONMENTAL HAZARDS**

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposing of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS

Combustible. Do not use or store near open flame

	First Aid
If in eyes:	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call poison control center or doctor for treatment advice.
If on skin:	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
If swallowed:	Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to by a poison control center or doctor. Do not give anything to an unconscious person.
If inhaled:	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or doctor for treatment advice.
NOTE TO PHYSICIAN:	May pose an aspiration pneumonia hazard. Contains petroleum distillate.

Have the product container or label with you when calling a poison control center or doctor or going for treatment. For emergency information or (product, use, etc.), call a National Pesticides Information Center at 1-800-858-7378, 6:30AM to 4:30PM Pacific Time (PT), seven days a week. During other times, call poison control center 1-800-225-21222.

New Nautical Coatings, Inc. 14805 49th Street North, Clearwater, FL 33762 www.SeaHawkpaints.com 800-528-0997 EPA Est. No. 44891-FL-1 EPA Reg. No. 44891-19