



OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

WASHINGTON, D.C. 20460

June 26, 2024

Erik Norrie
New Nautical Coatings Inc
Electronic Transmittal: enorrie@seahawkpaints.com

Subject: Label Amendment – Tralopyril Amended Interim Registration Review Decision
Label Mitigation
Registration Review Interim Decision Label Mitigation
Product Name: Seahawk Smart Solution Antifouling Coating Black
EPA Registration Number: 44891-19
Received Date: 7/24/2020
Decision Number: 564888

Dear Erik Norrie:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

The Agency, in accordance with the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, has completed reviewing all of the information submitted with your application to support the Registration Review of the above referenced product in connection with the Tralopyril Amended Interim Decision, and has concluded that your submission is acceptable.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. Pursuant to 40 CFR 156.10(a)(6) you must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 12 months from the date of this letter. After 12 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under FIFRA and is subject to review by the Agency. See FIFRA section 2(p)(2). If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process, FIFRA section 12(a)(1)(B). Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. If you have any questions, please contact Erin Dandridge by phone at 202-566-0635, or via email at dandridge.erin@epa.gov.

Sincerely,

A handwritten signature in cursive script, appearing to read "Kimberly Whitesell".

Kimberly Whitesell
Senior Environmental Protection Specialist
Reevaluation Branch
Antimicrobials Division
Office of Pesticide Programs

Enclosure: Stamped Label

Notes to reviewer are bracketed []
Statements in parenthesis are optional or alternative text ()

[In accordance with 40 CFR 156.68(d), all first aid statements, as prescribed, will appear on the front panel of the product label.]

SEAHAWK SMART SOLUTION ANTIFOULING COATING BLACK

[Alternative Brand Names]

Smart Solution, Sea Hawk Premium Quality Smart Solution Antifouling Coating
Smart Solution Antifouling Coating
Smart Solution Antifouling Paint
Sea Hawk Yacht Finishes Premium Quality Smart Solution Antifouling Coating

ACCEPTED

06/26/2024

Under the Federal Insecticide, Fungicide
and Rodenticide Act as amended, for the
pesticide registered under
EPA Reg. No. 44891-19

Active Ingredients:
(2-(p-chlorophenyl)-3-cyano-4-
bromo-5-trifluoromethyl pyrrole)
(tralopyril) 2.90%
Other Ingredients: 97.10%
TOTAL 100.00%
*Contains petroleum distillates,
xylene, or xylene range aromatic
solvents.

KEEP OUT OF REACH OF CHILDREN
DANGER

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

First Aid	
If in eyes:	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call poison control center or doctor for treatment advice.
If on skin:	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
If swallowed:	Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to by a poison control center or doctor. Do not give anything to an unconscious person.
If inhaled:	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or doctor for treatment advice.
Have the product container or label with you when calling a poison control center or doctor or going for treatment.	
For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night. Within USA and Canada 1-800-424-9300. Outside USA and Canada +1-703-741-5970 CHEMTREC. Account #15570.	
For Non Emergencies call New Nautical Coatings Inc., Within the USA and Canada 1-800-528-0997, Outside USA and Canada +1-727-523-8053.	
NOTE TO PHYSICIAN: May pose an aspiration pneumonia hazard. Contains petroleum distillate.	

(LIMITED WARRANTY: The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty of this product, expressed or implied.)

[OPTIONAL MARKETING STATEMENTS:]

Outdrive Paint
Metal Free Coating
Outboard Paint
Lower Unit Coating
Environmental Buoy Paint
Eco Buoy
Crap Trap Paint
Yacht Finishes
Premium Finishes
Sea Hawk
Sea Hawk Paints
Premium Quality
Antifouling Coating
Antifouling Paint
Copper-Free Antifouling
Metal-free self-polishing ablative antifoulant
Environmentally safe
Compatible over most existing antifoulants
Econea
Lloyd's Register certified
Ideal outdrive antifoulant
The ECONEA Tradename and logo are registered trademarks of Janssen PMP, a division of
Janssen Pharmaceutica, NV, Beerse, Belgium
Premium Yacht Finishes
California Compliant
Limited One Year Warranty
Multi Season Protection
Metal-Free
Aluminum Hull Compatible
4705 Black
4702 Bright Blue
4730 Dark Blue
4701 Bright Red
4703 Bright Green
4710 White
4731 Light Grey

[Optional Graphics]

PREMIUM QUALITY





[ABOVE BAR CODE WILL APPEAR ON EACH CAN AND THE NUMBERS WILL CORRESPOND WITH THE BAR CODE ISSUED FOR THAT PRODUCT.]



[Above will be used with contents and manufacturer depending on the size]

[Net Contents:] (5-gallon pail 18.927), (Gallon 3.785 Liters), (Quart 0.9463 Liters) (Pint .4732 Liters)
(Batch Code) [to appear on front or back panel of the label or immediate container depending on the container type/size]

DIRECTIONS FOR USE: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Using a program that conforms to OSHA's requirements (see 29 CFR Part 1910.134), occupational handlers' employers must verify that any handler who uses a respirator is: fit tested and fit-checked, trained and examined by a qualified practitioner to ensure physical ability to safely wear the style of respirator to be worn. A qualified practitioner is a physician or other licensed health care professional who will evaluate the ability of a worker to wear a respirator. The initial evaluation consists of a questionnaire that asks about the medical conditions (such as a heart condition) that would be problematic for respirator use. If concerns are identified, then additional evaluations, such as a physical exam, might be necessary. The initial evaluation must be done before respirator use begins. Handlers must be reexamined by a qualified medical practitioner if their health status of respirator style or use-conditions change. Upon request by local/state/federal/tribal enforcement personnel, employers must provide documentation demonstrating how they have complied with these requirements.

GENERAL DESCRIPTION: Ablative, self-polishing antifoulant. This product is designed to control barnacles, algae and other marine fouling in salt or fresh water. This product is designed for use on the surfaces of hulls on ships, boats, barges, yachts, or running gear.

Shake vigorously for several minutes with a mechanical paint shaker before use. Due to the settlement in the product, if this product is not properly shaken it will become ineffective.

SHAKE VIGOROUSLY FOR A MINIMUM OF 10 MINUTES BEFORE APPLICATION

PRODUCT INFORMATION

Finish/Sheen: Semi-Gloss

Converter: One Pack

Volume Solids: 63% \pm 2%

Mix Ratio: One Pack

Shipping Weight: 10-11 lbs/gal

Flash Point: 100° F/38° C

Theoretical Coverage: 267 sq.ft./gal.

APPLICATION DETAILS

Sweat-In Time: N/A

Thinner: Sea Hawk 2033, 2035

Cleaner: Sea Hawk Xylene 7130

OVERCOATING INTERVALS:

Drying Time (Hrs):

Substrate Temp.	Touch	Min.	Max.	Launch
73°F (23°C)	2 Hrs	6 Hr	N/A	12 Hrs
95°F (35°C)	1 Hr	4 Hr	N/A	12 Hrs

Consult your Sea Hawk Representative for the system best suited for surfaces to be protected.

REGULATORY DATA

VOC: 328 Grams/Liter

Limitations: Apply in good weather when air and surface temperature are above 50° F (10°C). Surface temperatures must be at least 5°F (1°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application.

Unmixed material (in closed containers) should be maintained in protected storage between 40-100°F (4-38°C). Prolonged atmospheric exposure of the product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating application procedures. See published data sheets for more specific application data. As application, environment and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of coating.

SURFACE PREPARATION: Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing (SSPC-SPI).

Application: This product can be applied by brush, roller, or spray.

Thinning: We do not recommend thinning. If necessary, thin no more than 10% by volume with 2033 or 2035.

Clean Up: Clean all equipment immediately after using with Sea Hawk Xylene 7130.

Safety: Read and observe all precautionary statements on this Label.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER. Corrosive: Causes irreversible eye damage. Causes skin irritation. May be fatal if swallowed. Harmful if inhaled. Do not get in eyes or on clothing. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Avoid contact with skin, eyes or clothing. Avoid breathing vapor or spray. When handling, wear goggles or face shield, chemically resistant gloves, long sleeved shirt and pants, socks, chemical resistant footwear, and chemically resistant gloves (such as Barrier Laminate, Butyl Rubber, and Nitrile Rubber). When mixing, loading, or cleaning equipment, wear chemical-resistant apron. For overhead exposure wear chemical-resistant headgear. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco. Remove and wash contaminated clothing before reuse.

PERSONAL PROTECTION EQUIPMENT (PPE)

Occupational handlers in the sprayman position applying this product are required to wear a NIOSH approved full facepiece supplied-air respirator (PF 1000) during use OR a continuous flow supplied air or powered air purifying respirator equipped with a hood that covers the face, neck, and shoulders. The air or powered air purifying respirator is required to have an assigned protection factor of 1,000, per NIOSH standards, and must be used with an organic vapor cartridge and a high efficiency (HEPA) pre-filter. The spray man must wear safety glasses beneath the hood respirator. Occupational handlers in the line tender position applying this product are required to wear a NIOSH approved air-purifying half-face mask elastomeric respirator (PF 10) with any R or P filter during use. Follow manufacturer's instructions for cleaning / maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

ENVIRONMENTAL HAZARDS

This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS

Combustible. Do not use or store near open flame.

STORAGE AND DISPOSAL

Do not contaminate food, feed or water by storage or disposal.

Storage: Do not store near open heat or flame. Store below 100°F/38°C. Store in well ventilated area.

Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal: Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

EPA Reg. No. 44891-19 EPA Est No. XXXXX-XX-X