

#### OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

WASHINGTON, D.C. 20460

July 15, 2024

Kevin Kutcel Agent New Nautical Coatings Inc

Electronic Transmittal: kevinkutcel@gmail.com

Subject: Label Amendment – Tralopyril Amended Interim Registration Review Decision

**Label Mitigation** 

Registration Review Interim Decision Label Mitigation

Product Name: ColorKote

EPA Registration Number: 44891-21

Received Date: 7/21/2020 Decision Number: 564795

#### Dear Kevin Kutcel:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

The Agency, in accordance with the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, has completed reviewing all of the information submitted with your application to support the Registration Review of the above referenced product in connection with the Tralopyril Amended Interim Decision, and has concluded that your submission is acceptable.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. Pursuant to 40 CFR 156.10(a)(6) you must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 12 months from the date of this letter. After 12 months, you may only distribute or sell this product if it bears this new revised

Page 2 of 2 EPA Reg. No. 44891-21 Decision No. 564795

labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under FIFRA and is subject to review by the Agency. See FIFRA section 2(p)(2). If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process, FIFRA section 12(a)(1)(B). Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. If you have any questions, please contact Erin Dandridge by phone at 202-566-0635, or via email at <a href="mailto:dandridge.erin@epa.gov">dandridge.erin@epa.gov</a>.

Sincerely,

Michael J. Varco
Acting Senior Environmental Protection Specialist
Reevaluation Branch
Antimicrobials Division
Office of Pesticide Programs

Enclosure

Notes to reviewer are bracketed [] Statements in parenthesis are optional or alternative text ()

### ACCEPTED

07/15/2024

Under the Federal Insecticide, Fungicide and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No.

44891-21

## [Brand Names] **COLORKOTE**

[Alternative Brand Names]
(COLORKOTE AF)
(SPECTRUM AF)
(ECLIPSE AF)
(PRISM AF)
(WHITE LIGHTNING)
(FISHMAN)

**Active Ingredients:** 

Tralopyril	3.20%
Zinc Pyrithione	4.72%
Copper Thiocyanate	10.65%
Other Ingredients	81.43%
Total	100.00%
Copper expressed as metallic 5.58%.	
Contains Petroleum Distillates.	

# KEEP OUT OF THE REACH OF CHILDREN CAUTION SEE BACK PANEL FOR ADDITIONAL PRECUATIONARY STATEMENTS AND FIRST AID

(LIMITED WARRANTY: The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty of this product, expressed or implied.)

#### [OPTIONAL MARKETING STATEMENTS:]

(Sea Hawk)
(Premium Yacht Finishes)
(Yacht Finishes)
(Premium Quality)
(Antifouling Coating)
(Antifouling Paint)
(Fouling Control)
(Hand Crafted in America!SM)
(Tough on Barnacles)
(California Compliant)
(Self Polishing)
(Ablative)
(Controlled Release)

(PL3 Technology)

(Limited One Year Warranty)

(Multi Season Protection)

(Lloyds Register Certified)

(Multi-Biocide Antifouling Power!SM)

(Powerful Antifouling Formula)

(Triple Biocide)

(Slime Reducing)

(Reduces Slime and Algae)

(High Performance)

(Racing Finish)

(Burnishable)

(Vibrant Colors)

(Mixable Colors)

(Customizable Colors)

(Bright White)

(White)

(Deep Black)

(Black)

(Bright Blue)

(Blue)

(Bright Red)

(Red)

(Fighting Lady Yellow)

(Mellow Yellow)

(Yellow)

(Bright Green)

(Green)

(330 VOC)

(Aluminum Safe)

(For use on Fiberglass, Wood, Steel, and Aluminum)

(Hull, Outdrive, Propeller)

(Ideal for Outdrives)

(Suitable for Salt Water, Fresh Water, Brackish Water)

(Color Your Bottom)

(Color Your Hull)

(Express Yourself)

(The ECONEA trade name and logo are trademarks of Janssen PMP, a division of Janssen Pharmaceutica, NV,

Beerse, Belgium)

(New)

(Part numbers with colors)

[Optional Graphics]















## PREMIUM QUALITY





[ABOVE BAR CODE WILL APPEAR ON EACH CAN AND THE NUMBERS WILL CORRESPOND WITH THE BAR CODE ISSUED FOR THAT PRODUCT.]



[Above will be used with contents and manufacturer depending on the size] [Net Contents:] (5-gallon pail 18.927), (Gallon 3.785 Liters), (Quart 0.9463 Liters)

(Batch Code) [to appear on front or back panel of the label or immediate container depending on the container type/size]

#### **DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Occupational handlers' employers must verify that any handler who uses a respirator is: fit tested and fit-checked, trained and examined by a qualified practitioner to ensure physical ability to safely wear the style of respirator to be worn. A qualified practitioner is a physician or other licensed health care professional who will evaluate the ability of a worker to wear a respirator. The initial evaluation consists of a questionnaire that asks about the medical conditions (such as a heart condition) that would be problematic for respirator use. If concerns are identified, then additional evaluations, such as a physical exam, might be necessary. The initial evaluation must be done before respirator use begins. Handlers must be reexamined by a qualified medical practitioner if their health status of respirator style or use-conditions change. Upon request by local/state/federal/tribal enforcement personnel, employers must provide documentation demonstrating how they have complied with these requirements.

#### PRODUCT GENERAL DESCRIPTION

Ablative, self-polishing antifoulant with Vibrant Colors designed for use on Aluminum Hull vessels but also can also be used on Fiberglass, Wood and Steel. This product controls barnacles, algae, and other marine organisms. It can be used in both fresh and salt water. This product has a copolymer, biocide release mechanism. The product prevents coating buildup and is able to be hauled for extended periods and then relaunched without affecting the antifouling properties.

SHAKE VIGOROUSLY FOR A MINIMUM OF 10 MINUTES BEFORE APPLICATION

Note-Stirring with a Jiffy Mixer or paint paddle is not adequate.

#### PRODUCT INFORMATION

Finish/Sheen:Semi-GlossShipping Weight:12-13 Lbs./Gal.Flash Point:86.2°F/30°C

Cleaner: Sea Hawk Xylene 7130
Thinner: Sea Hawk 2053

Substrate Temp.	Dry Time	Overcoating	Launch
73°F (23°C)	2 Hrs	5 Hr	12 Hrs

95°F (35°C) 1 Hr 3 Hr 12 Hrs

Consult with your Sea Hawk representative for the system best suited for surfaces to be protected.

#### **REGULATORY DATA**

VOC: 330 Grams/Liter

**LIMITATIONS:** Apply in good weather when air and surface temperature are above 50°F (10°C). Surface temperature must be at least 5°F (1°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40 and 100°F (4-38°C). Prolonged atmospheric exposure of this product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating and the proper coating application procedures. As application, environmental and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of the coating.

SURFACE PREPARATION: Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing. (SSPC-SPI)

New Construction: As yard procedures may vary, consult with your Sea Hawk Representative.

**APPLICATION:** Apply two coats by brush, roller or spray.

**THINNING:** We do not recommend thinning. However, if thinning is necessary, thin up to a maximum of 10% with Sea Hawk 2053.

**CLEANUP:** Clean all equipment immediately after use with Sea Hawk Xylene 7130. It is good practice to periodically flush out spray equipment during the course of the day. Frequency depends upon the amount sprayed, temperature, elapsed time including delay, etc.

**SAFETY:** Read and observe all precautionary statements on this label.

#### STORAGE AND DISPOSAL

Do not contaminate food, feed or water by storage or disposal.

**Storage:** Do not store near heat or open flame. Store below 100°F/38°C. Store in well-ventilated area. **Pesticide Disposal:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by the use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**Container Disposal:** Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

### PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**CAUTION.** Causes moderate eye irritation. Harmful if swallowed. Harmful if absorbed through skin. Avoid contact with eyes or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove and wash contaminated clothing before reuse. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

#### PERSONAL PROTECTION EQUIPMENT (PPE)

Wear protective eyewear such as goggles, face shield or safety glasses. Wear a NIOSH-approved respirator with an organic vapor (OV) cartridge with a combination N, R, or P filter with NIOSH approval number prefix 84A; or NIOSH approved gas mask with an organic vapor canister with NIOSH approval number prefix TC-14G; or a NIOSH approved powered air purifying respirator with organic vapor (OV) cartridge and combination HE filter with NIOSH approval number prefix TC 23C. Occupational handlers in the sprayman position applying this product are required to wear a NIOSH approved full facepiece supplied-air respirator (PF 1000) during use OR a continuous flow supplied air or powered air purifying respirator equipped with a hood that covers the face, neck, and shoulders. The air or powered air purifying respirator is required to have an assigned protection factor of 1,000, per NIOSH standards, and must be used with an organic vapor cartridge and a high efficiency (HEPA) prefilter. The spray man must wear safety glasses beneath the hood respirator. Occupational handlers in the line tender position applying this product are required to wear a NIOSH approved air-purifying half-face mask elastomeric respirator (PF 10) with any R or P filter during use. Follow manufacturer's instructions for cleaning / maintaining PPE.

If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

#### **USER SAFETY RECOMMENDATIONS**

Remove clothing / PPE immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Remove PPE immediately after handling this product. As soon as possible, wash thoroughly and change into clean clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove and wash contaminated clothing before reuse.

#### **ENVIRONMENTAL HAZARDS**

This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewer treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

#### PHYSICAL AND CHEMICAL HAZARDS

Combustible: Do not use or store near heat or open flame.

FIRST AID		
IF ON SKIN OR CLOTHING:	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15 – 20 minutes. Call a poison control center or doctor for treatment advice.	
IF SWALLOWED:	<ul> <li>Immediately call a poison control center or doctor immediately for treatment advice.</li> <li>Do not induce vomiting unless told to do so by a poison control center or doctor.</li> <li>Do not give any liquid to the person.</li> <li>Do not give anything by mouth to an unconscious person.</li> </ul>	
IF INHALED:	Move person to fresh air     If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.     Call a poison control center or doctor for further treatment advice.	
IF IN EYES:	Hold eye open and rinse slowly and gently with water for 15-20 minutes.     Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.     Call a poison control center or doctor for treatment advice.	

Have the product container or label with you when calling a poison control center or doctor or going for treatment. For general information on product use, etc., call the National Pesticides Information Center at 1-800-858-7378. You may also contact the poison control center at 1-800-222-1222 for emergency medical treatment information.

For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night. Within USA and Canada 1-800-424-9300. Outside USA and Canada +1-703-741-5970 CHEMTREC Account #15570.

For Non Emergencies call New Nautical Coatings Inc., Within the USA and Canada 1-800-528-0997, Outside USA and Canada +1-727-523-8053.

**NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of gastric lavage. Contains petroleum distillate, vomiting may cause aspiration pneumonia.

EPA Reg. No. 44891-21 EPA Est. No. XXXXX-XX-X