



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

April 14, 2021

Kevin Kutcel  
Agent for  
New Nautical Coatings Inc.  
14805 49<sup>th</sup> Street  
Clearwater, FL 33762

Subject: Notification per PRN 98-10 – Addition of “contents under pressure”  
Product Name: Smart Solution Antifouling Spray Paint  
EPA Registration Number: 44891-22  
Application Date: March 16, 2020  
Action Case Number: 219614

Dear Mr. Kutcel:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Assurance.

If you have any questions, you may contact Tara Flint via email at [flint.tara@epa.gov](mailto:flint.tara@epa.gov).

Sincerely,

A handwritten signature in blue ink that reads "Tara M. Flint".

For  
Eric Miederhoff, Product Manager 31  
Regulatory Management Branch 1  
Antimicrobials Division (7510P)  
Office of Pesticide Programs

Notes to reviewer are bracketed [ ]  
Statements in parenthesis are optional or alternative text ( )  
[Delete] Strike Through

**HIGHLIGHTED**

[Brand Names]  
**SMART SOLUTION ANTIFOULING SPRAY PAINT**

**NOTIFICATION**

[Alternative Brand Names]  
**Smart Solution**  
**Sea Hawk Spray Paint**  
**Smart Solution Aerosol**

44891-22  
The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

04/14/2021

Active Ingredients:	
tralopyril .....	0.98%
Other Ingredients: .....	99.02%
TOTAL .....	100.00%

\*Contains petroleum distillates, xylene, or xylene range aromatic solvents.

**KEEP OUT OF REACH OF CHILDREN**  
**DANGER**

**CONTENTS UNDER PRESSURE**

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

(**LIMITED WARRANTY:** The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty of this product, expressed or implied.)

**[OPTIONAL MARKETING STATEMENTS:]**

Premium Quality  
Sea Hawk  
Sea Hawk Paints  
Antifouling Spray  
Antifouling Spray Paint  
For Outboards, outdrives, and propellers  
Ideal for Outboards, outdrives, and propellers  
Ideal for crap traps

Antifouling Coating  
Copper-Free Antifouling  
Metal-free self-polishing ablative antifoulant  
Econea  
Ideal Outdrive Antifoulant  
The ECONEA Tradename and logo are registered trademarks of Janssen PMP, a division of  
Janssen Pharmaceutica, NV, Beerse, Belgium  
Metal Free Coating  
Outboard Paint  
Lower Unit Coating  
Premium Yacht Finishes  
Hand Crafted in America!  
Outdrive Paint  
Compatible with aluminum outboards, outdrives and hulls  
4705A Black

[Optional Graphics]

## PREMIUM QUALITY





[ABOVE BAR CODE WILL APPEAR ON EACH CAN AND THE NUMBERS WILL CORRESPOND WITH THE BAR CODE ISSUED FOR THAT PRODUCT.]

**Manufactured by:**  
**NEW NAUTICAL COATINGS, INC.**  
14805 49<sup>TH</sup> Street North, Clearwater, FL 33762

**Net Contents 16 Oz. (454 g)**

[Above will be used with contents and manufacturer]

(Batch Code) [to appear on front or back panel of the label or immediate container depending on the container type/size]

#### **DIRECTIONS FOR USE**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

**GENERAL DESCRIPTION:** This aerosol is an antifouling spray paint ideal for outboards, outdrives and propellers. It is a metal-free coating that is compatible with aluminum, outboards, outdrives and hulls.

#### **APPLICATION DETAILS**

Apply this spray paint after applying Barnacle Blocker as a primer.

1. Shake can vigorously for 2 minutes.
2. Hold can 12-16 inches away from unit.
3. Apply contents of one can for each outdrive/outboard for best antifouling protection. It will be dry to the touch in 30 minutes.
4. Be sure the paint is completely dry before immersion. Allow a minimum of 12 hours at 75°F/24°C prior to launch.
5. When finished spraying, clear spray valve by turning can upside down and spraying until no more paint comes out.

**SURFACE PREPARATION:** Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing (SSPC-SPI).

**Consult your Sea Hawk Representative for the system best suited for surfaces to be protected.**

#### **REGULATORY DATA**

##### **VOC/MIR: 0.91**

**Limitations:** Apply in good weather when air and surface temperature are above 50° F (10°C). Surface temperatures must be at least 5° F (1°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40-100°F (4-38°C). Prolonged atmospheric exposure of the product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating application procedures. See published data sheets for more specific application data. As application, environment and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of coating.

**Safety:** Read and observe all precautionary statements on this Label.

### STORAGE AND DISPOSAL

Do not contaminate food, feed or water by storage or disposal.

**Storage:** Do not store near open heat or flame. Store in a closed, properly labeled container in a cool, dry place. Keep container tightly closed and upright to prevent leakage. In case of spillage, absorb and dispose of in accordance with local and state authorities.

**Pesticide Disposal:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

**Container Handling:** Do Not Puncture or Incinerate! If empty: Place in trash or offer for recycling, if available. If partly filled: Call your local solid waste agency for disposal instructions.

### PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER. Corrosive: Causes skin burns, irreversible eye damage. Causes skin irritation. May be fatal if swallowed. May be fatal if inhaled. Do not get in eyes or on clothing. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Avoid contact with skin, eyes or clothing. Avoid breathing vapor or spray. A minimum of a half face NIOSH approved respirator (TC-84A) with organic vapor cartridges with any R or P combination filter. Higher level respirators that are NIOSH approved for organic vapors and particulates that contain oil can also be used. When handling, wear goggles or face shield, chemically resistant gloves, long sleeved shirt and pants, socks, chemical resistant footwear, and chemically resistant gloves (such as Barrier Laminate, Butyl Rubber, and Nitrile Rubber). When mixing, loading, or cleaning equipment, wear chemical-resistant apron. For overhead exposure wear chemical-resistant headgear. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco. Remove and wash contaminated clothing before reuse.

### ENVIRONMENTAL HAZARDS

This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

### PHYSICAL AND CHEMICAL HAZARDS

Combustible. Do not use or store near open flame.

First Aid	
If on skin:	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
If in eyes:	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call poison control center or doctor for treatment advice.
If inhaled:	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or doctor for treatment advice.
If swallowed:	Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to by a poison control center or doctor. Do not give anything to an unconscious person.
Have the product container or label with you when calling a poison control center or doctor or going for treatment.	
For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night. Within USA and Canada 1-800-424-9300. Outside USA and Canada +1-703-741-5970 CHEMTREC. Account #15570. For Non Emergencies call New Nautical Coatings Inc., Within the USA and Canada 1-800-528-0997, Outside USA and Canada +1-727-523-8053.	
<b>NOTE TO PHYSICIAN:</b> Probable mucosal damage may contraindicate the use of gastric lavage.	