



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

January 13, 2021

Kevin Kutcel
Agent
New Nautical Coatings
14805 49th Street North
Clearwater, FL 33762

Subject: Notification per PRN 98-10 – Revision to storage and disposal, optional marking statement, update Est. No, name and address
Product Name: Aquagard II Antifouling Spray paint for Outdrive and Outboards
EPA Registration Number: 44891-28
Application Date: July 21, 2020
Decision Number: 564947

Dear Mr. Kutcel:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

If you have any questions, you may contact Zebora Johnson at (703) 308-7080 or via email at johnson.zebora@epa.gov

Sincerely,
Zebora Johnson
John Hebert, Branch Chief 33
Antimicrobials Division
Office of Pesticide Programs (7510P)

NOTIFICATION

44891-28

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

01/13/2020

Notes to reviewer are bracketed []
Statements in parenthesis are optional or alternative text ()
[Delete] Strike Through

[Brand Names]

Aquagard II Antifouling Spray Paint for Outdrive & Outboards

[Alternative Brand Names]

Aquagard II Alumi-Coat Outboard & Lower Unit Antifouling Paint

[ADD AS ALTERNATIVE NAME]

(Aquagard II Alumi-Koat)

(Alumi-Koat Outboard & Lower Unit Antifouling Paint)

(Alumi-Koat Spray Anti-fouling Paint)

(Transducer Paint)

(Aquagard Transducer Paint)

(Aquagard II Spray)

**AQUAGARD II SPRAY
ANTIFOULING PAINT FOR
OUTDRIVES & OUTBOARDS**

ACTIVE INGREDIENT	
Cuprous Thiocyanate N-Cyclopropyl-N ^o -(1:1-dimethylethyl)-6-(methylthio)-1,3, 5-triazine-2,4-diamine-CAS No. 1111-67-7	3.71%
OTHER INERT INGREDIENTS	95.49%
TOTAL	100.00%
Copper expressed as metallic 1.98%	
Contains Petroleum Distillates	

KEEP OUT OF REACH OF CHILDREN

CAUTION

Extremely flammable. Contents under pressure. Harmful if inhaled.

SEE **OTHER CAUTIONS ON SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS AND FIRST AID**

[OPTIONAL MARKETING STATEMENTS:]

Control slime & other fouling organisms!
For use on aluminum & other non-ferrous materials
Ideal for use on stern drives and other lower units
Repels Barnacles & Other Growth
Ideal for Use on Nylon or Bronze Transducers
Antifouling Spray
Antifouling Paint
Antifouling Spray Paint
Hand Crafted in America
American Owned and Operated

[Optional Graphics]

FLEXDEL

AQUAGARD®



8 11577 01595 9

[ABOVE BAR CODE WILL APPEAR ON EACH CAN AND THE NUMBERS PROVIDED THE ABOVE WILL CORRESPOND WITH THE BAR CODE ISSUED FOR THAT PRODUCT.]

Manufactured by: ~~Flexabar Corporation~~
~~1069 Rutgers University Blvd.,~~
~~Lakewood New Jersey 08701~~
~~Phone: 732-901-6500~~
{New Nautical Coatings, Inc.}
{14805 49th Street North}
{Clearwater, FL 33756}

EPA Est. No. ~~3993-NJ01~~ 44891-FL-1

[Above will be used with contents and manufacturer depending on the size]

[Net Contents:] (12oz. /340g) (6 oz. / 170g)

(Batch Code) [to appear on front or back panel of the label or immediate container depending on the container type/size]

SIDE PANEL

FIRST AID: IF SWALLOWED: 1.) Call poison control center or doctor immediately for treatment advice. 2.) Do not give any liquid to the person. 3.) Do not induce vomiting unless told to do so by a poison control center or doctor. 4.) Do not give anything by mouth to an unconscious person. **IF ON SKIN OR CLOTHING:** 1.) Take off contaminated clothing. 2.) If on skin wash with plenty of water. 3.) Get medical attention if irritation persists. **IF INHALED:** 1.) Move person to fresh air. 2.) If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. 3.) Call a poison control center or doctor for further treatment advice. **IF IN EYES:** 1.) Hold eye open and rinse slowly and gently with water for 15-20 minutes. 2.) Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. 3.) Call a poison control center or doctor for treatment advice.

ENVIRONMENTAL HAZARDS

This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD: Extremely flammable. Contents under pressure. Keep away from heat, sparks and open fire or heat surfaces. Do not puncture or incinerate container. Exposure to temperatures above 103°F may cause bursting.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING. Causes substantial but temporary eye injury. May be fatal if swallowed or inhaled. Harmful if absorbed through skin. Do not get in eyes or clothing. Do not breathe vapors or spray mist, or dust or chips from sanding. Avoid contact with skin, eyes or clothing. Wear protective eyewear (goggles, face shield, or safety glasses). While spraying paint or sanding boat surface, wear a minimum of a NIOSH-approved particulate filtering facepiece respirator with any N1,R, or P filter; OR a NIOSH-approved elastomeric particulate respirator with any N1, R, or P filter; OR a NIOSH-approved powered air purifying respirator with HE filters. Wear protective clothing (long-sleeved cotton shirt, long pants and hat) and waterproof gloves. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco. Remove contaminated clothing and wash before reuse.

SIDE PANEL

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

APPLICATION; A clean dry surface free of scale, corrosion, dirt, grease, oil, marine fouling or other foreign matter will provide the optimum performance of this paint. Inadequate surface preparation will

result in unsatisfactory performance. Be sure to remove all dust, debris and other surface contaminations that are generated by the cleaning process prior to painting. Bring to room temperature (72°) before spraying. Shake can for 3 minutes, listening for mixing ball.

New Outdrive Units: Lightly sand the factory finish with 80 grit sandpaper, wipe clean with Aquagard 180 Solvent Wash. allow to dry. Then apply two (2) coats of Aquagard II Alumi-Koat allowing 2-4 hours drying time between coats. Allow to dry 2-4 hours before launching.

Bare Aluminum: Make sure surface is dry and free of grease, wax, oil and loose paint. Abrade to bright metal by sandblasting, sanding or wire brushing. Wipe clean of any residue, then apply Aquagard 181 Primer or 189 Sandless Primer Spray. Closely follow these instructions. Then apply two (2) coats of Aquagard II Alumi-Koat allowing 2-4 hours drying time between coats. Allow to dry 2-4 hours before launching.

Previously Painted Aluminum: Previously painted surfaces in poor condition (chipping or flaking) should be stripped to bare metal, then proceed with the bare aluminum instructions specified above. If the previous antifouling paint is a vinyl type, sand it thoroughly with 80 grit sand paper, wipe clean of sanding residue and apply at least two (2) coats of Aquagard II Alumi-Koat.

STORAGE AND DISPOSAL

Do not contaminate food, feed or water by storage or disposal.

Storage: Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. Store in cool dry area away from heat or flame. Keep container closed when not in use. Keep container tight and upright to prevent leakage. Do not store near heat or open flame. Store below 100°F/38°C. Store in well-ventilated area. Keep from freezing.

Pesticide Disposal: Pesticide wastes are toxic. Pesticide wastes are acutely hazardous. Paint that cannot be disposed of according to label instructions, must be disposed of according to applicable Federal, State or Local procedures. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal: Do not puncture or incinerate. A completely empty can, can be disposed of with household trash. Wrap in paper before disposal.

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of New Nautical Coatings, Inc., Flexdel Corp, including environmental conditions. Therefore, Flexdel Corp, New Nautical Coatings, Inc., cannot guarantee this product's suitability for your particular purpose of application. Implied warranties of fitness for particular purpose and of merchantability are excluded. Flexdel Corp, New Nautical Coatings, Inc., shall not under any circumstances, be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Flexdel Corp., New Nautical Coatings, Inc., option.

E.P.A. Reg. No. 9339-31 EPA Est. No. 9339-NJ04 44891-28/ E.P.A. Est. No. 44891-FL-1