

Albaphos CTB-500

ACCEPTED
JUL 1981
EPA REG. NO.

ACTIVE INGREDIENT

Polyoxyethylene (dimethylamino) ethylene (dimethylamino) ethylene dihydrochloride 40.0%

INERT INGREDIENT

80.0%

This product contains 1.74 lb. of active ingredient per gallon and weighs 8.69 lb. per gallon.

KEEP OUT OF REACH OF CHILDREN

CAUTION

PRECAUTIONARY STATEMENT

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

FIRST AID: If swallowed, drink promptly a large quantity of milk or water with gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol for a physician immediately.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish, birds, and aquatic life. Do not apply to lakes, streams, or ponds. Permitting may be required for this pesticide. Do not apply to lakes, streams, ponds, or public water. For more information, contact the regional office of the Environmental Protection Agency.

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Albaphos CTB 500 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 2.9 to 7.3 fluid ounces of Albaphos CTB 500 per 1000 gallons of water to provide a concentration of 24 to 60 parts per million of Albaphos CTB 500, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 0.73 to 7.3 fluid ounces of Albaphos CTB 500 per 1000 gallons of water (6 to 60 parts per million of Albaphos CTB 500) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

Albaphos CTB 500 is used to control bacteria in industrial air washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 11.1 to 18.3 fluid ounces of Albaphos CTB 500 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 7.5 to 18.3 fluid ounces of Albaphos CTB 500 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection trays of the airwash system.

STORAGE & DISPOSAL: Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal, or cleaning of equipment. Residue that cannot be used or reprocessed, should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open containers should be buried.

METAL CONTAINERS: Triple rinse and offer for recycling, reconditioning, or disposal in an approved landfill or bury in a safe place.

PLASTIC CONTAINERS: Do not reuse empty container. Triple rinse and incinerate or dispose of in an approved landfill or bury in safe place.

Manufactured by

BA Latentburg Corporation
11112 Hartland St., P.O. Box 3245
North Hollywood, CA 91605

EPA EST. NO.

NET CONTENTS