

BETZ Slime-trol[®] RX-34

PAPERCHEN, INC.

SLIME CONTROL AGENT

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND
DOMESTIC ANIMALS

WARNING

HARMFUL IF SWALLOWED. CAUSES EYE AND SKIN IRRITATION. DO NOT GET INTO EYES, ON SKIN OR ON CLOTHING. DO NOT INHALE VAPOR OR MIST. USE WITH ADEQUATE VENTILATION. ALL INDUSTRIAL WORKERS APPLYING THIS PRODUCT MUST WEAR COVERALLS OVER A LONG-SLEEVED SHIRT AND LONG PANTS, SHOES, SOCKS & CHEMICAL-RESISTANT GLOVES. DURING DILUTION, A CHEMICAL-RESISTANT APRON & GOGGLES OR FACE SHIELD MUST ALSO BE WORN. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE. WASH THOROUGHLY AFTER HANDLING.

ENVIRONMENTAL HAZARDS

THIS PESTICIDE IS TOXIC TO FISH & WILDLIFE. DO NOT DISCHARGE EFFLUENT CONTAINING THIS ACTIVE INGREDIENT INTO LAKES, STREAMS, PONDS, ESTUARIES, OCEANS OR PUBLIC WATERS UNLESS THIS PESTICIDE IS SPECIFICALLY IDENTIFIED & ADDRESSED IN AN NPDES PERMIT. DO NOT DISCHARGE EFFLUENT CONTAINING THIS PESTICIDE TO SEWER SYSTEMS WITHOUT PREVIOUSLY NOTIFYING THE SEWAGE TREATMENT PLANT AUTHORITY. FOR GUIDANCE CONTACT YOUR STATE WATER BOARD OR REGIONAL OFFICE OF THE EPA. APPLY THIS PESTICIDE ONLY AS SPECIFIED ON THIS LABEL.

EPA WORK COPY

DO NOT STAMP

cc highlight for
changes

NET WT.: _____ LBS.
LOT NO. _____

FOR INDUSTRIAL USE. Technical advice regarding specific site problems is available from BETZ RX34EPA 9205

Active Ingredients:

Sodium dimethylidithio-	
carbamate.....	15%
Nabam (Disodium Ethylene	
Bisdithiocarbamate).....	15%
Inert Ingredients.....	70%
Total.....	100%

CONTENTS: LIQUID

EPA EST. NO.

POUNDS PER GALLON: 9.58 (60F)

EPA REG. NO.: 45017-14

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

STORAGE: Keep container tightly closed. Protect from freezing. Store in a dry place. Do not store at elevated temperatures.

PESTICIDE DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Pesticide wastes are acutely hazardous and/or toxic. Improper disposal of pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: METAL AND PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose in a sanitary landfill, or incinerate or burn, if allowed by state and local authorities. If burned, stay out of smoke.

FIBER DRUMS WITH LINERS: Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application container. Dispose of liner and drum in a sanitary landfill or incinerate if allowed by state and local authorities. Do not reuse empty drum or liner.

PULP AND PAPER MILL SYSTEMS

This product aids in the control of objectionable bacteria and fungi in pulp, paper mill and the additive system, and for the preservation of pulp, pigment slurries, emulsions, adhesives, defoamers, polymers & paper products.

Additions can be made on a continuous or intermittent basis, depending upon the severity of the problem.

BADLY FOULED SYSTEMS must be cleaned before treatment is begun.

FOR SLIME CONTROL

This product should be added directly to the pulp and paper mill systems. Apply at a point in the system where the product will be uniformly mixed.

INTERMITTENT OR SLUG METHOD--INITIAL DOSE: When the system is noticeably fouled, add this product at the rate of 0.15 to 2.5 pounds per ton of pulp or paper produced.

Additions to the additive system should be made directly at the rate of 0.2 to 2.5 pounds (24 to 300ppm) per 1000 gallons. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add this product at the rate of 0.15 to 2.0 pounds per ton of pulp or paper produced. Treat the system as needed to maintain control. Additions to the additive system may be reduced to 0.2 to 2.0 pounds (24 to 240 ppm) per 1000 gallons.

CONTINUOUS FEED METHOD--INITIAL DOSE: When the system is noticeably fouled, add this product at the rate of 0.15 to 2.5 pounds per ton of pulp or paper produced. Additions to the additive system should be made directly at the rate of 0.2 to 2.5 pounds (24 to 300 ppm) per 1000 gallons. Repeat until control is achieved.

SUBSEQUENT DOSE: Maintain the following level by continuous feed. Additions to the additive system should be at the rate of 0.2 to 2.0 pounds per 1000 gallons.

FOR PRESERVATION
This product should be added directly to the material to be preserved. Additions to the additive system should be made directly at the rate of 0.2 to 2.5 pounds (24 to 300 ppm) per 1000 gallons. Repeat until control is achieved.

This product should be added directly to the material to be preserved. Additions to the additive system should be made directly at the rate of 0.2 to 2.5 pounds (24 to 300 ppm) per 1000 gallons. Repeat until control is achieved.

WARNING KEEP OUT OF REACH OF CHILDREN STATEMENT OF PRACTICAL TREATMENT

In case of contact with skin, wash immediately with plenty of soap and water. Immediately contact physician.

In case of contact with eyes, flush promptly and thoroughly with clear water for at least 15 minutes. Immediately contact physician.

If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or water. If none is available, drink large quantities of water. Immediately contact physician.

A Material Safety Data Sheet containing more detailed information relative to this product is available upon request.