



**Betz PaperChem, Inc.**

# Slime-trol RX-32P

## DIRECTIONS FOR USE

### GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

### PULP AND PAPER MILL SYSTEMS

BETZ PaperChem Slime-trol RX-32P aids in the control of objectionable bacteria and fungi in pulp, paper mill and the additives system, and for the preservation of pulp, pigment slurries, emulsions, adhesives, defoamers, polymers and paper products. Additions can be made on a continuous or intermittent basis, depending upon the severity of the problem.

**BADLY FOULED SYSTEMS** must be cleaned before treatment is begun.

### FOR SLIME CONTROL

BETZ PaperChem Slime-trol RX-32P should be added directly to the pulp and paper mill systems. Apply at a point in the system where the product will be uniformly mixed.

### INTERMITTENT OR SLUG METHOD

**INITIAL DOSE:** When the system is noticeably fouled, add 0.1 to 0.75 pound per ton of pulp or paper produced. Additions to the additive system should be made directly at a rate of 0.1 to 1.0 pound per 1000 gallons or 12 to 120 parts per million. Repeat until control is achieved.

(Directions for use continued on right panel.)

PM1014 5101

## PRECAUTIONARY STATEMENTS

### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

#### DANGER

**CORROSIVE.** Causes eye and skin damage. Harmful if swallowed or absorbed through skin. Do not inhale dust or fumes. Do not get in eyes, on skin or clothing. Keep container closed when not in use. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly after handling.

### ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge into lakes, streams, ponds or public waters unless in accordance with a NPDES permit. For guidance contact your Regional Office of the EPA. Do not contaminate water by cleaning of container and equipment or disposal of wastes. Apply this pesticide only as specified on this label.

### KEEP CONTAINER COVERED

### STORE IN A DRY PLACE

### DO NOT STORE AT ELEVATED TEMPERATURES

### Contents: PELLETS

#### Active Ingredients:

Methylenebis (thiocyanate) ..... 7.0%

Inert ingredients\* ..... 93.0%

\*Inert ingredients include solubilizing and dispersing agents.

EPA Reg. No. 45017-19

**NET WEIGHT AND VOLUME**  
As Marked on Container

### KEEP OUT OF REACH OF CHILDREN

#### DANGER

#### FIRST AID

If swallowed, promptly drink a large quantity of milk, beaten egg whites or gelatin solution. If these are not available, drink large quantities of water. Avoid alcohol. Call a physician at once. Never give an unconscious person anything by mouth.

If on skin, immediately flush with plenty of water for at least 15 minutes. Remove and wash contaminated clothing.

If in eyes, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

ACCEPTED

MAY 08 1981

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 45017-19

# Control RX-32P SLIME CONTROL AGENT

Contents: PELLETS

Active Ingredients:

Methylenebis (thiocyanate) ..... 7.0%

Inert Ingredients\*: ..... 93.0%

\*Inert ingredients include solubilizing and dispersing agents.

EPA Reg. No. 45017-19

NET WEIGHT AND VOLUME  
As Marked on Container

KEEP OUT OF REACH OF CHILDREN

**DANGER**

**FIRST AID**

If swallowed, promptly drink a large quantity of milk, beaten egg whites or gelatin solution. If these are not available, drink large quantities of water. Avoid alcohol. Call a physician at once. Never give an unconscious person anything by mouth.

If on skin, immediately flush with plenty of water for at least 15 minutes. Remove and wash contaminated clothing.

If in eyes, immediately flush eyes with plenty of water for at least 15 minutes. Call physician.

**SUBSEQUENT DOSE:** When microbial control is evident, add 0.1 to 0.5 pound per ton of pulp or paper produced. Treat the system as needed to maintain control. Additions to the additive system may be reduced to 0.1 to 0.75 pound per 1000 gallons or 12 to 90 parts per million.

#### CONTINUOUS FEED METHOD

**INITIAL DOSE:** When the system is noticeably fouled add 0.1 to 0.75 pound per ton of pulp or paper produced. Additions to the additives should be made directly at a rate of 0.1 to 1.0 pound per 1000 gallons or 12 to 120 parts per million. Repeat until control is achieved.

**SUBSEQUENT DOSE:** Maintain the following level by continuous feed of 0.1 to 0.5 pound per ton of pulp and paper produced. Additions to the additive should be at a rate of 0.1 to 0.75 pound per 1000 gallons or 12 to 90 parts per million.

**BADLY FOULED SYSTEMS** must be cleaned before treatment is begun.

#### FOR PRESERVATION

This product should be added directly to the material to be preserved prior to manufacturing into the finished product, i.e., pulp, broke, polymers, defoamers, alum, emulsions, adhesives, paper mill coatings, pigment slurries, paper products, etc. The dosage rate will depend upon the material to be preserved and the storage time. The usual addition should be

200-300 ppm and under extreme conditions of spoilage the dosage rate should be increased to 250-800 ppm. The above recommendations are based on a maximum storage time of 2 weeks. For storage time greater than 2 weeks, the maximum concentration should be increased to 1000 ppm.

#### STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Do not reuse empty container.

Pesticide or rinsate that cannot be used or chemically reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies.

Triple rinse the container or equivalent method before sending to drum conditioner or destroying by perforation or crushing and burying in a safe place. Consult Federal, state or local authorities for approved alternative procedures.

#### FOR INDUSTRIAL USE ONLY

Technical advice regarding specific site problems available from BETZ PaperChem.