



GEN 9905 - 5/14/99



HEALTH: :::	3
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	C

Packaging Date: 05/14/99

Net Weight: Lbs.

**DL RX-32P**

- AGENT

KEEP OUT OF REACH OF CHILDREN

**DANGER**

Industrial Use. Technical advice regarding specific site conditions is available from BetzDearborn Inc. A Material Safety Sheet containing more detailed information relative to this product is available upon request.

is inconsistent with its labeling.

and the additive system, and for the preservation of pulp, pigment slurries, emulsions, adhesives, defoamers, polymers and paper mill coatings. Additions can be made to BADLY FOULED SYSTEMS must be cleaned before treatment is begun.

present in the system where the product will be uniformly mixed.

If the system is fouled, add this product at the rate of 0.1 to 0.75 pound per ton of pulp or paper produced. Additions of this product to the additive system should be made until control is achieved. **SUBSEQUENT DOSE:** When microbial control is evident, add this product at the rate of 0.1 to 0.5 pound per ton of pulp or paper produced. The dosage system may be reduced to 0.1 to 0.75 pound (12 to 90 ppm) per 1000 gallons.

If the system is severely fouled, add this product at the rate of 0.1 to 0.75 pound per ton of pulp or paper produced. Additions of this product to the additive system should be made directly at the rate of 0.1 to 1.0 pound (12 to 120 ppm) per 1000 gallons. Continue until control is achieved. If the system is moderately fouled, add this product at the rate of 0.1 to 0.5 pound per ton of pulp and paper produced. Addition of this product to the additive system should be at the rate of 0.1 to 0.75 pound (12 to 90 ppm) per 1000 gallons.

Manufacturing into the finished product, i.e., pulp, broke, polymers, defoamers, alum, emulsions, adhesives, paper mill coatings, pigment slurries and paper mill coatings. The usual addition should be 200 to 300 ppm and under extreme conditions of spoilage the dosage rate should be increased to a maximum storage time of 2 weeks. For storage time greater than 2 weeks the maximum concentration of this product should be increased to 1000 ppm.

**SERVICE WATER, PROCESS WATER AND WASTE WATER SYSTEMS**

Control bacteria, sulfate reducing bacteria and algae in Recirculating Cooling Water, Auxiliary Water and Service Water, Process Water and Waste Water associated equipment.

If the system is severely fouled, add this product at the rate of 0.2 to 2.5 pounds (24 to 300 ppm) per 1000 gallons of water in the system. Repeat dose until control is achieved. If the system is moderately fouled, add this product at the rate of 0.2 to 1.5 pounds (24 to 180 ppm) per 1000 gallons of water in the system every 3 days or as needed to maintain control.

If the system is lightly fouled, add this product at the rate of 0.1 to 1.5 pounds (12 to 180 ppm) per 1000 gallons of water in the system. Repeat dose until control is achieved. Dosage of 0.1 to 1.5 pounds (12 to 180 ppm) per 1000 gallons of water loss from the system.

Precautions:

Excess pesticide wastes are acutely hazardous and/or toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by the manufacturer, they must be stored in a container labeled "Excess Pesticide" and taken to a local or Federal Pesticide Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance. Do not offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incinerate or burn, if allowed by state and local authorities. If burned, stay out of the fire. Do not empty into waterways. Do not empty into surface water. Do not empty into ground. Do not empty into storm drains. Do not empty into sewers. Do not empty into basins and bottom to loosen clinging particles. Empty residue into application equipment. Then dispose of liner and drum in a sanitary landfill or incinerate if allowed by state and local authorities.

MIAMI, FL, 32256 • Business Phone: 215-355-3300 • Emergency Phone: 800-877-1940

PM 83

45017-19

7-21-99

JUL 21 1999

45017-19