

# BETZ

PAPERCHEN, INC.

# Slime-trol

SLIME CONTROL AGENT

# DP-808

PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND  
DOMESTIC ANIMALS

### DANGER

CORROSIVE. CAUSES EYE DAMAGE AND SKIN BURNS. MAY CAUSE ALLERGIC SKIN REACTION. HARMFUL IF INHALED. HARMFUL IF SWALLOWED. DO NOT GET INTO EYES, ON SKIN, OR ON CLOTHING. AVOID BREATHING VAPOR OR MIST. USE WITH ADEQUATE VENTILATION. WEAR RUBBER GLOVES, GOGGLES AND FACE SHIELD WHEN HANDLING. AVOID CONTAMINATION OF FOOD. DO NOT TAKE INTERNALLY. WASH THOROUGHLY AFTER HANDLING.

### ENVIRONMENTAL HAZARDS

THIS PESTICIDE IS TOXIC TO FISH AND WILD-LIFE. DO NOT DISCHARGE INTO LAKES, STREAMS, PONDS OR PUBLIC WATER UNLESS IN ACCORDANCE WITH A NPDES PERMIT. FOR GUIDANCE, CONTACT YOUR REGIONAL OFFICE OF THE EPA. DO NOT CONTAMINATE WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. APPLY THIS PESTICIDE ONLY AS SPECIFIED ON THIS LABEL.

### Active Ingredients:

5-Chloro-2-methyl-4-isothiazolin-3-one..... 1.15%  
2-Methyl-4-isothiazolin-3-one..... 0.35%

Inert Ingredients:..... 98.50%  
Total..... 100.00%

CONTENTS: LIQUID  
POUNDS PER GALLON: 8.6 (70F)  
EPA REG. NO.: 45017-34

EPA EST. NO.

### DANGER

### KEEP OUT OF REACH OF CHILDREN STATEMENT OF PRACTICAL TREATMENT

In case of contact with skin, wash immediately with soap and water. Remove and wash contaminated clothing before reuse. Immediately contact physician. In case of contact with eyes, flush promptly and thoroughly with clear water for at least 15 minutes. Immediately contact physician. In case of inhalation, remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Immediately contact physician. In case of ingestion, do NOT induce vomiting. Drink promptly large quantities of water. Avoid alcohol. Immediately contact physician. Never give anything by mouth to an unconscious person. NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate use of gastric lavage. A Material Safety Data Sheet containing more detailed information relative to this product is available upon request.

See side panel for additional precautionary statements.

**DIRECTIONS FOR USE:** It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

### STORAGE AND DISPOSAL

This product is corrosive to mild steel. Do not store or transport in unlined metal containers.

**STORAGE:** Keep container tightly closed. Protect from freezing. Store in a dry place. Do not store at elevated temperatures.

**PESTICIDE DISPOSAL:** Do not contaminate food or feed by storage, disposal or cleaning of equipment. Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL: METAL AND PLASTIC CONTAINERS:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incinerate or burn, if allowed by state and local authorities. If burned, stay out of smoke.

This product aids in the control of objectionable bacteria and fungi in pulp, paper mill and the additive system, and for the preservation of pulp, pigment slurries, alum, emulsions, adhesives, defoamers and polymers. Additions can be made on a continuous or intermittent basis, depending upon the severity of the problem.

**BADLY FOULED SYSTEMS** must be cleaned before treatment is begun.

### FOR SLIME CONTROL

This product should be added directly to the pulp and paper mill systems. Apply at a point in the system where the product will be uniformly mixed.

**INTERMITTENT OR SLUG METHOD- INITIAL DOSE:** When the system is noticeably fouled, add this product at a rate of 0.44 to 1.5 lbs (7 to 23 fluid ounces) per ton (dry basis) of pulp or paper produced. Additions to the additive system should be made directly at the rate of 3.5-14.0 lbs (420 ppm to 1680 ppm) per 1000 gallons. Repeat until control is achieved. **SUBSEQUENT DOSE:** When microbial control is evident, add this product at the rate of 0.44 to 1.5 pounds (7 to 23 fluid ounces) per ton (dry basis) of pulp. Recommendations are based on a maximum storage time of two weeks. Additions to the additive system may be reduced to 3.5 to 7.0 lbs (420 ppm to 840 ppm).

**CONTINUOUS FEED METHOD-INITIAL DOSE:** When the system is noticeably fouled, add this product at the rate of 0.44 to 1.50 lbs (7 to 23 fluid ounces) per ton of pulp or paper produced. Additions to the additive system should be made directly at the rate of 3.5 to 7.0 lb (420 to 840 ppm) per 1000 gallons. Repeat until control is achieved. **SUBSEQUENT DOSE:** When microbial control is evident, add this product at the rate of 0.44 to 1.5 lbs (7 to 23 fluid ounces) per ton of pulp or paper produced. Treat the system as needed to maintain control. Additions to the additive system may be reduced to 3.5 to 5.0 lbs (420 ppm to 600 ppm) per 1000 gallons.

### FOR PRESERVATION

This product should be added directly to the material to be preserved prior to manufacturing into the finished product. The dosage rate will depend upon the material to be preserved and the storage time. Emulsions, add 0.43 - 3.3 lbs of product to each 1000 lbs. of emulsion to provide 425 to 3350 ppm product. Polymer, starch, defoamers, alum, adhesives, paper mill coatings and pigment slurries, add 0.43 - 1.65 lbs. of product to each 1000 lbs. of fluid to provide 420 to 1680 ppm product. The above recommendations are based on a maximum storage time of two weeks.

ACCEPTED

APR 28 1993

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act,  
as amended, for the pesticide  
registered under  
EPA Reg. No. 45017-34

NET WT.: LBS.  
LOT NO.

FOR INDUSTRIAL USE. Technical advice regarding specific site problems is available from BETZ. 808EPA 9304

JACKSONVILLE, FL 32256 BUSINESS: 904-733-7110 EMERGENCY (HEALTH OR ACCIDENT): 1-800-877-1940

45017-34

04/28/1993

1/1