

PM31

45168-6

1/2

Please read instructions on reverse before completing form.

Form Approved. OMB No. 2070-0060. Approval expires 05-31-98



United States
Environmental Protection Agency
Washington, DC 20460

Registration
 Amendment
 Other

OPP Identifier Number
245014

Application for Pesticide - Section I

1. Company/Product Number 45168-6	2. EPA Product Manager M. Johnson	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) VC17m Teflon Antifouling Bottom Paint Red V107E PM# 31		
5. Name and Address of Applicant (Include ZIP Code) Courtaulds Coatings Inc. Agent for Extensor AB 2270 Morris Avenue Union, NJ 07083 <input type="checkbox"/> Check if this is a new address		6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

- Clarification of Directions for Use

NOTIFICATION
SEP 20 1996

Section - III

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes* <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Metal <input type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____		
* Certification must be submitted		If "Yes" Unit Packaging wgt. No. per container	If "Yes" Package wgt. No. per container		
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container		5. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product	
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled			<input type="checkbox"/> Other _____		

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name John P. Pazdera	Title Pesticide Reg. Mgr.	Telephone No. (Include Area Code) 908-964-2288
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)
2. Signature 	3. Title Pesticide Reg. Mgr.	
4. Typed Name John P. Pazdera	5. Date 8/13/96	



PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. While spraying paint or sanding or sand blasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Safety & Health Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Drink promptly a large quantity of water. Avoid alcohol. Get medical attention.

IF ON EYES: Flush eyes with plenty of water. Get medical attention.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARD

This pesticide is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD

Flammable. Keep away from heat and open flame.

FOR CHEMICAL EMERGENCY, SPILL, LEAK, EXPOSURE OR ACCIDENT, CALL TOLL FREE: CHEMTREC 1-800-424-9300 (DAY OR NIGHT) MEDICAL ADVISORY: CONTACT YOUR LOCAL POISON CONTROL CENTER OR CALL 1-800-854-6813



See Side Panel for Additional
Precautionary Statements
0.75 U.S. Quart (0.710 liters)

RED
V107E

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Courtaulds Coatings, Inc. including surface preparation, proper application, and environmental conditions. Therefore, Courtaulds Coatings, Inc. cannot guarantee the product under these conditions. **NOTIFICATION:** THE WARRANTY, LIMITED WARRANTY, WARRANTIES OF FITNESS FOR PARTICULAR PURPOSES, AND WARRANTIES OF MERCHANTABILITY ARE EXCLUDED. COURTAULDS COATINGS, INC. SHALL NOT BE LIABLE FOR DAMAGES, IN ANY CIRCUMSTANCES, BE MATTER OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, BY PURCHASE OR USE OF THIS PRODUCT, BUYING, SELLING, RENTING, AND EXCLUSIVE REMEDY, IF ANY, IS LIMITED TO THE REFUND OF THE PURCHASE PRICE OR REPLACEMENT OF THE PRODUCT OF COURTAULDS COATINGS, INC.'S OPTION.

TEFLON® is a reg. ® of E.I. DuPont de Nemours Company

VC17m TEFLON® ANTI-FOULING BOTTOM PAINT

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PRODUCT DESCRIPTION:

VC17m is a reduced friction, low drag finish antifouling paint for fresh water or cold saltwater. It will prevent buildup of marine fouling organisms such as barnacles, zebra mussels, tereidos and algae. The friction reducing property of VC17m is a function of its Teflon® base and pigmentation system. When applied, VC17m will immediately give a thin super smooth "dip" finish that would traditionally take days of freestone sanding. VC17m no longer contains 1,1,1, Trichloroethane, which means it will dry slower and will improve the flow to give you a smoother finish. The new formula also reduces overspray and dry spray. When it's time to recoat VC17m no sanding is required. Just wash with fresh water, let dry and reapply VC17m. VC17m goes on 8 times thinner than traditional antifouling paint which virtually eliminates film buildup. VC17m can be used on fiberglass, wood and properly primed metal boat hulls (except aluminum), below the waterline. VC17m is recommended for use in fresh water and low fouling saltwater. Do not use VC17m in difficult fouling areas.

TECHNICAL INFORMATION:

Drying Time: 5-10 minutes

Coverage: Approximately 85 sq. ft./quart

Thinner: VC GENERAL THINNER V170

Application Tools: Short nap solvent resistant roller or electric airless spray.

Color:

[V107E] Red
At application - reddish copper bronze. Changes to bright burnt red after several weeks of immersion.

Number of Coats:

Low Fouling Cold Saltwater - Three coats the first season and two coats each season to follow.
Freshwater - Two coats the first season and one coat each season to follow.

SURFACE PREPARATION:

BARE FIBERGLASS (POLYESTER OR VINYLESTER)

It is very important that bare fiberglass be prepared properly to prevent delamination of antifouling paint. Scrub the surface thoroughly with soap and water using a stiff brush, or use INTERLUX ABRASIVE CLEANER YMA600. Flush well with fresh water. Wipe a small area with a clean rag that has been wetted with FIBERGLASS SOLVENT

WASH 202 While the surface is still wet, wipe with a clean dry rag. Continue this process until the entire surface has been cleaned. To be certain all wax and other contaminants have been removed, run water over the surface. If the water beads up or separates, wipe surface again with INTERLUX FIBERGLASS SOLVENT WASH 202. When the water sheets off, all contamination has been removed. Sanding does not remove surface contamination. After the surface has been properly cleaned, mottle sand with 320 grit sandpaper, or apply one coat of VC NO-SAND PRIMER V129. Then apply 2-3 coats of VC17m.

PREVIOUSLY PAINTED SURFACES:

HARD ANTI-FOULING PAINTS - Due to the porosity of hard antifouling paints, it will need to be sanded several times to reach an acceptable surface for application of VC17m. Begin sanding with 80 grit sandpaper and work through the sandpaper grades until a final sanding with 320 grit sandpaper is reached. Wipe the surface with INTERLUX SPECIAL THINNER 216 to remove sanding residue and apply 2-3 coats of VC17m.

SOFT ANTI-FOULING PAINTS - Soft antifouling paints should be removed prior to application of VC17m.

UNDERWATER METALS - Underwater metals must be primed to avoid contact with copper bottom paints. (Not for aluminum). Grind or sand blast to bright metal, clean thoroughly with INTERLUX SPECIAL THINNER 216. Overcoat within one hour with the first coat of VC-TAR. Apply 3-5 additional coats taking care to follow the label directions as to overcoating time. Apply VC17m within 48 hours of the last coat of VC-TAR. If you cannot apply VC-TAR within one hour of grinding or blasting, apply one thin coat of INTERLUX VINYL-LUX® PRIMEWASH 353/354 prior to application of VC-TAR.

BARE WOOD - Sand smooth with 80-100 grit sandpaper, and wipe with INTERLUX SPECIAL THINNER 216. Apply 3 coats of VC17m.

Mixing
Empty the contents of the copper bag (found under the blue lid) into the base. Mix thoroughly. Stir occasionally during application.

Application
VC17m is applied with a short nap roller, 4-6" wide or an electric airless spray gun. For rolling, pour only small amounts of the paint into the steel rolling tray. Roll with a fairly dry roller. Roll quickly and in one direction only. For spraying, make sure that the nozzle tip is not more than 6-8 inches from the hull. VC17m should be applied wet. Do not dry spray. Do not use conventional spray equipment as this may result in dry spray.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.
PESTICIDE DISPOSAL: Open dumping is prohibited. Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.
CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

Interlux For information call 908-686-1300
Or write: Interlux, 2270 Morris Ave., Union, NJ 07083

