

Majestic WATER REPELLENT CLEAR WOOD PRESERVATIVE

One coat protects wood against rot and decay.

ACCEPTED
AUG 19 1981
Under the Federal Insecticide
Fungicide and Rodenticide Act
as amended, this pesticide
is registered under
EPA Reg. No. *

**PRESERVES, PROTECTS
AND BEAUTIFIES YOUR HOME**

Zinc Napthenate	16.32%
Mineral Spirits	66.47%
Polyurethane	7.21%
Additives	10.00%
	100.00%

*Linseed oil alkyl partially
esterified with Linolenic,
Linoleic, Oleic, Palmitic &
Stearic acids, Phthalic Anhydride
& Modified with Toluene
Diisocyanate

POLYURETHANE FORTIFIED

WARNING!
KEEP OUT OF REACH OF CHILDREN
SEE ADDITIONAL PRECAUTIONS
ON BACK OF LABEL

EPA REG NO. 45478-1 EPA EST. NO. 45-478-QH-01

ONE GALLON (3.785 LITERS)

ACTIVE INGREDIENT	
Zinc Naphthenate	16.32%
INERT INGREDIENTS	83.68%
	100.00%
Equivalent to 2.01% Metallic Zinc	
Contains Petroleum Distillates	

CLEAR WOOD PRESERVATIVE

This product preserves, seals and accents the natural wood grain while it retards warping, swelling, shrinking, and checking. Registered with the Environmental Protection Agency, this product combines a fungicide (Zinc Naphthenate) with a superior water repellent.

DIRECTIONS FOR USE:

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER WHICH IS INCONSISTENT WITH ITS LABELING.

WHERE TO USE IT:

This product is recommended for structural lumber, fences, trellises, millwork and other exterior wood surfaces that are exposed to the natural enemies of wood.

TOOLS YOU WILL NEED:

Use brush, roller, pad applicator or spray. Always buy the best quality. You will probably need some drop cloths to protect shrubbery around your home.

SURFACE PREPARATION:

Surface must be clean and dry. This product can be used over previously stained surfaces. Do not apply this product over painted surfaces. Apply liberally by brush, roller, or spray. For extra protection apply a second coat. Do not apply in hot sunlight. If painting is ever desired, surface must be well weathered.

CLEAN OUT TOOLS IN MINERAL SPIRITS.

SPREADING RATE: 200-400 sq. feet (18.5-37.1 sq. meters) depending upon method of application and porosity of the wood.

DRYING TIME: To touch 1 hour. To recoat, within 1 hour. High humidity will cause slower drying.

PRECAUTIONARY STATEMENTS
HAZARD TO HUMAN AND
DOMESTIC ANIMALS

WARNING!

Contains Petroleum Distillates. Harmful if swallowed. Avoid prolonged contact with skin, eyes, or clothing. Wash clothing before reuse. Close container after each use. Use with adequate ventilation. **FIRST AID:** If swallowed do not induce vomiting. Call physician immediately. In case of contact, immediately remove contaminated clothing, and wash skin with soap and water; for eyes flush with water and get medical attention.

STORAGE AND DISPOSAL:
Do not reuse empty container. Wrap container and put in trash collection.

ENVIRONMENTAL HAZARDS:
This product is toxic to fish. Do not apply directly to lakes, streams or ponds. Do not contaminate water by cleaning equipment or disposal of waste. Apply this product only as specified on this label.

PHYSICAL AND
CHEMICAL HAZARDS.

COMBUSTIBLE.
DO NOT USE, POUR, SPILL
OR STORE NEAR HEAT OR
OPEN FLAME.

LIMITED WARRANTY

If this product, when applied according to directions, fails to perform as stated, return the unused portion to your dealer for a full refund or product replacement. This warranty does not include labor costs, incidental expenses, or consequential damages. Some states do not allow the exclusion or limitation of incidental or consequential damages, so these limitations may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Any questions regarding this warranty should be directed to your local dealer, or write Yenkin Majestic Paint Corp., 1920 Leonard Ave., Columbus, OH 43219.

Manufactured by

Yenkin-Majestic
PAINT CORPORATION
COLUMBUS, OHIO 43219