

Supplenergy Pool-trol 20

45597-1
Nov 10 1981

ACTIVE INGREDIENT:

Foly(oxyethylene (dimethyliminio) ethylene-
(dimethyliminio) ethylene dichloride) 20.0%

INERT INGREDIENT 80.0%

This product contains 1.74 lb. of active ingredient per gallon and weighs 8.69 lb. per gallon.

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 45597-1

KEEP OUT OF REACH OF CHILDREN

CAUTION


PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

FIRST AID: If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.



**DIRECTIONS FOR USE
GENERAL CLASSIFICATION**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Supplenergy Pool-trol 20 is used to control the growth of algae in swimming pools, exterior spas, whirlpools, and hot tubs. For maximum effectiveness pools, spas, whirlpools, and hot tubs containing heavy growth of algae should be cleaned prior to using Supplenergy Pool-trol 20.

For pools having just visible algae growth add an initial dose of 36.5 to 56 fluid ounces of Supplenergy Pool-trol 20 per 10,000 gallons of water and remove settled algae debris by cleaning. For treatment of a freshly cleaned and filled pool add initially 20 to 36.5 fluid ounces of Supplenergy Pool-trol 20 per 10,000 gallons of water. Subsequent additions of 6.5 to 13 fluid ounces of Supplenergy Pool-trol 20 per 10,000 gallons of water should be made every 5 to 7 days after initial treatment for maintenance.

Spas, whirlpools, or hot tubs having just visible algae growth require an initial dose of 4 to 6 fluid ounces of Supplenergy Pool-trol 20 per 1000 gallons of water. For treatment of a freshly cleaned and filled spa, whirlpool, or hot tub, add initially 2 to 4 fluid ounces of Supplenergy Pool-trol 20 per 1,000 gallons of water. Subsequent additions of 1 to 2 fluid ounces of Supplenergy Pool-trol 20 should be made every 5 to 7 days after initial treatment for maintenance.

Supplenergy Pool-trol 20 is compatible with those chemicals normally used to treat pools and spas and is effective at both acid and alkaline pH. Supplenergy Pool-trol 20 can be used in pools and spas treated with chlorine chemicals and may reduce the amount of those chemicals normally required. However, do not mix Supplenergy Pool-trol 20 with concentrated dry or liquid chlorine products.

STORAGE & DISPOSAL: Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment. Rinsate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.

METAL CONTAINERS: Triple rinse and offer for recycling, reconditioning, or disposal in an approved landfill or bury in a safe place.

PLASTIC CONTAINERS: Do not reuse empty container. Triple rinse and incinerate or dispose of in an approved landfill or bury in safe place.

Manufactured by:
Stitt Energy Systems, Inc.
1301 Hwy. 71 South
Rogers, Arkansas 72756

EPA REG. NO. 45597-1

EPA EST. NO. _____

19

NET CONTENTS _____