

45638-3 PM 21 1065

US ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (TS-767) WASHINGTON, DC 20460	EPA REGISTRATION NO. 45638-3	DATE OF ISSUANCE MAY 5 1986
	TERM OF ISSUANCE	
	NAME OF PESTICIDE PRODUCT Maxum Deck Stain Formula	

NOTICE OF PESTICIDE:  REGISTRATION  
 REREGISTRATION  
 (Under the Federal Insecticide, Fungicide,  
 and Rodenticide Act, as amended)

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

Premier Coatings, Inc. 2250 Arthur Avenue Elk Grove Village, IL 60007	161 18 162323 1
-----------------------------------------------------------------------------	--------------------------

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA section 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
2. Add the phrase "EPA Registration No. 45638-3" to your label before you release the product for shipment.
3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Henry M. Jacoby  
 Product Manager (21)  
 Fungicide-Herbicide Branch  
 Registration Division (TS-767C)

Enclosures

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL <i>Henry M. Jacoby</i>	DATE 5/5/86
-----------------------------------------------------------	----------------

PROTECTION FOR

# MAXI

EXT

KEEP OUT OF REACH  
OF CHILDREN

**WARNING:**

See side panel for additional  
precautionary statements

# DECK

## STAIN FORMULA

Semi-transparent En  
Stain and Wood Pres  
Decks and Other Wo  
Repels Water

Active Ingredient:	
3-Iodo-2-propynylbutyl-	
carbamate	0.52%
Inert Ingredients:	99.48%
TOTAL:	100.00%

Cleans-up with Water

CLEAR BASE

M-4001

120 OUNCES = 3.548

EPA Reg. No. 45638

MEETS FEDERAL SPECIFICATION  
TTW-572b, 3.7 FOR WATER  
REPELLENCY

(FRONT PANEL)

MAY

Under the F  
Fungicide, an  
as amended,  
registered un

456



# DECK STAIN FORMULA

4 of 5

SEMI-TRANSPARENT EMULSIFIED OIL STAIN AND WOOD PRESERVATIVE FOR  
DECKS AND NEW WOOD/REPELS WATER

Guaranteed - For New or Old Wood - Excellent on Decks and other Horizontal Surfaces Exposed to the Sun, Rain and Snow - Accents the Woodgrain and Texture - Allows the Woodgrain to Show Through - Resists Warping and Swelling - Protects Against Mildew and Woodrot - Easy to Apply - Water Cleanup - Dries to Touch in 4 to 6 Hours - Recoat when Dry - Will not Peel, Crack or Blister.

## DIRECTIONS FOR USE


It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Note to User: This Deck Stain formula contains a mildewcide which is designed to resist mildew growth on the dried finish. This powerful mildewcide will not mildew-proof your home nor completely prevent or destroy mildew.

Deck Stain is for exterior use only and is recommended for shingles (not asbestos), shakes, clapboards, smooth or rough-cut wood siding, decks, porches, railings, outdoor furniture, structural support timbers, flat beds, cold frames and greenhouses. The product is not recommended for use on primed or previously painted surfaces nor for wood used for ground, food, feed or potable water contact. Cover desirable plants and shrubs to avoid possible injury. This product can be used where dairy and farm animals may come in contact with the treated wood.

Surface Preparation: For new decks, railings and other unfinished wood surfaces: the surface must be clean and free of mildew, grease, oil, dirt and loose particles. Test for mildew by applying a solution of household bleach and water to any discolored area; if the discoloration dissolves and rinses away, mildew is present and the entire area to be stained should be thoroughly washed and rinsed with a solution of one part household bleach and three parts water. Be certain to wear protective gloves and use caution in application as bleach can burn unprotected skin. Protect plant life around the structure. Rinse and repeat operation if all discoloration is not removed. Hose down the surface and allow all surface water to dry. Surface to be stained may be damp but not wet. New Treated Lumber: Pressure treated wood will not receive this stain until exposed for at least six months in exposed areas and twelve months in sheltered areas. Delay staining until penetration can occur. Previously Stained Surfaces: Remove all loose and peeling films. Scuff up areas adjacent to any bare traffic areas to enhance color uniformity. Select a color deeper than the previous stain to enhance color uniformity. Test for mildew and treat as recommended above.

Color Selection: Different woods take stain differently. To ensure proper color selection it is recommended that a small sample area be stained before proceeding on the major area. Recoating previously stained areas requires a more opaque color and a more liberal application.



PAGE 3

Application: Mix thoroughly by stirring with a paddle. Do not shake as this will cause bubbling. Stir occasionally during use or to keep color uniform. Avoid applying in direct hot sunlight or when rain may occur within twelve hours. On vertical siding start at the top with several boards and apply continuously to the bottom. On horizontal decks or siding start on one or two boards and apply continuously across the surface or until a natural break in the board occurs. This minimizes the dangers of lapping. Apply a uniform coat with a synthetic brush, stain applicator or spray gun. Maintain a wet edge and apply product from the dry to wet, spreading uniformly.

Cleanup: Clean spills or splatters immediately with water. Clean tools with soap and warm water. Stubborn oil residue which has dried during the application may require a stronger solvent for removal. Thinning: Water reducible. Do not exceed one pint per gallon. Drying Time: Allow 24 hours before foot traffic. Coverage: 150 to 300 square feet per gallon depending on texture and porosity of wood.

#### STORAGE AND DISPOSAL

STORAGE: Do not store near excessive heat, or near food or feed products.

DISPOSAL: Do not reuse container. Rinse thoroughly before discarding in trash. Securely wrap original container in several layers of newspaper and discard in trash.

Guarantee: If, after proper application, MAXIM DECK STAIN FORMULA should crack, peel or blister, replacement gallon will be furnished free of charge or a refund of the product cost made at the manufacturer's option. Cracking, peeling or blistering caused by a breakdown of a previous coating are not covered by this Guarantee. Labor cost to apply any material and any responsibility to consequential damages are excluded from this Guarantee.

For more information consult your MAXIM dealer.

Prender Coatings, Inc. Elk Grove Village, IL 60007

