

**PHYSICAL HAZARDS**  
Keep away from heat and open flames.

**Combustible** . . .

**PRECAUTIONARY STATEMENTS**

**WARNING**

**HAZARDS TO HUMANS  
AND DOMESTIC ANIMALS**

Harmful or fatal if swallowed. Causes eye irritation. Do not get in eyes. Use with adequate ventilation. Avoid contact with skin and breathing of vapor or spray mist. Close container after each use. Do not transfer contents to bottles or other unlabeled containers. Wear goggles or face shield and rubber gloves when handling. Use protective breathing mask and protective clothing when spraying or sanding.

When used in enclosed areas, while spraying paint, or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

**FIRST AID:** If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention. If in eyes: Flush with plenty of soap and water. Get medical attention. If on skin: Wash with plenty of soap and water. Get medical attention. If inhaled: Remove victim to fresh air. If not breathing, give artificial respiration preferably mouth-to-mouth. Get medical attention.

**Use Only With Adequate Ventilation**

**KEEP OUT OF REACH OF CHILDREN**

**WARNING**

See side panel for additional precautionary statements.

**ACCEPTED**  
SEP 28 1982

Under the Federal Insecticide  
Fungicide and Rodenticide  
Act as amended by  
Public Law 95-603  
EPA Reg. No. 45726-1

**FORMULA**

**ANTIFOULING BLACK**

**AN EPOXY COATING  
for  
FIBERGLASS AND WOOD**

**EPA REG. NO. 45726-1**

Active Ingredient	% BY WT
Cuprous Oxide	54.18
Inert Ingredients	45.82
Elemental Copper	100.00
	48.12

**Contains Petroleum Distillate**  
**SPECIALTY MARINE COATINGS**  
209 Ardmore Road  
FAYETTEVILLE, TENNESSEE 37334  
(615) 433-1571

**One U.S. Quart**

This m  
not ap  
ing of  
Do not  
during  
Dispos  
appro

**BEST DOCUMENT AVAILABLE**

#### STORAGE AND DISPOSAL

**STORAGE**--cool and dry and keep away from flame.  
**DISPOSAL**--Triple rinse (or equivalent) and offer for recycling or reconditioning, or dispose of in a sanitary landfill, or by other approved State and local procedures.

Pesticide, spray mixture, or rinse water that cannot be used according to label instructions must be disposed of according to applicable Federal, state, or local procedures.

#### ENVIRONMENTAL HAZARDS

Do not contaminate water by cleaning of equipment or disposal of wastes.

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

#### INGREDIENTS FOR FORMULA 7

Formula 7 contains cuprous oxide, aliphatic hydrocarbons, ethylene glycol monoethyl ether acetate, epoxy resin, lamp black, graphite, zinc oxide, talc, and miscellaneous driers and additives.

#### PREPARATION FOR RACING FINISH by

##### SANDING FORMULA 7

Formula 7 will provide a durable smooth antifouling racing finish. Start by using wet dry sand paper (220 grit). Use some liquid detergent in the water to keep the paper open and work up to 800 grit wet dry. Buffing or burnishing may also be done for a smoother finish.

#### Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For salt and fresh water use.

For application to vessels subject to attack by barnacles, algae, tube worms, and other fouling organisms.

For wood and fiberglass boat:

Formula 7 may be applied by brush, rolling, or spraying. Allow 6 hours to overnight dry between each coat.

Reduce with mineral spirits to desired consistency for application of a smooth coat. Apply two to three coats. One (1) quart will cover about 150 square feet at 1.0 mils.

Launch within 48 hours after application of final coat. Paint should be dry to touch before immersion.

#### -FOR FIBERGLASS-

Formula #7 Antifouling Paint may be applied directly to well sanded and cleaned fiberglass without use of a primer. Sanding of fiberglass for good adhesion is required.

#### -WOODEN BOTTOMS (UNFINISHED WOOD)-

Reduce with mineral spirits for application of first coat. Apply second and third coats unreduced.

#### WOOD AND FIBERGLASS BOTTOMS (OLD WORK)

Remove all traces of loose paint, dirt, grease, etc. Sand the existing paint film well and apply two coats of Formula #7 Antifouling Paint.