

PHYSICAL HAZARDS
Keep away from heat and open flame.

FLAMMABLE

PRECAUTIONARY STATEMENTS

WARNING

**HAZARDS TO HUMANS
AND DOMESTIC ANIMALS**

Harmful or fatal if swallowed. Causes eye irritation. Do not get in eyes. Use with adequate ventilation. Avoid contact with skin and breathing of vapor or spray mist. Close container after each use. Do not transfer contents to bottles or other unlabeled containers. Wear goggles or face shield and rubber gloves when handling. Use protective breathing mask and protective clothing when spraying or sanding.

When used in enclosed areas, while spraying paint, or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

FIRST AID: If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention. If in eyes: Flush with plenty of soap and water. Get medical attention. If on skin: Wash with plenty of soap and water. Get medical attention. If inhaled: Remove victim to fresh air. If not breathing, give artificial respiration preferably mouth-to-mouth. Get medical attention.

Use Only With Adequate Ventilation

KEEP OUT OF REACH OF CHILDREN

WARNING

See side panel for additional precautionary statements.

ACCEPTED
8/23/82
U.S. Environmental Protection Agency
Federal Insecticide, Fungicide, and Rodenticide Act
EPA Reg. No. 45726-2

FORMULA

15

ANTIFOULING RED

A VINYL COATING

for

FIBERGLASS AND WOOD

EPA REG. NO. 45726-2

Active Ingredient	% BY WT
Citrous Oxide	55.70
Inert Ingredients	44.30
Elemental Copper	100.00
	48.47

Contains Petroleum Distillate

SPECIALTY MARINE COATINGS

209 Ardmore Road
FAYETTEVILLE, TENNESSEE 37334
(615) 433-1671

One U.S. Quart

This is not an...
ing of...
Do not...
during...
Dispos...
appro...

STORAGE AND DISPOSAL

STORAGE--cool and dry and keep away from flame.
DISPOSAL--Triple rinse (or equivalent) and offer for recycling or reconditioning, or dispose of in a sanitary landfill, or by other approved State and local procedures.

Pesticide, spray mixture, or rinse water that cannot be used according to label instructions must be disposed of according to applicable Federal, state, or local procedures.

ENVIRONMENTAL HAZARDS

Do not contaminate water by cleaning of equipment or disposal of wastes.

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

INGREDIENTS FOR FORMULA 15

Formula 15 contains cuprous oxide, rosin, iron oxide, methyl isobutyl ketone, xylol, vinyl resin, plasticizer, and suspension agent.

WARNING
CONTAINS XYLOL AND
METHYL ISOBUTYL KETONE
Harmful or Fatal if Swallowed
VAPOR HARMFUL

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For salt and fresh water use.

For application to vessels subject to attack by barnacles, algae, tube worms, and other fouling organisms.

For wood and fiberglass boats.

Formula 15 may be applied by brush, rolling, or spraying. Allow 6 hours to overnight dry between each coat.

Reduce with a good grade lacquer thinner to desired consistency for application of a smooth coat. Apply two to three coats. One (1) quart will cover about 230 square feet at 1.0 mils.

Launch within 48 hours after application of final coat. Paint should be dry to touch before immersion.

-FOR FIBERGLASS-

Formula 15 Antifouling Paint may be applied directly to well sanded and cleaned fiberglass without use of a primer. Sanding of fiberglass for good adhesion is required.

-WOODEN BOTTOMS (UNFINISHED WOOD)-

Reduce with mineral spirits for application of first coat. Apply second and third coats unreduced.

WOOD AND FIBERGLASS BOTTOMS (OLD WORK)

Remove all traces of loose paint, dirt, grease, etc. Sand the existing paint film well and apply two coats of Formula 15 Antifouling Paint.

BEST DOCUMENT AVAILABLE