

PRECAUTIONARY STATEMENTS**PHYSICAL HAZARDS**

Keep away from heat and open flame

Combustible**HAZARDS TO HUMANS AND DOMESTIC****ANIMALS — WARNING**

Harmful or fatal if swallowed. Causes eye irritation. Do not get in eyes. Use with adequate ventilation. Avoid contact with skin and breathing of vapor or spray mist. Close container after each use. Do not transfer contents to bottles or other unlabeled containers. Wear goggles or face shield and rubber gloves when handling. Use protective breathing mask and protective clothing when spraying or sanding.

When used in enclosed areas while spraying paint or sanding boat surface, wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

FIRST AID If swallowed, Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention. If in eyes, flush with plenty of water. Get medical attention. If on skin, wash with plenty of soap and water. Get medical attention. If inhaled, Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. Get medical attention.

Use Only With Adequate Ventilation**KEEP OUT OF REACH OF CHILDREN
WARNING**

See side panel for additional precautionary statements

FORMULA**15
ANTIFOULING RED
VINYL COATING**

for
FIBERGLASS AND WOOD
EPA REG. NO. 45725-2-106-2

Active Ingredient	BY WT
Cuprous Oxide	55.70
Inert Ingredients	44.30
	100.00
Elemental Copper	49.47

Contains Petroleum Distillate

A non-photoreactive, reactive solvent blend

SPECIALTY MARINE COATINGS

209 - *damore Road*
FAYETTEVILLE, TENNESSEE 37334
(615) 433-1671
One U.S. Quart

STORAGE AND DISPOSAL

STORAGE: Cool and dry and keep away from flame.
DISPOSAL: Triple rinse (or equivalent) and offer for recycling or reconditioning or dispose of in a sanitary land fill or by other approved State and local procedures.

Pesticide spray mixture, or rinseate that cannot be used according to label instructions must be disposed of according to applicable federal, state, or local procedures.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Deposit of paint debris in an approved landfill.

INGREDIENTS FOR FORMULA 15

Formula 15 contains cuprous oxide, rosin, iron oxide, methyl isobutyl ketone, xylol, vinyl resin, plasticizer, and suspension agent.

WARNING

**CONTAINS XYLOL AND
METHYL ISOBUTYL KETONE**
Harmful or Fatal if Swallowed
VAPOR HARMFUL

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For Salt and Fresh Water Use

For application to vessels subject to attack by barnacles, algae, tube worms, and other fouling organisms.

For Wood and Fiberglass Boats

Formula 15 may be applied by brush, rolling, or spraying. Allow 6 hours to overnight dry between each coat.

Reduce with a good grade lacquer thinner to desired consistency for application of a smooth coat. Apply two to three coats. One (1) quart will cover about 230 square feet at 1.0 mils.

Launch within 48 hours after application of final coat. Paint should be dry to touch before immersion.

FOR FIBERGLASS

Formula 15 Antifouling Paint may be applied directly to well sanded and cleaned fiberglass without use of a primer. Sanding of fiberglass for good adhesion is required.

WOODEN BOTTOMS (UNFINISHED WOOD)

Reduce with mineral spirits for application of first coat. Apply second and third coats unreduced.

**WOOD AND FIBERGLASS BOTTOMS
(OLD WORK)**

Remove all traces of loose paint, dirt, grease, etc. Sand the existing paint film well and apply two coats of Formula 15 Antifouling Paint.

BEST AVAILABLE COPY