

PRECAUTIONARY STATEMENTS:

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage. May be fatal if inhaled. Harmful if swallowed or absorbed through skin. Do not get in eyes, on skin, or on clothing. Do not breathe dust, vapor or spray mist. Wear goggles, face shield or safety glasses. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms.

NOTE: Buyer assumes all responsibility for safety and use not in accordance with directions.

PHYSICAL OR CHEMICAL HAZARDS: STRONG OXIDIZING AGENT Do not mix with other chemicals. Never add water to product. Always add product to large quantities of water. Use clean dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire or explosion. Contamination with moisture, organic matter or other chemicals will start a chemical reaction and generate heat, hazardous gas, possible fire and explosion. In case of contamination or decomposition, do not reseal container. If possible, isolate container in open air or well ventilated area. Flood area with large volumes of water.

STORAGE: Keep product dry in a tightly closed container when not in use. Store in a cool, dry, well-ventilated area away from heat or open flames. Do not reuse empty container.

DISPOSAL: If empty. Do not reuse this container. Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency or 1-800-CLEANUP (800-253-2687) for disposal instructions. Never place unused product down any indoor or outdoor drain.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. These wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Manufactured by:
Suncoast Chemicals Company
14480 62nd St. N.
Clearwater, FL 33760

In case of emergency call
1-800-255-3924

Item No. 00920967



5 7621519209

ACCEPTED
AUG 12 2003
Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 46043-15

suncoast
chemicals co.
SWIMMING POOL CHLORINATING
SHOCK
FAST DISSOLVING FOR
VINYL OR CONCRETE POOLS

SUPERCHLORINATOR AND SHOCK TREATMENT FOR SWIMMING POOLS

ACTIVE INGREDIENT:
SODIUM DICHLORO-S-TRIAZINETRIONE DIHYDRATE.....99%
INERT INGREDIENTS.....1%
TOTAL.....100%

KEEP OUT OF REACH OF CHILDREN
DANGER

See back panel for additional precautionary statements.

FIRST AID

- IF SWALLOWED:** Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person. Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
- IF ON SKIN:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
- IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth. Call a poison control center or doctor for further treatment advice.
- IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

HOTLINE NUMBER:

Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-255-3924 for emergency medical treatment information.


NOTE TO PHYSICIAN:

Probable mucosal damage may contraindicate the use of gastric lavage.

EPA Registration No. 46043-15

EPA Establishment No. 46043-FL-1

NET WT. 10 OZS.



WHY TO USE THIS PRODUCT: This product contains a completely soluble active ingredient to destroy non-filterable swimmer wastes in vinyl-lined, colored plaster or fiberglass pools. When used as directed, this product restores water clarity, kills germs, helps kill algae, and destroys unpleasant odors. For white plaster pools, use Shock Treatment and to shock your pool and swim in 15 minutes use Shock and Swim.

IMPORTANT NOTES: 1. Mixture of this product with any other shock product (in dry form or during pre-dissolving) prior to adding to pool could result in fire and/or explosion. 2. When using other products, as outlined in directions for this product, always follow label directions for those products. 3. Damage may be caused by direct contact of this product with pool surfaces or materials such as colored plaster, vinyl, wood or fiberglass. 4. This product may promote metal stains on pool surfaces. Always check water for metal content and if present, remove metals with a stain & scale inhibitor prior to the addition of this product. 5. Sunlight, rainfall, temperature, number of swimmers and frequency of pool use affect the rate of chlorine loss. Adjust cleaning and chemical maintenance accordingly. To eliminate harmful algae and microorganisms, superchlorinate pool every 2-4 weeks.

DIRECTIONS FOR USE: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

BEFORE YOU BEGIN: 1. Ensure all pool equipment is working properly. Backwash filter following manufacturer's directions. 2. Check water pH, alkalinity and calcium hardness with a test kit. Adjust pH to 7.2 - 7.6 by adding pH Minus to lower pH, or by adding pH Plus to raise pH. Adjust alkalinity to 80 - 125 ppm for plaster pools, 125 - 150 for vinyl or fiberglass pools by adding Total Alkalinity. Adjust calcium hardness to 200 - 275 ppm for plaster pools, 175 - 225 for vinyl or fiberglass pool by adding Calcium Hardness. Be sure to follow label directions.

NOW USE THIS PRODUCT:

For Start-Up Initial Shocking: 1. With pump running and pool not in use, broadcast 1 pound of this product per 10,000 gallons of water directly into the pool in the deep end of the pool. To prevent possible damage to pool surface, use a pool brush to disperse any granules that may have settled at the bottom of the pool. 2. Repeat procedure after 24 hours, if needed, to establish a chlorine residual of 1-3 ppm as determined by a test kit.

For Routine Shocking: 1. Every two weeks with pump running and pool not in use, broadcast 1 pound of this product per 10,000 gallons of water directly into the pool in the deep end of the pool. To prevent possible damage to pool surface, use a pool brush to disperse any granules that may have settled at the bottom of the pool.

Reentry into treated swimming pool is prohibited above levels of 3 ppm chlorine due to the risk of bodily injury.

46043-15
8/12/2003
Page 1 of 1