

Biotreat 200

46152-3

ACTIVE INGREDIENT

Polyoxyethylene (dimethylamino) ethylene
(dimethylamino) ethylene dichloride

100%

INERT INGREDIENT

900%

This product contains 0.85 lb. of active ingredient per gallon and weighs 8.49 lb. per gallon.

KEEP OUT OF REACH OF CHILDREN

CAUTION

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

FIRST AID: If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.

EPA REG. NO. 46152-3
EPA EST. NO. 44106

For information on the use of this product, contact your distributor or the manufacturer.

Biotreat 200 is used to control bacteria in industrial air washing systems. It is used to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 6.13 to 15.32 fluid ounces of Biotreat 200 per 1000 gallons of water to provide a concentration of 48 to 120 parts per million of Biotreat 200 based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 1.53 to 15.32 fluid ounces of Biotreat 200 per 1000 gallons of water (12 to 120 parts per million of Biotreat 200) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleed-off and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

Biotreat 200 is used to control bacteria in industrial air washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 24.7 to 41.2 fluid ounces of Biotreat 200 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 16.9 to 41.2 fluid ounces of Biotreat 200 per 1000 gallons of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleed-off and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection trays of the airwash system.

STORAGE & DISPOSAL Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment. Rinsate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.

METAL CONTAINERS Triple rinse and offer for recycling, reconditioning, or disposal in an approved landfill or bury in a safe place.

PLASTIC CONTAINERS Do not reuse empty container. Triple rinse and incinerate or dispose of in an approved landfill or bury in safe place.

Manufactured by

W. T. Chemicals

2612 West St. James Parkway

Cleveland Heights, OH 44106

EPA REG NO 46152 3

EPA EST NO

NET CONTENTS