

ENVIRONMENTAL PROTECTION AGENCY
OFFICE OF PESTICIDES PROGRAMS
REGISTRATION DIVISION (TS 767)
WASHINGTON, DC 20460

EPA REGISTRATION NO.
46183-1

DATE OF ISSUANCE
MAY 30 1995

NOTICE OF PESTICIDE: REGISTRATION
 REREGISTRATION
*(Under the Federal Insecticide, Fungicide
and Rodenticide Act, as amended)*

TERM OF ISSUANCE
NAME OF PESTICIDE PRODUCT
Sani-Way 6

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

Safeway Industries, Inc.
3372 N. Holton Street
Milwaukee, WI 53212

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

Based on your response to the Reregistration Eligibility Document, EPA has reregistered the above named product subject to the comments recorded in the succeeding paragraph. This action is taken under the authority of section 4(g)(2)(C) of the Federal Insecticide, Fungicide, and Rodenticide Act, as amended. Reregistration under this section does not eliminate the need for continual reassessment of pesticides. EPA may require submission of data at any time to maintain the registration of your product.

Make the following labeling changes before you release the product for shipment:

1. Revise the "Environmental Hazards" statement on the label to read:

"This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL _____ DATE _____

143


Resubmit a revised Confidential Statement of Formula and indicate the suppliers of Sodium Hypochlorite. The suppliers names should not be listed on separate sheet of paper.

A stamped copy of the product label is enclosed for your records. Submit one copy of the final printed label before releasing the product in channels of trade with the revised labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.



Ruth G. Douglas
Product Manager (32)
Antimicrobial Program Branch
Registration Division (7505C)



SANI-WAY 6

Active Ingredient:

Sodium Hypochlorite 6.4%
 Inert Ingredients 93.6%
 100.0%

**KEEP OUT OF REACH OF CHILDREN
 DANGER**

**STATEMENT OF PRACTICAL
 TREATMENT (FIRST AID)**

If on skin, wash with plenty of soap and water for at least 15 minutes. If in eyes, flush immediately with large quantities of water for at least 30 minutes. If swallowed, drink large quantities of water. Do not induce vomiting. Avoid alcohol. Call a physician or poison control center immediately.

**SEE RIGHT PANEL FOR ADDITIONAL
 PRECAUTIONARY STATEMENTS**

EPA Registration No. 46183-1
 EPA Establishment No. 46183-WI-1

**MANUFACTURED BY:
 SAFEWAY INDUSTRIES, INC.
 3372 N. HOLTON STREET
 MILWAUKEE, WI 53212**

NET CONTENTS:
 5 GALLONS (18.93 L.)
 15 GALLONS (56.98L.)
 30 GALLONS (113.56 L.)
 55 GALLONS (208.20 L.)



PC S70S

DIRECTION FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

SANITIZATION OF NONPOROUS FOOD CONTACT SURFACES: Porous surfaces should be rinsed with 600 ppm solution. **DO NOT RINSE** after use of 200 ppm solution.

RINSE METHOD: Prepare a sanitizing solution by thoroughly mixing 12 oz. of this product with 10 gallons of water to provide approximately 600 ppm available chlorine. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for at least 2 minutes. Prepare a 200 ppm solution with 10 gallons of water. Prior to using equipment rinse/immerse all surfaces with a 200 ppm available chlorine solution. Do not rinse equipment with water.

IMMERSION METHOD: Prepare a sanitizing solution by thoroughly mixing, in an immersion tank, 12 oz. of this product with 10 gallons of water to provide approximately 600 ppm available chlorine. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. Prepare a 200 ppm solution with 10 gallons of water. Prior to using equipment rinse/immerse all surfaces with a 200 ppm available chlorine solution. Do not rinse equipment with water.

SPRAY/FOG METHOD: Pre-clean all surfaces after use. Use a 200 ppm available chlorine solution to control bacteria, mold or fungi and a 600 ppm solution of sufficient size by thoroughly mixing the product in a ratio of 4 ounces product with 10 gallons of water. Prepare a 600 ppm solution by thoroughly mixing 10 gallons of water. Use spray or fogging equipment which can resist hypochlorite solutions. Always empty and rinse spray/fog equipment with potable water, allowing excess sanitizer to drain. Vacate area for at least 2 hours. Prior to using equipment, rinse all surfaces treated with a 600 ppm solution with a 200 ppm solution with 10 gallons of water.

DISINFECTION AND SLIME AND ALGAE CONTROL IN SWIMMING POOLS, HOT TUBS, SPAS, OR DECORATIVE FOUNTAINS: Mix 20 ounces of this product with 100 gallons of water to obtain a free available chlorine concentration of 5 ppm, as determined by a suitable test kit.

SPA/HOT-TUBS: Apply 10 oz. of product per 1,000 gallons of water to obtain a free available chlorine concentration of 5 ppm, as determined by a suitable test kit.

SWIMMING POOL WATER DISINFECTION: For a new pool or spring start-up, superchlorinate with 52 to 104 oz. of product for each 5,000 gallons of water to yield 5 to 10 ppm available chlorine residual. Adjust and maintain pool water pH to between 7.2 to 7.6. Adjust and maintain the alkalinity of the pool to between 50 to 100 ppm. To maintain the pool, add manually or by a feeder device: 1 oz. of this product for each 5,000 gallons of water to yield an available chlorine residual between 0.5 to 1.0 ppm. Test the pH, available chlorine residual and alkalinity of the water frequently with appropriate test kits. Frequency of testing depends on the number of swimmers. Every 7 days, or as necessary, superchlorinate the pool with 52 to 104 oz. of product for each 5,000 gallons of water to yield 5 to 10 ppm of available chlorine with a test kit. Do not reenter pool until the chlorine residual is between 1.0 to 3.0 ppm. At the end of the swimming pool season or when water is to be drained from the pool, chlorine must be allowed to dissipate from treated pool water before discharge.

WINTERIZING POOLS: While water is still clear & clean, apply 8 oz. of product per 1,000 gallons, while filter is running, to obtain a 3 ppm available chlorine residual. Prepare heater, filter and heater components for winter by following manufacturers' instructions.

NOTE: This product degrades with age. Use a suitable free available chlorine residual test kit and increase dosage, as necessary, or obtain the required chlorine residual.

MIXING AND DILUTION PROPORTIONS TABLE

200 ppm available chlorine solution	mix 2 fluid ounces to 5 gallons of water
600 ppm available chlorine solution	mix 8 fluid ounces to 5 gallons of water
5,000 ppm available chlorine solution	mix 45 fluid ounces to 4 1/2 gallons of water
10,000 ppm available chlorine solution	mix 90 fluid ounces to 4 1/2 gallons of water

STORAGE AND DISPOSAL

Store in a cool dry place, away from direct sunlight. In case of spill, flood area with large quantities of water. Rinse empty containers thoroughly with water. Empty containers should be placed in a trash collection. Product or container rinsate that cannot be used should be diluted with water and disposed of in a sanitary sewer or disposal, or by the use of this product.

HAZARDS TO HUMANS AND DOMESTIC ANIMALS PRECAUTIONARY STATEMENTS DANGER

CORROSIVE: May cause severe skin irritation or chemical burns to skin. Causes eye damage. Do not get in eyes, on skin, or on clothing. Wear goggles or eye protection. Vacate poorly ventilated areas as soon as possible. Do not return until odors have dissipated.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters. Do not discharge effluent containing this product into sewer systems without previously notifying the sewage treatment plant, local health department, or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS

STRONG OXIDIZING AGENT

Mix only with water according to these label directions. Mixing this product with gross filth such as feces, urine, etc. or with ammonia, acids, detergents, or other chemicals may produce a highly explosive mixture.

SANITIZATION OF NONPOROUS FOOD CONTACT SURFACES

DO NOT RINSE after use of 200 ppm solution.

RINSE METHOD: A solution of 100 ppm available chlorine may be used in the sanitizing solution if a chlorine test kit is available. Solutions containing an available chlorine residual of 100 ppm must be tested and adjusted periodically to ensure that the available chlorine does not drop below 50 ppm. Prepare a 100 ppm sanitizing solution by thoroughly mixing 4 oz. of this product with 10 gallons of water to provide approximately 200 ppm available chlorine. Clean equipment surfaces in the normal manner. Prior to use, rinse all surfaces thoroughly with the sanitizing solution, maintaining contact with the sanitizer for at least 2 minutes. Prepare a 200 ppm solution with 10 gallons of water. Prior to using equipment, rinse all surfaces treated with a 200 ppm solution with a 200 ppm solution with 10 gallons of water. Do not rinse equipment with water.

IMMERSION METHOD: A solution of 100 ppm available chlorine may be used in the sanitizing solution if a chlorine test kit is available. Solutions containing an available chlorine residual of 100 ppm must be tested and adjusted periodically to ensure that the available chlorine does not drop below 50 ppm. Prepare a 100 ppm sanitizing solution by thoroughly mixing 4 oz. of this product with 10 gallons of water to provide approximately 200 ppm available chlorine. Clean equipment surfaces in the normal manner. Prior to use, immerse equipment in the sanitizing solution for at least 2 minutes and allow the sanitizer to drain. Prepare a 200 ppm solution with 10 gallons of water. Prior to using equipment, rinse all surfaces treated with a 200 ppm solution with a 200 ppm solution with 10 gallons of water. Do not rinse equipment with water.

SPRAY/FOG METHOD: Pre-clean all surfaces after use. Use a 200 ppm available chlorine solution to control bacteria, mold or fungi and a 600 ppm solution of sufficient size by thoroughly mixing the product in a ratio of 4 ounces product with 10 gallons of water. Prepare a 600 ppm solution by thoroughly mixing 10 gallons of water. Use spray or fogging equipment which can resist hypochlorite solutions. Always empty and rinse spray/fog equipment with potable water after use, allowing excess sanitizer to drain. Vacate area for at least 2 hours. Prior to using equipment, rinse all surfaces treated with a 600 ppm solution with a 200 ppm solution with 10 gallons of water.

Sanitizers used in automated systems may be used for general cleaning but may not be re-used for sanitizing purposes.

FLOWPRESSURE METHOD: Disassemble equipment and thoroughly clean after use. Assemble equipment in operating position prior to use. Prepare a volume equal to 110% of volume capacity of the equipment by mixing the product in a ratio of 4 oz. product with 10 gallons of water. Pump solution through the system until completely filled with the sanitizer and all air is removed from the system. Close drain valves and hold under pressure for at least 2 minutes to ensure contact with all internal surfaces. Repeat entire cleaning/sanitizing process if effluent contains less than 50 ppm available chlorine.

CLEAN-IN-PLACE METHOD: Thoroughly clean equipment after use. Prepare a volume of a 200 ppm available chlorine sanitizing solution equal to 110% of volume capacity of the equipment by mixing the product in a ratio of 4 oz. product with 10 gallons of water. Pump solution through the system until full flow is obtained at all extremities. The system is completely filled with the sanitizer. Close drain valves and hold under pressure for at least 10 minutes to ensure contact with all internal surfaces. Remove some cleaning solution from drain valve and test with a chlorine test kit. Repeat entire cleaning/sanitizing process if effluent contains less than 50 ppm available chlorine. Do not rinse system with potable water prior to use.

SPRAY/FOG METHOD: Pre-clean all surfaces after use. Use a 200 ppm available chlorine solution to control bacteria, mold or fungi and a 600 ppm solution of sufficient size by thoroughly mixing the product in a ratio of 4 ounces product with 10 gallons of water. Prepare a 600 ppm solution by thoroughly mixing 10 gallons of water. Use spray or fogging equipment which can resist hypochlorite solutions. Always empty and rinse spray/fog equipment with potable water after use, allowing excess sanitizer to drain. Vacate area for at least 2 hours. Prior to using equipment, rinse all surfaces treated with a 600 ppm solution with a 200 ppm solution with 10 gallons of water.