

ACTIVE INGREDIENTS: Disodium cyanodithioimidocarbonate ... INERT INGREDIENTS This product contains $\frac{2.26}{}$ lb. of active ingredients per gallon and weighs $\frac{9.7}{}$ lb. per gallon.

KEEP OUT OF REACH OF CHILDREN

WARNING

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear graggies or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food

STATEMENT OF PRACTICAL TREATMENT: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician, Remove and wash contaminated clothing before reuse. If awallowed, call a physician or Poison Control Center, Drink 1 or 2 plasses of water and induce your hing by tour hing tlack of throat with linger. Do not induce vomiting or give anything by mosth to an unconscious person

NAMENTAL MAZARGO. This persocide is to rigital fish. Do not discharge effluent containing. inflye in the feet and lawes, streams, prinds, estuares, oceans, or public waters unless this proof tically when the dial. It all tressed in an NPCES permit. Do not discharge officent accordances of a final sewing system is writingly previously not fying the sewage treatment prantiauthority. For guidance content your State Water Board or Regional Office of the EPA

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

DIRECTIONS FOR USE

MC - 23_____is used to control algae and bacteria in recirculating commercial and industrial water cooling towers. Prior to its use. systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 2.6 to 5.2 fluid ounces of MC-23 _____ per 1000 gallons of water is recommended. Repeat initial desage until control is evident.

Subsequent slug additions of 0.85 to 5.2 fluid ounces of per 1000 gallons of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Do not expose to extreme temperatures. Do not stack more than five drums high. Drums should be opened in well-ventilated areas. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when no in use.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL:

- METAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a senitary landfill, or by other procedures approved by state and local authority.
- D PLASTIC: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineratic s, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke

Manufactured by:

BUTLER CHEMICAL CO. INC. 2369 E. OAKTON ST. ARLINGT N. HTS., II. 60005 EPA REG. NO. ______ EPA EST. NO. _____

NET CONTENTS