Union Guard 225-B

ACTIVE INGREDIENT:	
Potassium dimethyldithiocarbamate	25.0%
INERT INGREDIENTS	
This product contains 2.3 lb. of active ingredient per gallon and weighs 9.25	
lb. ner gallon	

KEEP OUT OF REACH OF CHILDREN WARNING

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes eye demage and skin irritation. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Avoid contamination of food, Wear goggles or face shield and rubber gloves when handling. Wash thoroughly after handling.

STATEMENT OF PRACTICAL TREATMENT: In case of skin contact, with with plenty of soap and water. Remove contaminated clothing and week before rouse. If product gets in the eyes, flush immediately with copious amounts of clean, cool water for at least 15 minutes. Get medical attention immediately. If product is swallowed, call a physician immediately. If patient is conscious, induce vorniting by stroking or ticking the patient's throat or far back on patient's tongue, Emetics such as 2 teaspoonsful (10 mL) of specac syrup or 1 teaspoonful (5 mL) of dry musterd in warm water to form a paste or even adep in warm water can be used. Repeat until vomit fluid is clear, Then have patient drink planty of milk, gelatin solution, baaten agg whites, flour and water, or other nonoily demulcent. Never induce vomiting or give anything by mouth to an unconscious person. Note to physicien: Probable mucosal demage may contraindicate gastric lavage.

ENVIRONMENTAL HAZARDS; This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields Do not decharge treeted effluent into lakes, streams, ponds, or public waters are permit. For guidence, contect your Regional Office of the Environmental Protection Abbrey.

AUG 2 **7 1982**

Manufactured by:

.! Hodenticide Act as emended, let the posticide Union Chemical Specialties LAGIReg No. 46615

P. O. Box 1814 Ada, OK 74820

46615-1 EPA REG. NO. _

EPA ES 1. NO.

NET CONTENTS _

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Union Guard 225-B is used in industrial and/or commercial recirculating cooling tower systems and industrial air-washing systems to control microbiological slime. Prior to the use of Union Guard 225-B in industrial and/or commercial recirculating cooling tower systems, systems should be cleaned to remove algal growth, microbiological slime, and other deposits. Then make an initial slug addition of 4.5 to 6.8 fl. oz. of Union Guard 225-B per 1000 gal, of water to provide 40 to 60 ppm of Union Guard 225-B, based on total weight of water in the system. Repeat initial dosage until control is evident. Make subsequent slug addition of 2.3 to 6.8 fl. oz. of Union Guard 225-B per 1000 gal. of water (20 to 60 ppm Union Guard 225-B) every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of recirculating cooling tower systems.

Union Guard 225-B is used in industrial air-washing systems which maintain effective mist-eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 10.6 to 13.6 fl. oz. of Union Guard 225-B per 1000 gal. of water is recommended. Repeat initial dosage until control is evident, Subsequent slug additions of 7.9 to 13.6 fl. oz. of Union Guard 225-B per 1000 gallons of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem, Slug additions may be made to the sump or the water collection trays of the airwash system.

Union Guard 225-B is used to control both aerobic and anaerobic bacteria, including sulfate-reducing organisms, in petroleum secondary-recovery waterflooding operations. In systems fouled with microbiological deposits, Union Guard 225-B should be added as a slug dose to provide a concentration of 16 to 32 ppm (1.9 to 3.8 fl. oz. of Union Guard 225-B per 1000 gal, of water treated). This should be followed by a continuous addition of Union Guard 225-B employing a chemical-metering pump to maintain a concentration of 16 ppm, based on total weight of water treated. Both slug additions and continuous addition of Union Guard 225-B should be made at the heater-treater dump, gathering lines, or receiving tanks. Addition should always be made upstream to the filter.

Union Guard 225-B is also used to inhibit the growth of fungi and bacteria in waterbased drilling muds, completion fluids, packer fluids, and other water-based drilling fluids containing starch, gums, sugars, or other organic materials. For these purposes Union Guard 225-B is added at rates of 1.4 to 6.8 gal. per 100 barrels of fluid (0.03 to 0.16% by

STORAGE AND DISPOSAL

PROHIBITIONS: Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. PESTICIDE DISPOSAL: Posticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of in a lendfill approved for pesticides, or buried in a safe place away from water supplies. CONTAINER DISPOSAL:

[] METAL: Triple rinse (or equivalent) and offer for recycling, reconditioning, or disposal in an approved landful or bury in a safe place. Containers over 30 gallons should be resealed before offering for reconditioning.

13 PLASTIC: Containers under 30 gallons must not be reused but should be triple rinsed and disposed of in an incinerator or landfill approved for pesticide containers or buried in a safe place. Containers over 30 gallons are to be resealed and offered for reconditioning or triple rinsed (or equivalent) and offered for recycling, reconditioning, or disposal in an approved landfill or buried in a safe place

GENERAL. Consult Federal, State, or Local disposal authorities for approved alternative procedures.