

ALBANY PRESS REGISTERED STOCK LABEL 59-A

ACC
OCT 14 1982
Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the registration under EPA Reg. No. 46909-4

INGREDIENTS	
ACTIVE INGREDIENT - Cuprous Oxide (Copper as Metallic: 40%)	55.8%
INERT INGREDIENTS -	44.2%
TOTAL	100.0%

THIS PRODUCT CONTAINS PETROLEUM DISTILLATES. FLAMMABLE. DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.

KEEP OUT OF REACH OF CHILDREN
WARNING

If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

If in eyes: Flush with plenty of water. Get medical attention.

If on skin: Wash with plenty of soap and water. Get medical attention.

If inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. Get medical attention.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

MANUFACTURED BY

BEST DOCUMENT AVAILABLE

PRECAUTIONARY STATEMENTS

WARNING

HAZARDS TO HUMANS & DOMESTIC ANIMALS

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

When spraying and/or sanding boat surfaces, wear a mask or respirator, jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

ENVIRONMENTAL HAZARDS

This material is toxic to fish and wildlife. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS

Flammable. Keep away from heat or open flames. Flash Point 80° F.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Stir well before using.

A 3387 HULLGARD COPPER ANTI-FOULING PAINT is suitable for application to properly prepared and primed wood, steel, aluminum and fiberglass vessels subject to attack by barnacles, algae, tube worms and other fouling organisms. It should be used on bottoms which will receive constant immersion in medium to high salinity sea water. It is not recommended for brackish water or fresh water immersion.

The surface must be clean and dry prior to paint application. Where priming of steel or aluminum is needed, use P-111MR Viking Yellow Epoxy Primer. Where priming of wood or fiberglass is needed use A-553 Viking Epoxy Primer Surface. Surfaces in good condition do not need to be primed. Roughen the existing surface sufficiently with abrasive paper to insure a good bond. 120 grit paper is normally used.

Before applying to old paint, apply a small test patch to insure adhesion. If old paint is not vinyl, it may wrinkle and fail.

Application can be by spraying, brushing or rolling. Airless spray is strongly recommended if spraying is chosen. A minimum total dry film thickness of 5 mils is recommended. If airless spray is used, one coat may be sufficient to obtain 5 mils dry. If other application methods are used, two coats are generally required. Four hours drying time should be allowed between coats. At 5 mils dry film thickness a gallon of paint will cover approximately 187 square feet. Clean up with Savannah Vinyl Solvent.

Vessel should be launched immediately. Delay may cause a film to form which passivates the surface and allows attack by marine organisms.

STORAGE AND DISPOSAL

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL.

PESTICIDE DISPOSAL. Pesticide, spray mixture, or rinse solvent that cannot be used according to label instructions must be disposed of according to Federal, state or local procedures under Subtitle C of the Resource Conservation and Recovery Act.

CONTAINER DISPOSAL. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

BEST DOCUMENT AVAILABLE