



U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs
Antimicrobials Division (7510C)
1200 Pennsylvania Avenue NW
Washington, D.C. 20460

EPA Reg. Number:
47091-13

Date of Issuance:
November 7, 2006

Term of Issuance:
Unconditional

Name of Pesticide Product:
PREDATOR 1020

NOTICE OF PESTICIDE:

- Registration
- Reregistration

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

Aurora Specialty Chemistries
1520 Lake Lansing Road
Lansing, MI 48912

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is unconditionally registered in accordance with FIFRA sec 3(c)(5) provided that you:

1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA section 4.

2. Make the labeling changes listed below before you release the product for shipment:

- a. Add the phrase "EPA Registration Number 47091-13".

Signature of Approving Official:

Adam Heyward
Product Manager Team-34
Regulatory Management Branch II
Antimicrobials Division (7510C)

Date:

November 7, 2006

- b. Under "***DIRECTION FOR USE***" for most of the applications, place Parentheses around the dosage rates reported in gallons (e.g., 0.048-0.095 gal) and pounds (e.g., 0.01 to 1.0 lbs). The newly added dosage rates reported in fluid ounces must be separated from the dosage rates reported in gallons and pounds.
2. Submit Identify the quantity of product produced per theoretical batch size and identify the product specifications that are monitored as part of quality control analysis per § 830.1650 (Description of Formulation Process) requirement
3. Change the certified limits of material of the active ingredient from 21.43% to 21.0% for the upper limit, and from 19.39% to 19.8% for the lower limit.
4. Submit three (3) copies of the final printed label prior to releasing this product for sale.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



Adam Heyward
Product Manager 34
Regulatory Branch II
Antimicrobials Division (7510C)

Enclosure: (Stamped Labeling)

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

CORROSIVE

- CAUSES IRREVERSIBLE EYE DAMAGE
- MAY BE FATAL IF SWALLOWED
- HARMFUL IF INHALED OR ABSORBED THROUGH SKIN
- CAUSES SKIN BURNS
- PROLONGED OR FREQUENTLY REPEATED SKIN CONTACT MAY CAUSE ALLERGIC REACTIONS IN SOME INDIVIDUALS

Do not get in eyes, on skin, or on clothing. In case of contact immediately rinse skin with plenty of water. Get medical attention if irritation persists. Use with adequate ventilation. Wash thoroughly with soap and water after handling and before eating, drinking, using tobacco, or using the toilet. Remove contaminated clothing and wash clothing before reuse.

PERSONAL PROTECTION EQUIPMENT (PPE):

- Applicators and other handlers must wear:
- Coveralls worn over long sleeved shirt and long pants.
- Chemical resistant footwear plus socks.
- Goggles or face shield.
- Chemical-resistant gloves (such as barrier laminate, butyl rubber, neoprene rubber, nitrile rubber, polyvinyl chloride (PVC) and viton).
- For mixing/loading: Wear a chemical resistant apron
- For cleaning equipment: Wear a chemical resistant apron

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions exist for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

User Safety Recommendations
Users should wash hands before drinking, chewing gum, using tobacco, or using the toilet. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove personal protective equipment immediately after handling this product. Wash outside of gloves before removing. As soon as possible wash thoroughly.
General Precautions and Restrictions
Do not apply this product in a way that will contact workers or other persons.
WARRANTY
Seller warrants that this product conforms to its chemical description and is reasonably fit for the purposes stated on the label when used in accordance with label directions under normal conditions of use, but neither this warranty nor any other warranty of MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, express or implied, extends to the use of this product contrary to label instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to Seller, and Buyer assumes the risk of any such use.

PREDATOR 1020

DBNPA

A MICROBIOCIDAL BACTERICIDE, FUNGICIDE, ALGAEICIDE AND SLIMICIDE, USED IN TREATING RECIRCULATING COOLING WATER IN INDUSTRIAL COOLING SYSTEMS, PAPER MILLS, BREWERY PASTEURIZER WATER, METALWORKING CUTTING FLUIDS, NON-POTABLE REVERSE OSMOSIS SYSTEMS, ENHANCED OIL RECOVERY SYSTEMS, AIR-WASHER SYSTEMS, INDUSTRIAL PRESERVATION APPLICATIONS AND PUBLICLY-OWNED TREATMENT WORKS.

ACTIVE INGREDIENT: 2,2-Dibromo-3-nitropropionamide..... 20%
INERT INGREDIENTS: 80%
TOTAL: 100%

10 pounds PREDATOR 1020 liquid per gallon.

KEEP OUT OF REACH OF CHILDREN

DANGER

See side panels for additional precautionary statements

FIRST AID	
If in eyes	<ul style="list-style-type: none"> • Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Call a poison control center or doctor for treatment advice.
If inhaled	<ul style="list-style-type: none"> • Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. • Call a poison control center or doctor for further treatment advice.
If on skin or clothing	<ul style="list-style-type: none"> • Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 minutes. • Call a poison control center or doctor for treatment advice.
If swallowed	<ul style="list-style-type: none"> • Call poison control center, or doctor immediately for treatment advice. • Have person sip a glass of water if able to swallow. • Do not induce vomiting unless told to do so by the poison control center or doctor. • Do not give anything by mouth to an unconscious person.
<p>Have the product container or label with you when calling a poison control center or doctor, or going for treatment. YOU MAY ALSO CONTACT 1-800-24-9300 FOR EMERGENCY MEDICAL TREATMENT INFORMATION.</p>	
<p>NOTE TO PHYSICIAN "Probable mucosal damage may contraindicate the use of gastric lavage."</p>	

WASH THOROUGHLY AFTER HANDLING

ENVIRONMENTAL HAZARDS

This product is toxic to fish and aquatic organisms. Do not contaminate water by cleaning of equipment or disposal of waste. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

CHEMICAL AND PHYSICAL HAZARDS

Reaction with strong reducing agents may be explosive. Avoid misting.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE

Store in a dark, cool, dry, well-ventilated area, not above 104°F (40°C), in well-closed original containers, away from energy sources, combustible organic materials, oxidizers and moisture.

DISPOSAL

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinseate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

SPILLS

When handling or dealing with spills, use impact-resistant goggles with side shields, or face shield; wear body-covering clothes, including impervious rubber gloves and boots; use a respirator if misting occurs. Cover wet spills with 10% sodium bicarbonate solution, water and then an inert absorbent before sweeping up. Sweepings and residue should be disposed of in a sanitary landfill, or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE TO MAINTAIN PRODUCT QUALITY, STORE IN THE ORIGINAL CONTAINER AT TEMPERATURES BELOW 104°F (40°C). DO NOT SHIP WITH FOOD, FEEDS, DRUGS, OR CLOTHING. DO NOT SMOKE, DRINK, OR EAT WHEN HANDLING.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

DIRECTIONS FOR TREATING INDUSTRIAL RECIRCULATING COOLING WATER IN INDUSTRIAL COOLING SYSTEMS

NOTE: Add PREDATOR 1020 separately to the system. Do not mix it with other additives, so as to avoid decomposition of PREDATOR 1020 due to the high pH of many additive formulations.

Add PREDATOR 1020 to the basin (or any other point of uniform mixing). Addition should be made via a metering pump; it may be continuous or intermittent, depending on the severity of the contamination when treatment is begun, and the in-system retention time. Optimum performance with this product is achieved by continuous or "intermittent" treatment. If "shock" treatment is used, the blowdown should be discontinued for 24-48 hours.

FOR CONTROL OF BACTERIA

INITIAL DOSE: When the system is noticeably fouled, add 0.61 - 1.22 fluid ounces (6.0 - 11.9 ppm) of PREDATOR 1020 / 1000 gal. of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 0.3 - 1.22 fluid ounces (3.0 - 11.9 ppm) of PREDATOR 1020 / 1000 gal. of water in the system every 4 days, or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

Initial Dose: When the system is noticeably fouled, add 0.61 - 1.22 fluid ounces (6.0 - 11.9 ppm) of PREDATOR 1020 / 1000 gal. of water in the system.

Subsequent Dose: Maintain this level by pumping a continuous feed of 0.12 - 0.61 fluid ounces (1.2 - 6.0 ppm) of PREDATOR 1020 / 1000 gal. of water in the system lost by blowdown. Badly fouled systems must be cleaned before treatment is begun.

A CERTIFIED
 WITH COMMENTS
 EPA Letter # 1006
 NOV - 7 2006

Under the Federal Insecticide,
 Fungicide, and Rodenticide Act as
 amended, for the pesticide,
 registered under EPA Reg. No. 47091-13
 HKS

FOR CONTROL OF FUNGI AND ALGAE

Add 3.71 - 12.16 fluid ounces (36.2 - 118.5 ppm) of PREDATOR 1020 / 1000 gal. of water in the system, depending on the severity of contamination.

INTERMITTENT OR SLUG METHOD

Initial Dose: When the system is noticeably fouled, add 6.1 - 12.2 fluid ounces (60.0 - 118.5 ppm) of PREDATOR 1020 / 1000 gal. of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 3.7 - 12.2 fluid ounces (36.2 - 118.5 ppm) of PREDATOR 1020 / 1000 gal. of water in the system daily, or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

Initial Dose: When the system is noticeably fouled, add 6.1 - 12.2 fluid ounces (60.0 - 118.5 ppm)(0.048-0.095 gal.) of PREDATOR 1020 / 1000 gal. of water in the system.

Subsequent Dose: Maintain this treatment level by pumping a continuous feed of 3.7 - 12.2 fluid ounces (36.2 - 118.5 ppm)(0.029-0.095 gal.) of PREDATOR 1020 / 1000 gal. of water in the system per day. Badly fouled systems must be cleaned before treatment is begun.

DIRECTIONS FOR TREATING PULP AND PAPER MILL SYSTEMS

NOTE: Add PREDATOR 1020 separately to the system. Do not mix it with other additives, so as to avoid decomposition of PREDATOR 1020 due to the high pH of many additive formulations. For the control of slime-forming bacterial, fungal, or yeast growth in pulp, paper and paperboard mills add PREDATOR 1020 at the rate of 0.15-0.50 lb./ton (dry) of pulp or paper produced. Addition can be continuous or intermittent, depending upon the type of system and the severity of contamination. Addition is via a metering pump at a point in the system that will ensure uniform distribution of PREDATOR 1020 in the mass of fiber and water, such as the beaters, Jordan inlet or discharge, broke chests, furnish chests, savalls and white-water tanks. Heavily fouled systems must first be boiled out, then treated with 0.15-0.35 lb. of PREDATOR 1020 /ton (dry) of paper or pulp as necessary for control. Moderately fouled systems should be treated continuously with 0.35-0.50 lb. of PREDATOR 1020 /ton (dry) of paper or pulp until the slime accumulation is controlled. Subsequent rates can then be reduced to 0.15-0.35 lb. of PREDATOR 1020 /ton (dry) of paper on a continuous or intermittent basis as needed for control. Dislodged slime may cause breaks in the paper and a clean-up of the paper machine may be advisable.

Slightly fouled systems should be treated continuously with 0.15-0.35 lb. of PREDATOR 1020 /ton (dry) of paper or pulp, until the slime is controlled, then added on an intermittent basis to maintain control.

DIRECTIONS FOR TREATING NON-POTABLE REVERSE OSMOSIS SYSTEMS

For controlling bacteria, fungi and algae slimes in non-potable Reverse Osmosis systems and peripheral equipment, add PREDATOR 1020 to the system inlet water or before any other contamination area ahead of the Reverse Osmosis unit. PREDATOR 1020 should be added with a metering pump on an intermittent basis depending on the severity of contamination and the guidelines specified by the membrane manufacturer for PREDATOR 1020.

Add PREDATOR 1020 at the rate of 0.12 - 12.3 fluid ounces (0.01 to 1.0 lbs) (1.2 to 120 ppm) per 1000 gals of feedwater. During use of PREDATOR 1020 both permeate and reject waters should be directed to the drain. Once treatment is completed, rinsing with feedwater should continue until conductivity values in the permeate are at or below values before treatment with PREDATOR 1020. Badly fouled systems must be cleaned before treatment is begun.

FOR CONTROL OF BACTERIA

Initial Dose: When the system is noticeably fouled, add PREDATOR 1020 at the rate of 0.62 - 1.2 fluid ounces 0.05 to 0.1 lb (6.0 to 12 ppm) per 1000 gals of feedwater. Minimum treatment intervals should be 15 minutes. Repeat until control is achieved or as specified by guidelines recommended by the membrane manufacturer.

Subsequent Dose: When microbial control is achieved, add PREDATOR 1020 at the rate of 0.31 - 1.2 fluid ounces 0.025 to 0.1 lb (3.0 to 12 ppm) per 1000 gals of feedwater as needed to maintain control or as specified by guidelines recommended by the membrane manufacturer.

FOR CONTROL OF FUNGI AND ALGAE

Initial Dose: When the system is noticeably fouled, add PREDATOR 1020 at the rate of 6.2 - 12.2 fluid ounces 0.5 to 1.0 lb (60 to 120 ppm) per 1000 gals of feedwater. Minimum treatment intervals should be 15 minutes. Repeat until control is achieved or as specified by guidelines recommended by the membrane manufacturer.

Subsequent Dose: When microbial control is achieved, add PREDATOR 1020 at the rate of 3.7 - 12.2 fluid ounces (0.3 to 1.0 lb) (36 to 120 ppm) per 1000 gals of feedwater as needed to maintain control or as specified by guidelines recommended by the membrane manufacturer.

DIRECTIONS FOR TREATING METALWORKING FLUIDS CONTAINING WATER
PREDATOR 1020 is effective in metalworking fluid concentrates which have been diluted in water at ratios of 1:100 to 1:4. For controlling (or inhibiting) the growth of bacteria, fungi and yeasts that may deteriorate metalworking fluids containing water, add this product to the fluid in the collection tank. Additions should be made with a metering pump.

Initial or Slug Dose: When the system is noticeably fouled, add PREDATOR 1020 at the rate of 32 fluid ounces (0.25 gal) (2.65 lbs) per 1000 gals of metalworking fluid in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add PREDATOR 1020 at the rate of 12.8 - 25.6 fluid ounces (0.1 to 0.2 gal) (1.06 to 2.12 lbs) per 1000 gals of metalworking fluid per day, or as needed to maintain control. Additions of PREDATOR 1020 product can be made continuously or intermittently. Slug the system as required. Badly fouled systems must be cleaned before treatment is begun.

DIRECTIONS FOR TREATING BREWERY PASTEURIZER WATER

For controlling (or inhibiting) the growth of bacteria, fungi and yeasts in brewery pasteurizing water systems, add PREDATOR 1020 at a point in the system to insure uniform mixing.

Initial or Slug Dose: When the system is noticeably fouled, add PREDATOR 1020 at the rate of 32 fluid ounces (0.25 gal) (2.65 lbs) per 1000 gals of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add PREDATOR 1020 at the rate of 12.8 - 25.6 fluid ounces (0.1 to 0.2 gal) (1.06 to 2.12 lbs) per 1000 gals of water per day, or as needed to maintain control. Additions of PREDATOR 1020 product can be made continuously or intermittently. Slug the system as required. Badly fouled systems must be cleaned before treatment is begun.

DIRECTIONS FOR TREATING ENHANCED OIL RECOVERY SYSTEMS

NOTE: Add PREDATOR 1020 separately to the system. Do not mix it with other additives, so as to avoid decomposition of PREDATOR 1020 due to the high pH of many additive formulations. Addition of PREDATOR 1020 may be made at the free water knockouts, before or after the injection pumps and injection well headers. For controlling slime-forming bacteria, sulfide-producing bacteria, yeasts, and fungi in oil field water, polymer or micellar floods, water-disposal systems, or other oil field water systems, add 1-80 ppm PREDATOR 1020 (13 - 819 fluid ounces)(0.1- 6.4 gallons) of PREDATOR 1020 per 2400 barrels of water) depending on the severity of contamination. Additions should be made with a metering pump either continuously or intermittently.

CONTINUOUS FEED METHOD

When the system is noticeably fouled, add 10-80 ppm PREDATOR 1020 (102 - 819 fluid ounces) (0.8-6.4 gal.) of PREDATOR 1020 per 2400 barrels of water) continuously until the desired degree of control is achieved. Subsequently, treat with 1-15 ppm PREDATOR 1020 (13 - 154 fluid ounces) (0.1-1.2 gal.) of PREDATOR 1020 per 2400 barrels of water) continuously or as needed to maintain control.

INTERMITTENT OR SLUG METHOD

When the system is noticeably fouled or to maintain control of the system, add 10-80 ppm PREDATOR 1020 (102 - 819 fluid ounces) (0.8-6.4 gal. of PREDATOR 1020 per 2400 barrels of water) intermittently for 4-8 hours per day and from 1-4 times per week, or as needed depending on the severity of contamination.

NOTE: For control of bacteria, yeast, and fungi in aqueous solutions of biopolymer used in flooding operations, add 15-80 ppm PREDATOR 1020 (154 - 819 fluid ounces) (1.2-6.4 gal. of PREDATOR 1020 per 2400 barrels of water). Additions of PREDATOR 1020 should be made with a metering pump immediately after preparation of the aqueous biopolymer solution to reduce loss of viscosity.

DIRECTIONS FOR TREATING AIR-WASHER SYSTEMS

Add 0.0015-0.095 gallons PREDATOR 1020 / 1000 gal of water in the system, depending on the severity of contamination, to control slime-forming bacteria and fungi in industrial air washing systems.

Intermittent or Slug Method

Initial Dose: When the system is noticeably fouled, add 0.003-0.095 0.38 - 12.2 fluid ounces (3.8 - 118.5 ppm) gal PREDATOR 1020 / 1000 gal of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 0.0015-0.047 0.19 - 6.1 fluid ounces (1.9 - 59 ppm) gal PREDATOR 1020 / 1000 gal of water in the system every 2 days, or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

Initial Dose: When the system is noticeably fouled, add 0.38 - 12.2 fluid ounces (3.8 - 118.5 ppm) (0.003-0.095 gal) PREDATOR 1020 / 1000 gal of water in the system.

Subsequent Dose: Maintain this level by pumping a continuous feed of 0.0015-0.047 gal (0.19 - 6.1 fluid ounces) (1.9 - 59 ppm) PREDATOR 1020 / 1000 gal of water in the system per day. Badly fouled systems must be cleaned before treatment is begun.

NOTE: For use only in industrial air-washer systems that maintain effective mist eliminating components

DIRECTIONS FOR INDUSTRIAL PRESERVATION APPLICATIONS

PREDATOR 1020 may be used to reduce microbiological contamination in raw materials and/or products such as: aqueous paints and coatings, polymers, slurries, adhesives, latex and resin emulsions, sizing, caulk, process water, along with specialty industrial products including: inks, polishes, waxes, detergents, and cleansers.

TO REDUCE MICROBIOLOGICAL CONTAMINATION

Add PREDATOR 1020 to the material or product at a concentration of 25 to 2,000 ppm by weight. This concentration is equivalent to 2.8 to 224.0 fluid ounces PREDATOR 1020 per 1,000 gallons or 21.4 to 1,712.0 milliliters PREDATOR 1020 per 1,000 liters. The required concentration will depend on the material being treated and the level of contamination present.

DIRECTIONS FOR TREATING PUBLICLY-OWNED TREATMENT WORKS TO CONTROL COLIFORM AND OTHER BACTERIA

Add PREDATOR 1020 at a concentration of 1.0 to 10.0 ppm by weight of water being treated, depending on the severity and contamination in the system. Addition should be CONTINUOUS and should be made with a metering pump at a point in the system where mixing will be rapid and thorough. Add PREDATOR 1020 to the system in a location where contact time will be 30 minutes or greater before reaching the outfall.

TO USE AS A CO-TREATMENT WITH CHLORINE

Add 0.4 - 1.5 ppm PREDATOR 1020 by weight of water treated. Chlorination should result in a minimum detectable residual (i.e., greater than zero but less than the NPDES permit level) Addition should be CONTINUOUS and made at a point just after initial chlorine mixing. Rapid mixing is necessary for maximum effectiveness. PREDATOR 1020 should be added at a location where a contact time of 10 minutes or longer will be provided before reaching the outfall.

DIRECTIONS FOR TREATING OILFIELD AND PETROCHEMICAL SYSTEMS

PREDATOR 1020 may be used either in slug treatment or in continuous application. Dosages may vary from as much as 200 ppm of PREDATOR 1020 in slug application to 10 to 50 ppm of PREDATOR 1020 in continuous treatment (4 fluid ounces 1/4 pint PREDATOR 1020 per 1,000 gallons of water equals approximately 30 ppm). A typical slug treatment is to add 16 fluid ounces 1 pint of PREDATOR 1020 per 1,000 gallons at intervals as needed to prevent growth of microbial slime. Badly fouled systems may be slug treated to establish control, followed by continuous treatment to maintain control.

Manufactured for:

ASC Aurora
Specialty
Chemistries
1520 Lake Lansing Road
Lansing, MI 48912
(800) 344-3699

EPA Reg. No. 47091-G EPA Est. No. 47091-MI-1

NET CONTENTS: _____ GALS.(LBS.)

7/14