

RETARDS
ROTARD
MILLERY
REPELS

## **OX LINE LUMBER-CARE**

OX EINE LUMBER FARE Clear Wood Preservito exterior woods that have been weathered. It is igainst wood rot, mild wo warping and swele of WHERE TO USE: Apply on above-ground unfie milliwork, shingles, siding, doors, frames, said Do not apply over wood that is painted or variable being. Surface must be clear, and free of dirt is scrub off with detergent and water. If mildew natural tone of wood.

APPLICATION: MIX WELL DO NOT THIN Ap, more EUMBER-CARE the wood absorbs the protestion apoly a second coat. Do not apply applying paint on surface treated with LUMB's COVERAGE: Approximately 100-300 sq. ft. proposity of wood.

CLEAN-UP: Clean Equipment promptly with in-NOTE: For word surfaces where color is desire to in both semi-transparent and solid color type

## PRECAUTION HAZARDS TO HUMAN

warning: Contains Petroleum Distilluprolonged breathing of vapor or spray mist. Gray or on clothing. Wear goggles. Harmful if swales Remove contaminated clothing and wash be STATEMENT OF PRACTICAL TREATMENT: IF IN IF SWALL OWED. Drink promptly a large quartiles of water. As a IF ON SKIN. Wash with plenty of soap and a ENVIRONMENTAL HAZARDS: Do not apply disease of the luse water spray froam carbons.

STORAGE AND DISPOSAL:

PROHIBITIONS - Do not contaminate water: open fame.

PRODUCT DISPOSAL - Product or reside that of according to federal. State or focal procession transfer disposal - Do not reuse em, Wrap container and put in trash collection

From to

LEHMAN BROS. C

## OX LINE LUMBER-CARE CLEAR WOOD PRESER

OX LINE LUMBER-CARE Clear Wood Preservative is a chemical treatment for bare or previously stained  ${f x}$ woods that have been weathered. It is an effective fungicide and water repellent that protects

against wood rot, mildew, warping and swelling. LUMBER-CARE will not chip, peel or blister.

WHERE TO USE: Apply on above-ground untreated wood surfaces such as lumber, fences, trellises, millwork, shingles, siding, doors, frames, sash, decks and outdoor furniture.

Do not apply over wood that is painted or varnished.

DIRECTIONS FOR USE: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Surface must be clean and free of dirt, oil, grease and mildew. If dirt has caused discolored areas, scrub off with detergent and water. It mildew is present, consult dealer for removing mildew to rectore

APPLICATION: MIX WELL DO NOT THIN. Apply liberally by brush, roller, spray or by dipping wood. The more LUMBER-CARE the wood absorbs, the deeper and more lasting the protection will be. For extra protection apply a second coat. Do not apply in hot direct sunlight or in temperatures below 40°F. Before applying paint on surface treated with LUMBER-CARE it must be allowed to weather for 6-9 months. COVERAGE: Approximately 100-300 sq. ft. per gallon, depending upon method of application and the

CLEAN-UP: Clean equipment promptly with mineral spirits.

NOTE: For wood surfaces where color is desired, use OX-LINE Stain & Wood Preservative which is available in both semi-transparent and solid color types

## PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

warning; contains petroleum distillates. Use only with adequate ventilation. Avoid prolonged breathing of vapor or spray mist. Causes substantial but temporary eye in dry. Do not get in eyes or on clothing. Wear goggles. Harmful if swallowed. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before re-use.

STATEMENT OF PRACTICAL TREATMENT: IF IN EYES: Flush with plenty of water. Get medical attention. IF SWALLOWED: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol.

IF ON SKIN. Wash with plenty of soap and water. Get medical attention.

ENVIRONMENTAL HAZARDS: Do not apply directly to water. This product is toxic to fish. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label. PHYSICAL AND CHEMICAL HAZARDS: COMBUSTIBLE: Do not use, pour or spill near heat or open flame. In case of fire, use water spray, foam, carbon dioxide or dry chemical.

STORAGE AND DISPOSAL:

PROHIBITIONS - Do not contaminate water, food or feed by storage or disposal. Do not store near heat or

PRODUCT DISPOSAL - Product or rinsate that cannot be used according to label instructions must be disposed of according to Federal, State or local procedures under the Resource Conservation and Recovery Act. CONTAINER DISPOSAL - Do not reuse empty container. Destroy container by perforating or crushing. Wrap container and put in trash collection

From the laboratories of

HMAN BROS. CORP. **JERSEY CITY, NJ 07305**