



ACCEPTED
JUN 11 1982
 Under the Federal Insecticide,
 Fungicide, and Rodenticide Act,
 as amended, for the pesticide
 registered under
 EPA Reg. No. 47143-1

TIMBER LIFE WOOD FINISH PRESERVATIVE

Active Ingredient 3-Iodo-2-propynyl butyl carbamate 0.89%
 Inert Ingredients 99.11%

KEEP OUT OF REACH OF CHILDREN
WARNING

See Other Precautionary Statements on Back Panel

EPA Reg. #47143-1
 EPA Est. #47143-FL-1

Richard's Paint Manufacturing Co., Inc.
 Route 1, Box 1675 Cocoa, Florida 32922



TIMBER LIFE PENETRATING WOOD FINISH AND PRESERVATIVE

A natural finish that penetrates uncoated woods to either prolong or restore a natural wood appearance. Timber Life penetrates wood, providing embedded protection. Protects against wood rot, resists mildew growth and reduces swelling and cracking. For use on wood siding, shakes, shingles, and textured plywood. When Timber Life is first applied the wood will darken to a rich color which will lighten in several months depending on sun intensity. When a light gray appearance reappears it is time to recoat with Timber Life to renew protection and color. Use Timber Life as received.

DIRECTIONS

Surface Preparation: Wood must be clean and dry

New Wood: For roughsawn cedar, cedar shakes or shingles, redwood, pine, etc., apply Timber Life before wood begins to darken. Smooth lumber must be weathered 6 months or sanded to remove mill glaze.

Weathered Bare Wood: Timber Life restores an amber color to wood weathered to a silver-gray. This action requires at least a month of exposure to moisture and sunlight.

Mildewed Wood: Wood in this condition must be bleached to kill the fungus and rinsed thoroughly with fresh water. Then apply Timber Life.

Previously Stained, Varnished or Painted Wood: The old finish must be completely removed. Treat as new wood.

To Apply: Timber Life may be applied by dipping, brushing, rolling, or spraying. Let the wood determine amount of Timber Life to be used. As one coat is absorbed, apply another coat until the wood has a wet sheen. DO NOT ALLOW TIMBER LIFE TO SET UP OR DRY BETWEEN COATS.

Coverage: 100-250 square feet per gallon depending on porosity and texture of the wood.

Dry Time: 24-48 hours depending on temperature and humidity.

Clean Up: Use mineral spirits to clean equipment.

Tinting: Do not tint or intermix.

WARNING

PRECAUTIONARY STATEMENTS: HAZARDS TO HUMANS (AND DOMESTIC ANIMALS)

Harmful if swallowed, may be absorbed through skin. Causes skin irritation. Avoid breathing vapor or spray mist. Do not get in eyes, on skin, or on clothing.

First Aid Statement: If swallowed, do not induce vomiting. Call a physician immediately. In case of contact, immediately flush eyes or skin with plenty of water. Get medical attention if irritation persists.

NOTE: Wear goggles, rubber gloves, and protective clothing when applying or handling treated lumber.

ENVIRONMENTAL HAZARDS: Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL/CHEMICAL HAZARDS: Do not use or store near heat or open flame. Use with adequate ventilation.

DIRECTIONS FOR USE

It is violation of Federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

Do not reuse empty container. Wrap container and put in trash can.