



PA 10 1 75-75-5

KA 120

**BEST AVAILABLE COPY**

**ACCEPTED**  
with **COMMENTS**  
in EPA Letter Dated:

**OCT 17 1984**

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act  
as amended, for the pesticide  
registered under EPA Reg. No.

47895-5

**ACTIVE INGREDIENT:**

Poly(oxyethylene (dimethyliminio) ethylene-  
(dimethyliminio) ethylene dichloride) ..... 60.0 %

**INERT INGREDIENT** ..... 40.0 %

This product contains 5.76 lb. of active ingredient per gallon and weighs  
9.6 lb. per gallon.

**KEEP OUT OF REACH OF CHILDREN**

**CAUTION**

**PRECAUTIONARY STATEMENTS**

**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**CAUTION:** Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

**FIRST AID:** If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

**ENVIRONMENTAL HAZARDS:** This pesticide is toxic to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.

**DIRECTIONS FOR  
GENERAL CLASSIFICATION**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

KA 120 is used to control bacteria and fungi in recirculating commercial and industrial air wash systems. To its use, systems must be cleaned to remove slime, and other deposits. An initial slug addition of 8 fluid ounces of KA 120 per 1000 gallons of water to provide a concentration of 8 parts per million of KA 120 in the system, is recommended. Repeat initial dosages of 0.2 fluid ounces of KA 120 per 1000 gallons of water are recommended. Repeat initial dosages of 0.2 fluid ounces of KA 120 per 1000 gallons of water should be employed as frequently as needed. Slug additions should be made in the summer months. KA 120 is used in air-washing systems that maintain effective mist. To its use, systems should be cleaned to remove deposits. An initial slug dose of 3.33 fluid ounces of KA 120 per 1000 gallons of water should be employed as frequently as needed. Repeat initial dosages of 2.25 to 5.55 fluid ounces of KA 120 per 1000 gallons of water should be employed as frequently as needed. Slug additions may be made in the collection trays of the airwash system.

**STORAGE AND DISPOSAL**

Do not contaminate water, food, or feed by storage or disposal.

**STORAGE:** Do not stack more than four drums high. Leaking drums should be placed in a container for disposal. Spills should be absorbed in sawdust or sand and disposed of properly.

**PESTICIDE DISPOSAL:** Wastes resulting from the use of this product should be disposed of by a registered waste disposal facility.

**CONTAINER DISPOSAL:**

**PLASTIC:** Triple rinse (or equivalent). Then offer for recycling or for incineration, or, if allowed by state and local authorities, by other procedures approved by state and local authorities.

**METAL:** Triple rinse (or equivalent). Then offer for recycling or for incineration, or, if allowed by state and local authorities, by other procedures approved by state and local authorities.

**Manufactured by**

Kentucky Specialty Chemical

249 So. Limestone Street

Lexington, KY 40508

**EPA REG. NO.** \_\_\_\_\_ **EPA**

**NET CONTENTS** \_\_\_\_\_