

DELTA C-10

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS & DOMESTIC ANIMALS

WARNING

Harmful if swallowed, inhaled or absorbed through the skin. Contact with skin can cause irritation.
Do not get in eyes, on skin, or on clothing.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Keep out of ponds, lakes, and streams. Do not contaminate water by cleaning of equipment or disposal of wastes.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

STORAGE: Store at temperatures below 110°F. in original container and in a locked storage area. In case of a leak or spill absorb on clay for transport to approved waste disposal facility.

DISPOSAL: Do not contaminate water, food, or feed by storage or disposal. Triple rinse (or equivalent) metal container. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities. Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

WOOD PRESERVATIVE

INGREDIENT STATEMENT

ACTIVE INGREDIENTS

Cupric Hydroxide.....15.36%
Sodium Dimethylithiocarbamate..... 2.76%

INERT INGREDIENTS..... 81.88%
100.00%

READ THIS LABEL BEFORE USING PRODUCT

KEEP OUT OF REACH OF CHILDREN

WARNING

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED, induce vomiting.
IF INHALED, remove to fresh air.
IF ON SKIN, flush with water.
IF IN EYES, flush with water for 15 minutes and get medical attention.

SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS

DIRECTIONS

To protect from decay, mildew, termites, and powder post beetles treat wood as follows.

For wood above ground with low decay exposure, such as exterior siding with a roof overhang, dilute one part of Delta C-10 with nineteen parts of water and apply using two brush coats, a spray, or a three minute dip.

For wood above ground with moderate to high decay exposure, such as fencing pickets or wooden shakes, dilute one part of Delta C-10 with nine parts of water and apply using two brush coats, a spray, or a three minute dip.

For wood in ground contact exposures, such as fence posts, dilute one part of Delta C-10 with four parts of water and apply by soaking for 24 hours or longer, by hot-cold bath, or by vacuum processes!

Green or dry wood may be treated. Pigments or dyes may be added to the treating solution to provide a desired appearance to treated surfaces.

Treat wood outdoors and use treated wood only for exterior applications. Do not use treated wood where there may be extended periods of skin contact or contact with food or feed.

WARRANTY STATEMENT

Neither Delta Research Company nor the seller makes any representation or warranty, expressed or implied, concerning this material, other than indicated on the label. Neither shall be held responsible in any manner for any personal injury or property damage or other type of loss resulting from the improper handling, storage or use of this material. The buyer accepts and uses this material on these conditions.

ACCEPTED
NOV 29 1985
EPA Reg. No. 48106-3

EPA Reg. No.
EPA Est. No.

DELTA RESEARCH COMPANY

SENATOBIA, MISS 38668

Net Contents _____ Gallons