DELTA: C.12

10F/ Cm 33 47/06-5

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS

WARNING - Causes substantial but temporary eye injury. Harmful it swallowed, absorbed through the skin or inhaled. May cause skin sensitization reactions in certain individuals. Avoid contact with the skin, eyes, or clothing. Avoid breathing vapors. Protective clothing, including goggles, should be worn. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

"This pesticide is toxic to fish and aquatic organisms. Do not apply directly to water. Drift and runoff from treated areas may be hazardous to fish and aquatic organisms in adjacent aquatic sites. Do not allow rinsate from cleaning of equipment or disposed material to enter surface or ground water."

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a magney inconsistant with its taboling.

STORAGE AND DISPOSAL

STORAGE: Store at temperatures below 110°F, in original container aid in a locked storage area. In case of a leak or spill, absorb on clay for transport to approved waste disposal facility.

WOOD PRESERVAINE

INGREDIENT STATEMENT

ACTIVE INGREDIENTS

Copper as elemental	0.00%
Bis (Tri-n-Butyltin)oxide	0.95%

INERT INGREDIENTS 100.00%

*From copper-monoethanolamine complex

HEAD THIS LABEL REFORE USING PRODUCT

KEEP OUT OF REACH OF CHILDRES!

WARNING

STATEMENT OF PRACTICAL TREATMENT "IF IN EYES, flush with plenty of water. Call a physician. IF ON SKIN, wash with plenty of soap and water. Get medical attention. IF SWALLOWED, call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by louching the back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person."

EPA Reg. No.48106-5 EPA Est. No.

DELTA RESEARCH COMPANY

429ENATOBIA, MISS 20039

Net Contents _____ Gallor



DIPECTIONS

To protect from decay, mildew, termites, and powder post beetles treat wood as follows

For wood above ground with low decay exposure, such as exterior siding with a roof overhang, dilute one part of Delta C-12 with nineteen parts of water and apply using two brush coats, a spray, or a three minute dip.

For wood above ground with moderate to high decay exposure, such as fencing pickets or wooden shakes, dilute one part of Delta C-12 with nine parts of water and apply using two brush coats, a spray, or a three minute dip.

For wood in ground contact exposures, such as fence posts, dilute one part of Delta C-12 with four parts of water and apply by soaking for 24 hours or longer, by hot-cold bath, or by vacuum processes!

Green or dry wood may be treated. Pigments or dyes may be added to the treating solution to provide a desired appearance to treated surfaces.

Treat wood outdoors and use treated wood only for exterior applications. Do not use treated wood where there may be extended periods of skin contact or contact with food or feed.

CONTAINER DISPOSAL: Triple rinse (or equivalent) metal container. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary land fill, or by other procedures approved by state and local authorities.

PESTICIDE DISPOSAL - Wastes resulting from use of this product may be disposed of on site or at an approved waste disposal facility.