DELTA C-2 STAIN&WOOD PRESERVATIVE

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS **A DOMESTIC ANIMALS** WARNING

jarmful if swallowed, inhaled or absorbed hrough the skin: Contact with skin can ause irritation. to not get in eyes, on skin, or on clothing.

ENVIRONMENTAL HAZARDS

his product is toxic to fish and wildlife. (eep out of ponds, lakes, and streams. o not contaminate water by cleaning at equipment or disposal of wastes.

PHYSICAL AND CHEMICAL HAZARDS Do not use or store near heat or open flame.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its abelino. -

STORAGE AND DISPOSAL

STORAGE: Store at temperatures below 110°F, in original container and in a locked 'storage area, in case of a leak or spill absorb on clay for transport to approved waste disposal facility.

DISPOSAL: Do not contaminate water. food, or feed by storage or disposal. Triple rinse (or equivalent) metal container. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities. Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

ACTIVE INGREDIENTS

INERT INGREDIENT.97.96% 100.00\$

*Equivalent to 1% metallic: copper

MEAD THIS LABEL BEFORE USING PRODUCT

KEEP OUT OF REACH OF CHILDREN

WARNING

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED, induce vomiting. IF INHALED, remove to fresh air. IF ON SKIN, flush with water. IF IN EYES, flush with water for 15 minutes and get medical attention.

SEE SIDE PANEL FOR ADDITIONAL PRECALITIONARY STATEMENTS

> EPA Reg. No. EPA Est. No.

DELTA RESEARCH COMPANY

SENATOBIA, MISS 38668

Net Contents....

Under the Federal Insecticide. Railcoule, and Rodenticide A. s. as amended, for the pesticide regulated under 48/06-9

MAY 1 5 1986

DIRECTIONS

To protect from decay, mildew, termites. and powder post beetles treat wood as follows.

For wood above ground with low decay exposure, such as exterior siding with a roof overhang, apply using two brush coats, a spray, or a three minute dip.

For wood above ground with moderate to high decay exposure, such as fencing pickets or wooden shakes, apply using two brush coats, or a spray, or a three minute dip.

For wood in ground contact exposures, such as fence posts, apply by soaking for 24 hours or longer by hot-cold bath. or by vacuum processes.

Green or dry wood may be treated. Pigments or dyes may be added to the treating solution to provide a desired appearance to treated surfaces.

Treat wood outdoors and use treated wood only for exterior applications. Do not use treated wood where there may be extended periods of skin contact or contact with food or feed.

WARRANTY STATEMENT

Neither Delta Research Company nor the selier makes any representation or CCEPTED werranty, expressed or implied, concerning this material, other than indicated on the label. Neither shall be held responsible in any manner for any personal injury or property damage or other type of loss resulting from the improper handling, storage or use of this material. The buyer accepts and uses this meterial on these conditions