

ACCEPTED
with COMMENTS
by EPA Labor Dept.

SEP 23 1982

Under the Federal Insecticide,
Fungicide and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.

40223-1

ACTIVE INGREDIENT:	
3-IODO-2 PROPYNYL BUTYL CARBAMATE	0.50%
INERT INGREDIENTS	99.50%
TOTAL	100.00%

CONTAINS PETROLEUM DISTILLATES
EPA REG. NO. 48223-1
EPA EST. NO. 48223-PA-1

Finish: Transparent
Average Coverage: 400 to
600 sq ft
Thinner: none required
Application: sponge or
brush
Clean-up: Mineral spirits

ZAR WOOD PRESERVATIVE AND WATER REPELLEN For Above-Grade Use

Formulated to protect wood surfaces against wood rot and fungi that cause mildew. Recommended for use on shingles, shakes, fences, decks, outdoor furniture and smooth or rough cut wood siding. ZAR Wood Preservative provides a strong barrier against fungus, black mold and wood rot. When using under paint, apply sparingly. It is not advisable to recoat with any polyurethane finish.

DIRECTIONS FOR USE: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

SURFACE PREPARATION: Surface must be clean and free of dirt, oil, grease and mildew. Remove mildew with the following washing solution - 1 quart household bleach, 2 tablespoons detergent, 6 tablespoons UGL MEX or UGL TSP (trisodium phosphate) to 9 quarts of water. (Mildew is a dark, fuzzy or powdery deposit on wood surfaces.) Apply washing solution with a scrubbing brush, rinse thoroughly and allow to dry.

APPLICATION: Apply only when air and surface temperatures are above 45°F. DO NOT THIN. May be applied by brush but the ideal method is to soak the wood and saturate it for maximum protection. A common sponge mop will apply product generously. If the surface is to be stained or painted, apply only 1 coat of ZAR Wood Preservative. If the surface is to be left natural, multiple coatings of ZAR Wood Preservative should be applied. Do not apply over surface that has been previously painted, varnished or stained.

DRYING TIME: Allow a minimum of three days drying time before applying an oil base stain or paint or latex base finish, such as ZAR Rain Stain Solid oil base stain or paint or latex base finish, such as ZAR Rain Stain Solid Color Acrylic.

CLEAN-UP: Use UGL Fastrip Brush Cleaner or mineral spirits to remove product from brush. Lacquer thinner may be used to remove product from glass or other surfaces.

PRECAUTIONARY STATEMENTS — HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: CONTAINS PETROLEUM DISTILLATES. Use only with adequate ventilation. Avoid prolonged breathing of vapor or spray mist. Causes substantial but temporary eye injury. Do not get in eyes or on clothing. Wear goggles. Harmful if swallowed. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before re-use.

STATEMENT OF PRACTICAL TREATMENT: IF IN EYES: Flush with plenty of water. Get medical attention. IF SWALLOWED: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

ENVIRONMENTAL HAZARDS: Do not apply directly to water. This product is toxic to fish. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

PHYSICAL AND CHEMICAL HAZARDS: COMBUSTABLE: Do not use, pour or spill near heat or open flame. In case of fire, use water spray, foam, carbon dioxide or dry chemical.

STORAGE AND DISPOSAL:

PROHIBITIONS: Do not contaminate water, food or feed by storage or disposal. Do not store near heat or open flame.
CONTAINER DISPOSAL: Do not reuse empty container. Wrap container and put in trash collection.

United Gilsonite Laboratories
Scranton, PA 18501 • Lincoln, IL • Visalia, CA

BEST DOCUMENT AVAILABLE