

TRIS NITRO[®] BRAND OF 50% AQUEOUS TRIS(HYDROXYMETHYL)NITROMETHANE INDUSTRIAL BACTERIOSTAT

ACTIVE INGREDIENT:		
2-Hydroxymethyl-2-nitro-1,3-propanediol	50%
INERT INGREDIENTS:	50%
		100%

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS

KEEP OUT OF REACH OF CHILDREN

CAUTION!

AVOID CONTACT WITH EYES.
HARMFUL IF SWALLOWED. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING OR SMOKING.
HARMFUL IF INHALED. AVOID BREATHING SPRAY MIST REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE.

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.
IF IN EYES: Flush with plenty of water. Call a physician.
IF ON SKIN: Wash thoroughly with soap and water.
IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration and get medical attention.

ANGUS Chemical Company assumes no responsibility when this product is not used in accordance with the instructions and information contained on this label.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with a NPDES permit. For guidance, contact your Regional Office of the Environmental Protection Agency. Do not contaminate waters by cleaning of equipment or disposal of wastes.

STORAGE AND DISPOSAL

STORAGE: Freezes at 60°F. Store in a warm place. TRIS NITRO decomposes in the presence of alkaline materials. Protect from vapors of ammonia and amines during handling and storage to prevent deterioration and release of formaldehyde.
DISPOSAL: Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. Pesticide or rinsate that cannot be used or chemically reprocessed should be disposed of in a landfill approved for pesticides. Triple rinse or equivalent; all containers. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other approved state and local procedures.

See Additional Precautionary Statements on Side Panel and in Technical Bulletin

EPA Reg. No. 48301-11

Printed in U.S.A.

ANGUS[™]

ANGUS Chemical Company
2211 Sanders Road
Northbrook, IL 60062

DIRECTIONS FOR USE

Federal law prohibits use of this product in metalworking fluids.
USE IN METALWORKING FLUIDS
In Diluted Fluids: A concentration of 1000 to 2000 TRIS NITRO per each 100 gallons of fluid.

Maintenance Dosage: Add 250 to 500 ppm of active ingredient to each 100 gallons of fluid will provide a 250 ppm concentration.
In Concentrates: TRIS NITRO may be incorporated by long as the pH is maintained in the range of 6 to 8. Long term stability tests should be carried out by with TRIS NITRO stability. The amount to be incorporated for bacteriostatic activity, a concentration of 1000 TRIS NITRO per each 100 gallons of fluid.

USE IN INDUSTRIAL RECIRCULATION SYSTEMS

For control of bacteria in industrial recirculation systems.
Initial dose: When the system is noticeably fouled. Badly fouled systems must be cleaned before use.
Subsequent dose: Add 0.25-1 quart of 50% aqueous TRIS NITRO per 2000 barrels of water.

USE IN OILFIELD WATER SYSTEMS

For controlling aerobic slime-forming bacteria (*Desulfuricans*) in oilfield water systems. The severity of the contamination. Add injection pumps and injection well heads.
Continuous-feed method: If the system is noticeably fouled, add TRIS NITRO continuously until the desired degree of control is achieved (1000 TRIS NITRO per 2000 barrels of water) continuously as needed to maintain control.
Intermittent or slug method: If the system is noticeably fouled, add TRIS NITRO (1000 TRIS NITRO per 2000 barrels of water) intermittently as needed to maintain control.

USE AS A PRESERVATIVE FOR PAINTS AND POLISHES CONTAINING WATER

For control of bacterial contamination in paints and polishes containing water. Add 1000 TRIS NITRO per 2000 gallons of formulation.

USE IN DRILLING MUDS

For control of sulfate-reducing bacteria in drilling muds. Add 1000 TRIS NITRO per 2000 gallons of drilling mud.

USE IN PULP AND PAPER MILL PROCESSING

Do not use this product in any process where the product is used to control bacterial growth in pulp or paper (dry basis). Addition of TRIS NITRO should be made with a fiber and water, such as at the beaters. Heavily fouled systems should be bled out. Moderately fouled systems should be treated continuously as needed for control. Lightly fouled systems should be treated continuously as needed for control.

USE IN PAINTS AND EMULSIONS

TRIS NITRO is effective as a preservative in water-based emulsions. TRIS NITRO may be added at the time of formulation. The recommended rate for preservative use is 1000 TRIS NITRO per 2000 gallons of formulation.

BEST DOCUMENT AVAILABLE

48301-11

(METHYL)NITROMETHANE

50%

50%

100%

HAZARDS

Do not apply in marine and or discharge into lakes, streams, ponds, in accordance with a NPDES permit. For Regional Office of the Environmental Protection Agency. Do not contaminate waters by cleaning of equipment.

DISPOSAL

Do not use in the presence of alkaline materials. Protect from amines during handling and storage to prevent formaldehyde.

Do not use as water, food or feed by storage or disposal. Open side or rinsate that cannot be used or chemically recycled in a landfill approved for pesticides. Triple rinse containers. Then offer for recycling or reconditioning or sanitary landfill or by other approved state and local agencies.

See instructions on Side Panel and in Technical Bulletin.

A 67

Printed in U.S.A.

ANGUS Chemical Company
2211 Sanders Road
Northbrook, IL 60062

DIRECTIONS FOR USE

Federal law prohibits use of this product in a manner inconsistent with its labeling.

USE IN METALWORKING FLUIDS

In Diluted Fluids: A concentration of 1000 to 2000 ppm of active TRIS NITRO in the fluid is sufficient to control gross bacterial growth. Add 1-2 quarts of 50% aqueous TRIS NITRO per each 100 gallons of fluid.

Maintenance Dosage: Add 250 to 500 ppm of active TRIS NITRO weekly as required to maintain control of the system. The addition of 0.25 quart of 50% aqueous TRIS NITRO to each 100 gallons of fluid will provide a 250 ppm concentration.

In Concentrates: TRIS NITRO may be incorporated by the manufacturer in metalworking fluid concentrate. The higher levels required in such concentrates will be stable as long as the pH is maintained in the range of 6 to 8. Above such pH levels rapid deterioration of TRIS NITRO may result in the release of noticeable levels of formaldehyde. Long term stability tests should be carried out by the manufacturer on his specific formulation to ensure that the concentrate does not contain ingredients incompatible with TRIS NITRO stability. The amount to be incorporated will depend on the dilution factor recommended to be used when the concentrate is diluted for use. For efficient bacteriostatic activity a concentration of 1000 to 2000 ppm of active TRIS NITRO in the diluted fluid is suggested.

USE IN INDUSTRIAL RECIRCULATING WATER SYSTEMS

For control of bacteria in industrial cooling towers and evaporative condensers, treat the system with 500-1000 ppm of active TRIS NITRO.

Initial dose: When the system is noticeably fouled, add 0.5-1 gallon of 50% aqueous TRIS NITRO per 1000 gallons of water in the system. Repeat until control is achieved. Badly fouled systems must be cleaned before initial treatment.

Subsequent dose: Add 0.25-1 quart of 50% aqueous TRIS NITRO per 1000 gallons of water in the system as needed to maintain control.

USE IN OILFIELD WATER SYSTEMS

For controlling aerobic slime-forming bacteria (*Pseudomonas* sp.) and anaerobic sulfate-reducing bacteria (*Desulfovibrio desulfuricans*) in oilfield water systems, such as subsurface injection water, add 500-1000 ppm active TRIS NITRO depending on the severity of the contamination. Additions should be made with a metering pump at the free-water knockouts before or after injection pumps and injection well headers.

Continuous feed method: If the system is noticeably fouled, add 500-1000 ppm active TRIS NITRO (80-160 gallons of 50% aqueous TRIS NITRO per 2000 barrels of water) continuously until the desired degree of control is achieved. Subsequently, treat with 500 ppm active TRIS NITRO (80 gallons of 50% aqueous TRIS NITRO per 2000 barrels of water) continuously as needed to maintain control.

Intermittent or slug method: If the system is noticeably fouled, in to maintain control of the system, add 500-1000 ppm active TRIS NITRO (80-160 gallons of 50% aqueous TRIS NITRO per 2000 barrels of water) intermittently for 2-8 hours per day, or from 1-4 days per week, depending on the severity of contamination.

USE AS A PRESERVATIVE FOR PACKAGED EMULSIONS, SOLUTIONS, OR SUSPENSIONS SUCH AS DETERGENTS AND POLISHES CONTAINING WATER.

For control of bacterial contamination, add 500-1000 ppm of active TRIS NITRO (1/2-2 gallons of 50% aqueous TRIS NITRO) per 1000 gallons of formulation.

USE IN DRILLING MUDS

For control of sulfate-reducing bacteria in water-based drilling muds, add 0.5 quart-1 gallon of 50% aqueous TRIS NITRO to 1000 gallons of drilling mud.

USE IN PULP AND PAPERMILL PROCESS WATER SYSTEMS

Do not use this product in any process which makes paper or paperboard that will come into contact with food or feed. For control of bacterial growth in pulp, paper, and paperboard mills, add 50% aqueous TRIS NITRO at the rate of 0.25-1.0 gallon per ton of pulp or paper, dry basis. Addition may be continuous or intermittent, depending upon the type of system and the severity of contamination. It should be made with a metering pump at a location that will insure uniform distribution of TRIS NITRO in the mass of fiber and water, such as at the beaters, Jordan mill, or discharge broke chests, furnish chests, save-alls and white-water tanks. Heavily fouled systems should be treated initially with 1 gallon of 50% aqueous TRIS NITRO per ton of paper, dry basis, as necessary for control. Moderate fouled systems should be treated initially with 0.5 gallon of 50% aqueous TRIS NITRO per ton of paper, dry basis, on a continuous or intermittent basis as needed. Light fouled systems should be treated initially with 0.25 gallon of 50% aqueous TRIS NITRO per ton of paper, dry basis, until control is achieved.

USE IN PAINTS AND EMULSIONS

TRIS NITRO is effective as a preservative in water-based emulsions, solutions, and suspensions. It should be added at a concentration of 0.2 to 1.0 lb per 100 lb total formulation weight. TRIS NITRO may be added to the formulation at any stage. The recommended rate for preservation of a latex paint is 0.2 to 0.4 lb per 100 lb of the formulation. The recommended rate for preservation of a water-based emulsion is 0.4 lb per 100 lb of the formulation.

BEST DOCUMENT AVAILABLE



Angus Chemical Company
2211 Sanders Road
Northbrook, IL 60062

03 AUG 1984

Attention: Allen F. Bollmeir, Jr.
Manager Technical Communications

Gentlemen:

Subject: Tris Nitro® Brand of 50% Aqueous Tris
(Hydroxymethyl) Nitromethane
EPA Registration No. 48301-11
Submission Dated July 5, 1984

The amendment referred to above, submitted in connection with registration under FIFRA sec. 3(c)(7)(A), is acceptable provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data.

2. Submit five (5) copies of your final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,

John B. Lee
Product Manager (31)
Disinfectants Branch
Registration Division (TS-767C)

Enclosure

RD/DIS:J.L. (DCP-44029;WAG-61127;G-11011;479-1013;7-25-84;Del.8/10

BEST DOCUMENT AVAILABLE

EPA

OFFICIAL FILE COPY