

ACCEPTED

NOV 13 1990

# AMICAL 48

## ANTIMICROBIAL AGENT

### ACTIVE INGREDIENT:

Diiodomethyl p tolyl sulfone

95%

### INERT INGREDIENTS

Related Compounds & Carriers

5%

TOTAL 100%

### PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS (AND DOMESTIC ANIMALS)

## CAUTION!

### KEEP OUT OF REACH OF CHILDREN

May be harmful if absorbed through skin.

May cause eye irritation

Avoid contact with skin

Wash thoroughly after use

Do not take internally

### STATEMENT OF PRACTICAL TREATMENT

IF ON SKIN, wash thoroughly with water

IF IN EYES, flush with plenty of water and seek medical attention if irritation persists

EPA Reg. No. 48301-19

EPA Est. No. 33657 JP 3

33657 JP-4

U.S. Patent Nos. 3615745, 3657353,  
3663623, 3806351, 4078888,  
and 4130434

### STORAGE AND DISPOSAL

**STORAGE:** Do not contaminate water, food or feed by storage or disposal. Store in a dry area. Keep container closed when not in use.

**PESTICIDE DISPOSAL:** Wastes resulting from use of this product may be disposed of on site or at an approved waste disposal facility.

### CONTAINER DISPOSAL:

Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then dispose of liner in a sanitary landfill or by incineration if allowed by state and local authorities. If drum is contaminated and cannot be reused, dispose of in the same manner.

### ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not contaminate water when disposing of equipment washwaters.

### DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

#### USE IN LATEX PAINTS AND PIGMENTS

Amical 48 is an effective mildewcide for pigment dispersions. Use levels are to be protected and upon the expected latex paint systems formulated without per 100 gallons of paint. In formulations use 2.4 lb Amical 48 per 100 gallons of Amical 48 at concentrations ranging (ingredient). A suggested procedure is glycols, wetting agents and then pigments.

#### USE IN LATEX CAULKS AND ADHESIVES

Amical 48 is recommended for use in mildew growth. It is applied prior to the final cure. Active ingredient is 0.01 to 0.02% (dry basis). Use 0.02 to 0.04 lb Amical 48 per gallon of product. For water based products, use 0.02 to 0.04%.

#### USE IN LEATHER TANNING

Amical 48 is used in protecting chrome from mildew and mold during leather processing. Wet blue during long storage for normal protection of chrome tanned weight of hides use 0.01 to 0.02% (dry basis weight) (0.01 to 0.02% for green weight) (0.01 to 0.02% for chrome weight) to be calculated on the dry basis weight to be 20% dry basis and color. When long hold or export protection for cattle 0.08 to 0.15% for sheep, and recommendations for normal protection during retanning/fatliquor protection hides types is 0.1 to 0.3% on wet blue. In all applications, add the dry Amical 48 preferably by sprinkling across the wet blue done just prior to chrome addition. If formate is added dry prior to chrome retanning/fatliquor, add Amical 48 prior to chrome.

#### USE IN WOOD PRESERVATION - FORMULATED PRODUCTS

Amical 48 can be used for control of rotting organisms. Incorporate Amical 48 in aqueous or solvent based systems. A 0.3 to 1.0% (w/w) solvent based system require a suitable carrier for the active ingredient. For more information, refer to the product literature for the formulated products.

24 Hour  
Emergency  
Telephone

**(318)665-4451**

# ANGUS®

ANGUS Chemical Company  
2211 Sanders Road  
Northbrook, IL 60062 U.S.A.

A 106A