

AMICAL[®] 50

ACCEPTED
May 1 1999
Under Federal
Food, Drug,
and Cosmetic
Administration
Registration
EPA Reg. No. 48301-20

ANTIMICROBIAL AGENT

INGREDIENT:	
methyl p-tolyl sulfone	75%
ADJUVANTS:	
Compounds & Carriers	25%
	<u>TOTAL 100%</u>

CAUTIONARY STATEMENTS (FOR USE BY HUMANS & DOMESTIC ANIMALS)

WARNING!

PREVENTION OF REACH OF CHILDREN

Avoid contact with skin
if absorbed through skin
eye irritation
do not get on skin
wash thoroughly after use.
Do not ingest internally.

STATEMENT OF PRACTICAL TREATMENT

IF ON SKIN, wash thoroughly with water.

IF IN EYES, flush with plenty of water and seek medical attention if irritation persists.

EPA Reg. No. 48301-20
EPA Est. No. 275-L-1

U.S. Patent Nos. 3,615,745, 3,647,353,
3,663,623, 3,806,351, and 4,130,434

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food or feed by storage or disposal. Store in a dry area. Keep container closed when not in use.

PESTICIDE DISPOSAL: Wastes resulting from use of this product may be disposed of on site or at an approved waste disposal facility.

CONTAINER DISPOSAL: Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then dispose of liner in a sanitary landfill or by incineration if allowed by state and local authorities. If drum is contaminated and cannot be reused, dispose of in the same manner.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not contaminate water when disposing of equipment washwaters.

(800) 318-6651

ANGUS

ANGUS Chemical Company
2211 Sanders Road
Northbrook, IL 60062 U.S.A.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

USE IN LATEX PAINTS

Amical 50 is an effective mildewcide for latex paint, containing color suppressants to alleviate off-color sometimes associated with the use of nonmercurial mildewcides. Use levels are dependent upon paint formulation to be protected and upon the expected severity of field conditions. In latex paint systems formulated without zinc oxide, use 4-6 lbs. Amical 50 per 100 gallons of paint. In formulations containing 50 lbs. zinc oxide, use 2-4 lbs. Amical per 100 gallons of paint. For best results and economy in white paint formulations, use 2 lbs. Amical 50 per 100 gallons of paint, plus 50 lbs. of zinc oxide. A suggested procedure is to add the water, Amical 50, glycols, wetting agents and then pigments in the dispersion process.

USE IN LATEX CAULKS AND ADHESIVES

Amical 50 is recommended for use in adhesives and sealants where mildew growth on the applied product may be a problem. Suggested levels (% by wt. active ingredient) are: Ceramic Tile Adhesives 0.02-0.15, Wallboard Joint Compounds (Ready Mix) 0.08-0.30, Vinyl Wallpaper Pastes 0.02-0.12, Mastics 0.05-0.15, Latex Caulks 0.05-0.30. Add Amical 50 at a point in the production process where sufficient mixing will assure good suspension of the material as other ingredients are added.

P4121
48301-20
P4 1071