

ACTIVE INGREDIENT:

2-Bronio-2-nitropropane-1,3-diol 95.0%

INERT INGREDIENTS: 5.0%**TOTAL** 100.0%**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
KEEP OUT OF REACH OF CHILDREN****DANGER****CORROSIVE: CAUSES EYE AND SKIN DAMAGE.
MAY BE FATAL IF SWALLOWED.**

Avoid breathing dust.

Wash thoroughly with soap and water after handling.

Wear goggles or face shield and rubber gloves when handling.

Remove contaminated clothing and wash before reuse.

STATEMENT OF PRACTICAL TREATMENT**IF SWALLOWED:** Drink egg whites, gelatin solution, or if these are not available, drink large quantities of water. Call a Physician.**IF INHALED:** Remove person to fresh air**IF ON SKIN:** Immediately flush skin with plenty of water for 15 minutes**IF IN EYES:** Immediately flush eyes with plenty of water for 15 minutes
Call a Physician.**NOTE TO PHYSICIAN**

Probable mucosal damage may contraindicate the use of gastric lavage

ANGUS Chemical Company assumes no responsibility when this product is not used in accordance with the instructions and information contained on this label

ACCEPTED**MAR 24 1992**Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under 48301-27
EPA Reg. No.**ENVIRONMENTAL HAZARDS**

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste

STORAGE AND DISPOSAL**STORAGE AND DISPOSAL:** Do not contaminate water, food, or feed by storage or disposal. Keep away from heat.**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.**CONTAINER DISPOSAL:** Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Triple rinse (or equivalent) then offer drum for recycling or reconditioning, or puncture. Dispose of drum and liner in a sanitary landfill, or by incineration, if allowed by State and local authorities. If burned, stay out of smoke.

See Additional Precautionary Statements on Side Panel and in Technical Bulletin.

EPA Reg. No. 48301-27

A-126A-1

EPA Est. No. 33753-EN-1

Printed in U.S.A.

ANGUS

ANGUS Chemical Company

2211 Sanders Road

Northbrook, IL 60062 U.S.A.

MYACIDE is a registered trademark of The Boots Company PLC

HYDROCARBON PHASE: MYACIDE AS PLUS may be pre-dissolved in warm water to give up to a 20% concentrate. This concentrate can be injected directly into the water bottom or may be sprayed over the surface of the hydrocarbon phase and allowed to precipitate through. Using a carrier solvent for addition of MYACIDE AS PLUS into the hydrocarbon phase will provide long term water concentrations by a diffusion process.

FREQUENCY AND DOSE: Direct addition to the water phase should be carried out every 30-60 days using a carrier solvent for addition to the hydrocarbon phase will provide longer term water concentrations depending on frequency of hydrocarbon movement, draining of water bottom, and other factors. MYACIDE AS PLUS should be dosed at a rate which will achieve concentrations of 50-100 ppm in the aqueous phase when using a carrier solvent. Higher initial concentrations may be used to allow diffusion into the aqueous phase.

METALWORKING FLUIDS

MYACIDE AS PLUS is recommended for use in soluble oils, semi-synthetic and synthetic fluids. It should be added directly to the sump (with agitation) or pre-dissolved in water and added as a solution. A dose of 200 ppm is recommended for metal treatment, higher levels up to 1800 ppm, but no greater for luvied systems. After addition of MYACIDE AS PLUS, the system should be circulated for about one hour before shut-down.

INJECTED FLUIDS: A concentration of 250 to 1000 ppm of MYACIDE AS PLUS in the fluid is sufficient to control gross microbial growth. For example, add 0.5 lb of MYACIDE AS PLUS to 1000 lb of fluid to obtain a dose level of 500 ppm in the fluid.

MAINTENANCE DOSAGE: Add 100-200 ppm of MYACIDE AS PLUS to maintain control of the system.

CONCENTRATES: MYACIDE AS PLUS may be incorporated in metalworking fluid concentrate by the manufacturer. However, the manufacturer should determine the storage stability of MYACIDE AS PLUS in the concentrate to ensure that incompatibility will not affect its efficacy. The amount to be incorporated will depend on the dilution factor recommended for the concentrate.

PAPER MILL PROCESS WATER

To inhibit slime forming bacteria in paper or paperboard process water systems, MYACIDE AS PLUS may be dosed at the head of a conveyer belt in the process system. Suitable dosing points are the machine chest, constant head box or backwater loop system.

FREQUENCY AND DOSE: MYACIDE AS PLUS should be shock-dosed once, twice or three times daily in quantities sufficient to meet the required dose based on the daily production of finished products. Dose at between 0.02 and 0.5 lb per ton of finished paper or paperboard depending on the complexity of the system, quality of raw paper, and type and degree of contamination.

PAPER MILLS - BULK PULP

To preserve bulk quantities of pulp in paper and paperboard manufacturing systems or to prevent mold odors and general biodegradation of stock when it is stored in bulk for any significant period of time, add MYACIDE AS PLUS to the solid or pre-dissolve in a quantity of warm water, then dose directly into the hydrocyclone, machine chest or stock chest.

FREQUENCY AND DOSE: In general, a single slug dose will provide protection for up to 3 days or longer depending upon the initial level of contamination in the stock. In situations where contamination is high, repeat dosing every 1-7 days may be required. MYACIDE AS PLUS should be dosed at between 0.05-0.44 lb per ton of stock (0.42-1.7 lb/1000 gallons) depending on the type and degree of contamination.

WATER-BASED PRINTING INKS AND FOUNT SOLUTIONS

To inhibit the growth of spoilage bacteria during the storage and use of water-based printing inks and fount solutions, for in-kan preservation, add MYACIDE AS PLUS at any convenient point during the manufacturing process. Ideally, it should be added as a final step after any heating stage and when the product has cooled to below 40°C. To control bacterial spoilage during the use of fount solutions, MYACIDE AS PLUS should be shock-dosed at a suitable point in the fount reservoir where there is adequate flow or turbulence to ensure quick dissemination. MYACIDE AS PLUS may be shock-dosed once or twice weekly as a normal routine. Where conditions indicate, more frequent shock-dosing may be required.

IN-KAN PRESERVATION: MYACIDE AS PLUS should be dosed at 100 to 500 ppm based on the final formulation volume (0.84-4.2 lb/1000 gallons).

FOUNT SOLUTIONS: MYACIDE AS PLUS should be shock-dosed at between 25 and 100 ppm (0.21-0.84 lb/1000 gallons) depending on the contamination level in the fount reservoir.

STARCH, PIGMENT AND EXTENDER SLURRIES

To inhibit the growth of spoilage bacteria during the manufacture, storage and distribution of water-based suspension and concentrates, MYACIDE AS PLUS may be dosed at or close to the end of the manufacturing process as the solid or pre-dissolved in a quantity of the process water. If the manufacturing process involves a heating stage, the MYACIDE AS PLUS should be added after this stage when the product has cooled to below 40°C.

FREQUENCY AND DOSE: MYACIDE AS PLUS should be dosed at 100 to 500 ppm based on the final formulation volume (0.84-4.2 lb/1000 gallons).

PAINTS, LATEX AND ANTIFOAM EMULSION SYSTEMS

To provide in-kan preservation and prevent bacterial spoilage during shelf-life storage of acrylic, styrene-acrylic, polyvinyl acetate and other latex emulsion, concentrates and latex emulsion based paints. Also for the preservation of silicone and other antifoam emulsion systems. Add MYACIDE AS PLUS at any convenient point during the manufacturing process. Ideally, it should be added as a final step just prior to packing of the product into bulk or sales packs. If a heating stage is involved in the manufacture, add MYACIDE AS PLUS after this stage when the product has cooled to below 40°C.

FREQUENCY AND DOSE: MYACIDE AS PLUS should be dosed at 100 to 500 ppm based on the final formulation volume (0.84-4.2 lb/1000 gallons).

ADHESIVES


For the control of microbial contamination, add 0.1-0.5 lb of MYACIDE AS PLUS per 100 lb total formulation weight. The solution is best accomplished by pre-dissolving the MYACIDE AS PLUS in any water to be incorporated into the formulation.

ABSORBENT CLAYS

Impregnate absorbent clays with MYACIDE AS PLUS to inhibit the growth of odor-causing bacteria. The suggested application rate is 25-200ppm (0.04-0.32 oz av.) per 1000 pounds of clay.

ANGUS CHEMICAL COMPANY

ad as ppm are ppm active



DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS AND EVAPORATIVE CONDENSERS

To control slime-forming bacteria and fungi in industrial recirculating cooling towers and evaporative condensers, MYACIDE AS PLUS may be dosed as the solid directly into the sump or basin or it may be added to the cooling water return at a suitable point. The MYACIDE AS PLUS should be added at a point where there is adequate flow or turbulence to ensure quick dissolution (e.g. the pump outlet from the tower sump).

FREQUENCY AND DOSE: MYACIDE AS PLUS may be slug dosed once or twice weekly as a normal routine. Where contamination is heavy, more frequent shock dosing may be required. MYACIDE AS PLUS should be shock dosed at between 0.21-0.84 lb/1000 gallons depending on the condition of the tower, the quality of the raw water input, and the amount of bleed off.

PRODUCED WATER

To inhibit the growth of slime-forming or corrosion-inducing sulfate-reducing bacteria in formation water produced by wells, together with oil or gas, MYACIDE AS PLUS may be used as the solid or pre-dissolved in a quantity of warm water or alcohol, then injected into the water-containing oil or gas stream at any convenient point. It should be injected in slug doses, not as a continuous feed.

FREQUENCY AND DOSE: Depending on severity and rapidity of contamination, MYACIDE AS PLUS should be slug dosed from once a week to once a month with 0.018-0.036 lb per barrel.

INDUSTRIAL PROCESS WATER

Use MYACIDE AS PLUS to effectively control bacterial and algal growth in industrial process water including closed circuit machine cooling (injection molding, etc.) and stored (non-potable) water, as well as to reduce the fouling of pipework, heat exchangers, and condenser tubes, and to minimize microbially produced corrosion. Dosing should be carried out into the sump/tank of the process water system. Shock dosing is preferred. It is not necessary to dilute MYACIDE AS PLUS concentrate prior to dosing. MYACIDE AS PLUS can also be used as an intermittent flush treatment during regular maintenance cleaning of tanks and equipment.

FREQUENCY AND DOSE: In open systems, shock dosing should be carried out on a once weekly to once monthly basis, depending on the degree of contamination. In closed circuit systems, less frequent dosing (once or twice monthly) would be sufficient. Dosing should be carried out to give an initial concentration of 50 ppm (0.42 lb/1000 gallons). When the above treatment has been successful, dosing can be lowered to a maintenance of 10 ppm MYACIDE AS PLUS (0.08 lb/1000 gallons). For intermittent treatment of industrial process waters during routine maintenance, MYACIDE AS PLUS should be used at 100 ppm (0.84 lb/1000 gallons) and a contact time of at least one hour.

DRILLING FLUIDS AND WORKOVER AND COMPLETION FLUIDS

To inhibit the growth of catalytic, slime-forming or sulfate-reducing bacteria in oil and gas well drilling fluids and brines, MYACIDE AS PLUS may be used as the solid or pre-dissolved in a quantity of warm water, then dosed directly into the mud or brine.

FREQUENCY AND DOSE: A single slug dose once to three times each 24 hrs. Dosing may be less frequent where contamination is low. Each slug dose should be 0.018-0.036 lb per barrel (total fluid volume).

PIPELINE MAINTENANCE

To control aerobic and anaerobic bacteria, particularly sulfate-reducing bacteria, growth in oil and gas related production piping and transportation systems, pre-dissolve MYACIDE AS PLUS in warm water or in a carrier solvent to give up to a 20% concentrate. This concentrate can be injected directly into the pipeline or may be added to the hydrocarbon phase. Using carrier solvent addition of the MYACIDE AS PLUS will produce long term water phase concentrations by a diffusion process.

FREQUENCY AND DOSE: Carrier additions will vary with the degree of contamination and volume of fluids through the pipeline. Slug treatments are recommended and can vary from daily to monthly to control growth. MYACIDE AS PLUS should be dosed at a rate which will achieve concentrations of 25-200 ppm in the aqueous phase. While using a carrier solvent, higher concentrations may be used to allow diffusion into the aqueous phase. Dose will depend on the volume of oil or crude and the expected water fraction.

WATERFLOOD

To inhibit the growth of anaerobic and aerobic bacteria in oil waterflood base fluids used in the recovery of oil and gas reservoirs, add MYACIDE AS PLUS as a dry product or pre-dissolve in any base fluid or inject directly at the well head.

FREQUENCY AND DOSE: MYACIDE AS PLUS should be added continuously to waterflood fluids - slug dosing depending on the bottom hole temperature and fluid chemistry at the rate of 25-100 ppm (0.009-0.036 lb per barrel) depending on the quality of the base fluid.

INJECTION FLUIDS

For the control of contamination and corrosion from bacterial sources in flowback fluids that are disposed of through injection into an approved well further off-shore, pre-dissolve MYACIDE AS PLUS as a dry product or pre-dissolve in each volume of fluid prior to injection.

FREQUENCY AND DOSE: MYACIDE AS PLUS should be added at a rate of 50-100 ppm (0.018-0.036 lb per barrel) based on the water percent of the injection fluid.

ENHANCED OIL RECOVERY (EOR) FLUIDS

For the effective control of bacterial growth and minimizing degradation of EOR gels and fluids used in the oil and gas industry, add MYACIDE AS PLUS during mixing as a dry product or pre-dissolve or add by injection during the EOR procedure.

FREQUENCY AND DOSE: MYACIDE AS PLUS should be added throughout the EOR operation at the rate of 50-100 ppm (0.018-0.036 lb per barrel) depending on the quality of the makeup water.

WELL SQUEEZE FLUIDS

For the effective control of aerobic and anaerobic bacteria in squeeze fluids and downhole well bore areas, add MYACIDE AS PLUS during pre-flushing of the well squeeze fluid or (in the case of direct mix injection systems) on squeeze solution may be added by direct injection at the well head during the well squeeze procedure.

FREQUENCY AND DOSE: MYACIDE AS PLUS should be used for each well squeeze operation to ensure best results. Add MYACIDE AS PLUS at a rate of 0.21-0.84 lb/1000 gallons, depending on the quality of the makeup water.

FRACTURING FLUIDS

MYACIDE AS PLUS reduces bacterial contamination and degradation of fracturing gels and fluids used in well stimulation in the oil and gas industry. MYACIDE AS PLUS may be added during pre-flushing of the fracturing fluid or (in the case of direct mix injection systems) on squeeze solution may be added by direct injection at the well head during the fracturing procedure.

FREQUENCY AND DOSE: MYACIDE AS PLUS should be used for each fracturing operation to ensure best results. MYACIDE AS PLUS should be added at a rate of 0.42-0.84 lb/1000 gallons depending on the quality of the makeup water.

Recommended dosing rates