

PM 31 118301-28
 UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

1044

APR 20 1995

Angus Chemical Company
 1500 E. Lake Cook Road
 Buffalo Grove, IL 60089

Attention: Allen Bollmeier
 Manager, Regulatory Affairs

Subject: Myacide S-2
 EPA Registration No. 48301-28
 Your Submission Dated April 11, 1995.

The submissions (correcting use dilutions) referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable provided that you:

1. Make the following labeling changes below before you release the product for shipment bearing the amended labeling.

a. The statement: "Do not get in eyes, on skin or clothing" must be retained.

b. Include the heading: Net Contents

c. Revise the Environmental Hazards section to comply with PR Notice 93-10.

2. A release for shipment of the product bearing the amended labeling constitutes acceptance of these conditions.

3. A stamped copy of the labeling is enclosed for your records.

If you have any questions concerning this letter, contact V. Goncarovs at 703-305-6663.

Sincerely,

Marion Johnson

Product Manager 31

CONCURRENCE

Antimicrobial Program Branch
 Registration Division (7505C)

SYMBOL							
SURNAME							
DATE							

134

2074

MYACIDE® S-2

ACTIVE INGREDIENT:

2-Bromo-2-nitropropane-1,3-diol40.8%

INERT INGREDIENTS:59.2%

TOTAL 100.0%

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS
KEEP OUT OF REACH OF CHILDREN

DANGER

CORROSIVE: CAUSES EYE AND SKIN DAMAGE.
MAY BE FATAL IF SWALLOWED.

Avoid breathing vapor or mist.

Wash thoroughly with soap and water after handling.

Wear goggles or face shield and rubber gloves when handling.

Remove contaminated clothing and wash before reuse.

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Drink egg whites, gelatin solution, or if these are not available, drink large quantities of water. Call a Physician.

IF INHALED: Remove person to fresh air.

IF ON SKIN: Immediately flush skin with plenty of water for 15 minutes.

IF IN EYES: Immediately flush eyes with plenty of water for 15 minutes.
Call a Physician.

NOTE TO PHYSICIAN

Probable mucosal damage may contraindicate the use of gastric lavage.

ANGUS Chemical Company assumes no responsibility when this product is not used in accordance with the instructions and information contained on this label.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office or the EPA. Do not contaminate water by cleaning of equipment or disposal of waste.

STORAGE AND DISPOSAL

STORAGE AND DISPOSAL: Do not contaminate water, food, or feed by storage or disposal. Keep away from heat.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative of the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Completely empty container and triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by procedures approved by state and local authorities.

See Additional Precautionary Statements on Side Panel and in Technical Bulletin.

E.P.A. Reg. No. 48301-28

A-125C-1

Est. No. 33753-EN-1

Printed in U.S.A.

ANGUS®

ANGUS Chemical Company

1500 E. Lake Cook Road

Buffalo Grove, IL 60089 U.S.A.

MYACIDE is a registered trademark of The Boots Company PLC

APR 20 1995

BEST COPY AVAILABLE

7830128

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with the label.

INDUSTRIAL RECIRCULATING WATER SYSTEMS

To control slime-forming bacteria and algae in industrial recirculation cooling towers and evaporative condensers, MYACIDE S-2 may be slug-dosed directly into the sump or basin or it may be added by a suitable chemical pump. Where metering pumps are used, these must be set to deliver the required dose as fast as possible (e.g. within 1 hour). The dosing point should be located close to the outlet from the basin to ensure rapid dispersal around the system.

FREQUENCY AND DOSE: MYACIDE S-2 may be shock-dosed once or twice weekly as a normal routine. Where contamination is heavy, more frequent dosing may be required. In heavily loaded systems, the tower should be drained and cleaned before treating with MYACIDE S-2. MYACIDE S-2 should be shock-dosed at between 0.4-1.0 pt./1000 gallons depending on the condition of the tower, the quality of raw water input, and the amount of bleed off.

PRODUCED WATER

To inhibit the growth of slime-forming or corrosion-inhibiting sulfate-reducing bacteria in formation water produced by wells together with oil or gas, inject MYACIDE S-2 into the water-containing oil or gas stream at any convenient point. It should be injected as slug doses, not as a continuous feed.

FREQUENCY AND DOSE: Depending on severity and rapidity of contamination, MYACIDE S-2 should be slug-dosed from once a week to once a month with 0.025-0.072 pt./barrel.

INDUSTRIAL PROCESS WATER

Use MYACIDE S-2 to effectively control bacterial and algal growth in industrial process water, including closed (recirculation) cooling (distillation) systems, etc., and stored (non-potable) water, as well as to reduce the fouling of pipework, heat exchangers, condenser tubes, and to minimize microbially produced corrosion. Dosing should be carried out into the components of the process water system. Shock-dosing is preferred. MYACIDE S-2 can also be used as an intermittent, flush treatment during regular maintenance cleaning of water lines (non-potable) or equipment.

FREQUENCY AND DOSE: In open systems, shock-dosing should be carried out on a once weekly to once monthly basis, depending on the degree of contamination. In closed circuit systems, with little possibility of re-infection of loss of MYACIDE S-2 because of makeup or blowdown, less frequent dosing (once monthly/bi-monthly) should be sufficient. Dosing should be carried out to give an initial concentration of 100 ppm MYACIDE S-2 (0.0 to 1000 gallons). When the above treatment has been successful, dosing can be lowered to a minimum of 20 ppm MYACIDE S-2 (0.016 pt./1000 gallons). For intermittent treatment of industrial process waters during routine maintenance, MYACIDE S-2 should be used at 200 ppm (1.6 pt./1000 gallons) and a contact time of at least one hour.

OIL FLOODING/INJECTION WATERS

To inhibit the growth of slime-forming or corrosion-inhibiting sulfate-reducing bacteria in oil well injection waters, inject MYACIDE S-2 as a slug dose at any convenient point.

FREQUENCY AND DOSE: Depending on severity and rapidity of contamination, MYACIDE S-2 should be used from once a month at a concentration of 0.4-1.0 pt./1000 gallons.

PIPELINE MAINTENANCE

To control aerobic and anaerobic bacteria, particularly sulfate-reducing bacteria, growth in oil and gas related production piping and transportation systems, inject MYACIDE S-2 directly into the pipeline or add to the hydrocarbon phase. Addition of the MYACIDE S-2 will produce long-term water concentrations by a diffusion process.

FREQUENCY AND DOSE: Slug treatments are recommended and can vary from daily to monthly to control growth. MYACIDE S-2 should be dosed at a rate which will achieve concentrations of 50-400 ppm in the aqueous phase. Higher concentrations may be used to allow diffusion into the aqueous phase. Dose will depend on the volume of crude or oil and the expected water fraction.

DRILLING FLUIDS AND WORKOVER AND COMPLETION FLUIDS

For use in oil and gas well drilling fluids, and brines, inhibiting growth of catalytic, slime-forming or sulfate-reducing bacteria. MYACIDE S-2 may be dosed directly into the mud or brine.

FREQUENCY AND DOSE: A single slug dose once to three times each 24 hours. Dosing may be less frequent where the contamination is low. Each slug dose should be 0.025 to 0.072 pt./barrel total mud volume.

INJECTION FLUIDS

To control contamination and corrosion from bacterial sources in fluid/water fluids that are disposed of through injection into an approved well following approved guidelines, add MYACIDE S-2 to each volume of fluid prior to injection.

FREQUENCY AND DOSE: MYACIDE S-2 should be added at a rate of 100-200 ppm (0.025-0.072 pt./barrel) based on the water content of the injection fluid.

ENHANCED OIL RECOVERY (EOR) FLUIDS

For the effective control of bacterial growth and minimizing degradation of EOR gels and fluids used in the oil and gas industry, add MYACIDE S-2 during mixing or by injection during the EOR procedure.

FREQUENCY AND DOSE: MYACIDE S-2 should be added throughout the EOR operation. MYACIDE S-2 should be added at the rate of 100-200 ppm (0.025-0.072 pt./barrel) depending on the quality of the makeup water.

WELL SQUEEZE FLUIDS

For the effective control of aerobic and anaerobic bacteria in squeeze fluids and downhole well bore areas, add MYACIDE S-2 during the mix or by direct injection of the well head during the well squeeze procedure.

FREQUENCY AND DOSE: MYACIDE S-2 should be used for each well squeeze operation to ensure best results. Add MYACIDE S-2 at a rate of 0.4-1.0 pt./1000 gallons, depending on the quality of the makeup water.

FRACTURING FLUIDS

MYACIDE S-2 reduces bacterial contamination and degradation of fracturing gels and fluids used as well stimulants in the oil and gas industry. Add MYACIDE S-2 directly to the water phase at any stage of the fracturing operation, for example at the pre-flaring stage or by direct injection at the well head in condensed stimulation procedures.

FREQUENCY AND DOSE: MYACIDE S-2 should be used for each fracturing operation to ensure best results. Add MYACIDE S-2 at a rate of 0.4-1.0 pt./1000 gallons, depending on the quality of the makeup water.

ANGUS CHEMICAL COMPANY

Recommended doses expressed in pt./barrel

BEST COPY AVAILABLE

istent with its labeling.

WATER BOTTOMS IN OIL OR TRANSPORTATION TANKS

For effective control of bacterial contamination in water bottoms, in crude, and related hydrocarbon storage systems. Above and below ground storage tanks and large marine systems are all suitable for treatment. MYACIDE S-2 may be injected directly into the water bottom or may be sprayed over the surface of the hydrocarbon phase and allowed to penetrate through.

FREQUENCY AND DOSE: Direct addition to the water phase by injection or percolation should be carried out every 30-60 days, depending on the severity of the problem. Addition to the hydrocarbon phase will result in longer term protection by gradual diffusion from the hydrocarbon phase into the water phase (depending on storage conditions). Incorporate MYACIDE S-2 at a rate which will achieve concentrations of 100-200 ppm in the aqueous phase. Larger quantities may be added when drying the hydrocarbon phase to allow diffusion of active ingredient into the water bottom during the drying time.

METALWORKING FLUIDS

MYACIDE S-2 is recommended for use in soluble oil, semi-synthetic, and synthetic fluids. It should be added directly to the pump (with agitation). A dose of 500 ppm is recommended for initial treatment, higher levels up to 2000 ppm, but no greater for loaded systems. After addition of MYACIDE S-2, the system should be circulated for about one hour before shut down.

IN DILUTED FLUIDS: A concentration of 500 to 2000 ppm of MYACIDE S-2 in the fluid is sufficient to control or suppress microbial growth. For example, add 1.0 gallon MYACIDE S-2 per 1000 gallons fluid to obtain a dose level of 1000 ppm in the fluid.

MAINTENANCE DOSAGE: Add 200-400 ppm of MYACIDE S-2 to maintain control of the system.

IN CONCENTRATES: MYACIDE S-2 may be incorporated in metalworking fluid concentrates by the manufacturer. However, the manufacturer should determine the storage stability of MYACIDE S-2 in the concentrate to ensure that incompatibility will not affect its efficacy. The amount to be incorporated will depend on the dilution factor recommended for the concentrate.

PAPER MILL PROCESS WATER

To control slime forming bacteria in paper or paperboard process water systems, MYACIDE S-2 may be dosed at a convenient point early in the process system. Suitable dosing points are the machine chest, constant head tank or backwater loop system.

FREQUENCY AND DOSE: MYACIDE S-2 should be shock-dosed twice daily or three times daily in quantities sufficient to meet the required dose based on the daily production of finished products. Dose of between 0.04 and 1.0 pint per ton of finished paper or paperboard depending on the complexity of the system, quality of raw paper and type and degree of contamination.

PAPER MILLS - BULK PULP

To preserve bulk quantities of pulp in paper and paperboard manufacturing systems or to prevent fed odors and general biodegradation of stock when it is stored in bulk for any period of time, add MYACIDE S-2 directly into the hydropulper, machine chest or stock chest.

FREQUENCY AND DOSE: In general, a single slug dose will provide control for up to 3 days or longer depending upon the initial level of contamination in the stock. In situations where contamination is high, repeat dosing every 1-7 days may be required. MYACIDE S-2 should be dosed at between 0.0-2.2 pt./1000 gallons per ton of stock depending on the type and degree of contamination.

ADHESIVES

For the control of microbial contamination, add 0.2-1.0 pint of MYACIDE S-2 per 100 lb total formulation weight. The addition is the best accomplished by adding the MYACIDE S-2 to any water to be incorporated into the formulation.

WATER-BASED PRINTING INKS AND FOUNT SOLUTIONS

To inhibit the growth of spoilage bacteria during the storage and use of water-based printing ink and fountain solutions. For in-can preservation, add MYACIDE S-2 at any convenient point during the manufacturing process. Ideally, it should be added as a final step after any heating stage and when the product has cooled to below 40°C. To control bacterial spoilage during the use of fountain solutions, MYACIDE S-2 should be shock-dosed at a suitable point in the fountain reservoir where there is adequate flow or turbulence to ensure quick mixing. MYACIDE S-2 may be shock-dosed once or twice weekly as a normal routine. Where conditions indicate more frequent shock-dosing may be required.

IN CAN PRESERVATION: MYACIDE S-2 should be dosed at 200 to 1000 ppm based on the final formulation volume (1.6 to 8 pt./1000 gallons).

FOUNT SOLUTIONS: MYACIDE S-2 should be shock-dosed at between 40 and 200 ppm (0.32 to 1.6 pt./1000 gallons) depending on the contamination level in the fountain reservoir.

STARCH, PIGMENT AND EXTENDER SLURRIES

To inhibit the growth of spoilage bacteria during the manufacture, storage and distribution of water-based suspension concentrates, MYACIDE S-2 may be dosed at or close to the end of the manufacturing process in a quantity of the process water. If the manufacturing process involves a heating stage, the MYACIDE S-2 should be added after this stage when the product has cooled to below 40°C.

FREQUENCY AND DOSE: MYACIDE S-2 should be dosed at 200 to 1000 ppm based on the final formulation volume (1.6 to 8 pt./1000 gallons).

PAINTS, LATEX AND ANTIFOAM EMULSION SYSTEMS

To provide in-can preservation and prevent bacterial spoilage during shelf life storage of acrylic, styrene-acrylic, polyvinyl acetate and other latex emulsion concentrates and latex emulsion based paints. Also for the preservation of silicone and other antifoam emulsion systems, add MYACIDE S-2 at any convenient point during the manufacturing process. Ideally it should be added as a final step just prior to packing of the product into bulk or case packs. If a heating stage is involved in the manufacture, add MYACIDE S-2 after this stage when the product has cooled to below 40°C.

FREQUENCY AND DOSE: MYACIDE S-2 should be dosed at 200 to 1000 ppm based on the final formulation volume (1.6 to 8 pt./1000 gallons).

ABSORBENT CLAYS

Incorporate absorbent clays with MYACIDE S-2 to inhibit the growth of odor causing bacteria. The suggested application rate is 50-400 ppm (0.08-0.84 oz or 1 pt. per 100+ pounds of clay).

ACCEPTED

COMMENTS

APR 20 1995

ressed as ppm are ppm product as sold.

A-125C-2

4830128

BEST COPY AVAILABLE