


57040: I:CR-31:Dutch:L-13:KENCO:12/06/89:01/20/90:CL:SW:CL:SW:VO:EK:CT

-2-

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.


John H. Lee
Product Manager (31)
Antimicrobial Program Branch
Registration Division (H7505C)

Enclosure

DEC 14 1989

ANTIFOULING PAINT

48302-8

TFA-10 [LA]

Active Ingredients

Cuprous Oxide 49.0%

Inert Ingredients 51.0%

100.0%

Code No.

Batch No.

This product contains the toxic inert ingredient, Tri-orthocresylphosphate (TOCP).

14.5 lbs. per 5 Gallons

KEEP OUT OF REACH OF CHILDREN

WARNING

MAY BE FATAL IF SWALLOWED OR INHALED, HARMFUL IF ABSORBED THROUGH SKIN

SEE REAR LABEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA Establishment No.

EPA Registration No. 48302

CHUGOKU MARINE PAINTS [U.S.A.] INC.

370 Lexington Ave., New York, NY 10017

FRONT PANEL FOR TFA-10 A, EPA FILE SYMBOL 48302-T, AND/OR TFA- O LA, EPA FILE SYMBOL 48302-I.

8

7

ADDITIONAL PRECAUTIONARY STATEMENTS

With COMMENTS
in EPA Letter dated:

HAZARD TO HUMANS & DOMESTIC ANIMALS

Warning. Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe spray mist. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap after handling.

PRACTICAL TREATMENT

If Swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

In In Eyes: Flush with plenty of water. Get medical attention.

If On Skin: Wash with plenty of soap and water. Get medical attention.

If Inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARD

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approval landfill.

CHEMICAL & PHYSICAL HAZARD

Flammable. Keep away from open flame.

STORAGE & DISPOSAL

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA regional Office for Guidance.

DIRECTION FOR USE

(FOR COMMERCIAL USE ONLY)

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

TFA-10 A [LA] is an antifouling paint suitable for application to wood, fiberglass, or metal vessels subject to attack by barnacles, algae, tube-worms, and other fouling marine organisms. TFA-10 A [LA] may be used on vessels in both salt and fresh water.

Stir paint thoroughly before applying. TFA-10 A [LA] may be applied by spray, brush, or roller. Airless spray is strongly recommended if spray is chosen. The surface should be clean and dry prior to paint application. A suitable anticorrosive coating should be applied to metals, and a primer is recommended for wood or fiberglass.

A minimum of two coats is recommended. Allow minimum of 12 hours before returning vessel to water.

For additional information refer to the technical data sheet.