

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

MAY 13 1997

CMP Coatings
1610 Engineers Road
Belle Chasse, LA 70037

SUBJECT: AF SEAFLO Z-100 LE-HS
EPA Registration No. 48302-10
Review of Letter of April 17, 1997


ATTN: Kevin Casey, General Manager

The label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act is acceptable subject to the following comments listed below.

- 1. Change "Fatal, if swallowed" to "Maybe be fatal if swallowed".
- 2. Add, "May be fatal if inhaled". "Harmful, if absorbed through skin."

If you have any further questions, please contact Ms. Barbara Pringle at (703) 308-6236.

Sincerely,



Marshall Swindell
Acting Product Manager 31
Regulatory Branch I
Antimicrobial Division (7505W)

CONCURRENCES

SYMBOL							
SURNAME							
DATE							

New Label

6030

PEST REG. C.D.P.R. TEL: 916-324-1719 APR 25:97 12:29 No.005 P.09

PRECAUTIONARY STATEMENTS
PRACTICAL TREATMENT
MAY BE FATAL IF INHALED,
HARMFUL IF SWALLOWED OR
ABSORBED THROUGH THE SKIN

IF SWALLOWED: Drink promptly large quantities of water. Avoid alcohol. Get medical attention.

IF INHALED: Remove to fresh air.

IF ON SKIN: Wash with soap and water.

IF IN EYES: Flush with water and get immediate medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

ENVIRONMENTAL HAZARDS

This material is toxic to aquatic organisms including fish and shellfish. Do not apply directly to water. Do not contaminate water by cleaning equipment or disposal of waste. Do not allow chips and dust generated during removal to enter water. Dispose of paint debris in an approved landfill.

HAZARD TO HUMANS & DOMESTIC ANIMALS

Danger corrosive. Causes severe skin and eye damage. Wear a face shield, rubber gloves and protective clothing such as long sleeved cotton shirt, long pants and hat when handling. Use in a well ventilated area. When used in confined areas or applied by spraying, wear protective clothing and a pesticide respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11. May be fatal if inhaled, harmful if swallowed or absorbed through the skin. Do not breathe vapors or spray mist. Wash thoroughly with soap and water.

PHYSICAL & CHEMICAL HAZARD

Flammable. Keep away from heat and open flames. FLASH POINT 85°F.

RESTRICTED USE PESTICIDE

Due to toxicity to Aquatic Organisms including shellfish: For sale only to certified commercial applicators and for use only by persons under the direct supervision of an on-site (at the work site) certified commercial applicator.

AF SEAFLO Z-100 LE-HS

THIS PRODUCT WEIGHS 71 LBS. PER 5 GALLONS

DANGER	ACTIVE INGREDIENTS	Code No.
	Cuprous oxide 37.8 Tributyltin Methacrylate (as part of a copolymer) 9.2% Inert ingredients 53.0%	Batch No.
Total 100.0%	Total Tin 3.0%	

KEEP OUT REACH OF CHILDREN

DANGER

MAY BE FATAL IF INHALED, HARMFUL IF SWALLOWED OR ABSORBED THROUGH THE SKIN

CHUGOKU PAINT COMPANY, INC.

1610 Engineers Road, Belle Chasse, LA 70037

EPA Establishment No. 45302-LA-01

EPA Registration No.

45302-10

with COMMENTS to EPA Letter dated

MAY 13 1997

Only change from Cat III to Cat II Inhalation Hazard.

Under the Federal Insecticide, Fungicide, and Rodenticide Act... MAY 13 1997

SP It is unlawful to use this product in any vessel except of vessel.
S Following re-spend abrasion paint removal. Following paint that rec other waste p of according quirements Recovery Ac
O Triple rinse (if recommended) and by local authori
D (F0 it is a violation in a manner in
Users must requirement AF SEAFLO suitable for a vessels subj worms, and should be cl suitable anti metals and fiberglass. A ing. Alerts ing is chosen propriate ME the clothing, by applicat laundered by Clean up with launched off

copy

SPECIAL RESTRICTIONS

to use this product on non-aluminum hulls less than 82 feet (25 meters) in length (on the outboard motor or lower drive unit).

STORAGE & DISPOSAL

removal of old TBT paint, all paint chips, sludge, and any other waste materials from hulls must be disposed of in a sanitary land-fill. Application of new TBT paint, any excess paint, unused paint containers, and any other materials from application must be disposed of in accordance with the Federal, State and local regulations under the Resource Conservation and Recovery Act (RCRA).

CONTAINER DISPOSAL

containers. Then offer for recycling or reuse (if equivalent). Then offer for recycling or reuse, or purchase and dispose of in a sanitary land-fill. Other procedures approved by state and local agencies.

INSTRUCTIONS FOR USE

FOR COMMERCIAL USE ONLY

in accordance with its labeling.

comply with all applicable OSHA

Z-100 LE-HS is an anti-fouling paint application to wood, steel, and fiberglass hulls to protect from barnacles, algae, tube worms, and other fouling organisms. The surface must be clean and dry prior to paint application. A primer is recommended for wood or fiberglass hulls. When spraying, applicators must use appropriate respiratory protection. Production of dust and fumes should be avoided. Contaminated clothing should be removed and washed before reuse. Disposable suits are preferred. Avoid contact with eyes, nose, mouth, or skin. Wash thoroughly before eating or drinking. Ventilate well before re-entrance.

ACCEPTED
WITH COMMENTS
in EPA Letter Dated

MAY 13 1997

Under the Federal Insecticide, Fungicide, and Rodenticide Act, registration for this pesticide was suspended under EPA Regs. No. 18302-10