
 <p style="text-align: center;">U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Pesticide Programs Antimicrobials Division (7510C) 1200 Pennsylvania Avenue NW Washington, D.C. 20460</p> <p style="text-align: center;">NOTICE OF PESTICIDE: <u> x </u> Registration <u> </u> Reregistration</p> <p>(under FIFRA, as amended)</p>	EPA Reg. Number: 48302-13	Date of Issuance: JUL 19 2006
	Term of Issuance: Conditional	
Name of Pesticide Product: Sea Grand Prix 50-US Part B Antifouling Paint Component		
Name and Address of Registrant (include ZIP Code): A. Chigoku Marine Paints, Ltd; CMP Coatings, Inc. 1610 Engineers Road Belle Chasse, LA 70037		
Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.		
On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.		
Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.		
This product is conditionally registered in accordance with FIFRA sec 3(c)(7)(A) provided that you:		
<ol style="list-style-type: none"> 1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA section 4. 2. Make the labeling changes listed below before you release the product for shipment: <ol style="list-style-type: none"> a. Revise the "EPA Registration Number to read, "EPA Reg. No. 48302-13". 		
Signature of Approving Official:  Marshall Swindell Product Manager Team-33 Regulatory Management Branch I Antimicrobials Division (7510P)	Date: JUL 19 2006	

286

Page 2
EPA Registration No. 48302-13

b. Please note that the Product Chemistry and Acute toxicity data must be submitted by December 31, 2006.

3. Submit three (3) copies of your final printed labeling before distributing or selling the product bearing the revised labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510P)

Enclosure: (Stamped Label)

RESTRICTED USE PESTICIDE

Due to Acute Toxicity

For commercial sale to and use only by Certified Applicators or persons under their direct supervision and only for those uses covered by the Certified Applicator's certification.

SEA GRAND PRIX 500-US PART B ANTIFOULING PAINT COMPONENT

ACTIVE INGREDIENTS:

Cuprous Oxide 72.60%

Zinc 2-pyridinethiol-1-oxide 1.41%

INERT INGREDIENTS 25.99%

TOTAL 100.00%

If on the Federal Insecticide, Fungicide and Rodenticide Act as amended for the pesticide, registered under EPA Reg. No. 48302-13

ACCEPTED
with COMMENTS
EPA Letter Dated:
JUL 19 2006

KEEP OUT OF REACH OF CHILDREN

DANGER SKULL & POISON PELIGRO CROSSBONES

Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle. (If you do not understand this label, find someone to explain it to you in detail.)

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

FIRST AID

- If inhaled:
 - Move person to fresh air.
 - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.
 - Call a poison control center or doctor for treatment advice.
- If on skin or clothing
 - Take off contaminated clothing.
 - Rinse skin immediately with plenty of water for 15-20 minutes.
 - Call a poison control center or doctor for treatment advice.
- If in eyes:
 - Hold eye open and rinse slowly and gently with water for 15-20 minutes.
 - Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
 - Call a poison control center or doctor for treatment advice.
- If swallowed:
 - Call a poison control center or doctor immediately for treatment advice.
 - Have person sip a glass of water if able to swallow.
 - Do not induce vomiting unless told to do so by the poison control center or doctor.
 - Do not give anything by mouth to an unconscious person.

For emergencies involving this product, call toll free 1-800-424-9300. Have the product container or label available when seeking treatment advice.

EPA Registration No. 48302-XX

EPA Establishment No. 48302-LA-001

Manufactured by: CMP Coatings, Inc.

A Chugoku Marine Paints Group Company

1610 Engineers Road, Belle Chasse, LA 70037

Weight: 117.1 lbs. Per 5 gallons

Contents: 5 gallons

Code No. _____

Batch No. _____

ACCEPTED
with COMMENTS
EPA Letter Dated:
JUL 19 2006

4 8 6

Sea Grand Prix 500-US Part B
Draft label
03-07-06; rev. 070406 RUP
Page 2 of 4

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

48302-13

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Corrosive. Causes irreversible eye damage and skin irritation. Fatal if swallowed. Do not get in eyes, on skin or on clothing. Wear protective clothing such as protective eyewear, goggles, face shield or safety glasses, gloves, long sleeved cotton shirt, and long pants. May be fatal if inhaled. Do not breathe vapor or spray mist. Wash thoroughly with soap and water after handling. Remove contaminated clothing before reuse.

Personal Protective Equipment (PPE) for Commercial Applicators - Users must wear a disposable coverall with hood, chemical resistant gloves, protective eyewear (goggles, safety glasses, or face shield) long-sleeved shirt and long pants, socks, and chemical resistant footwear. While removing existing paint by sanding or blasting, or applying new paint, users must wear a fit tested, NIOSH approved full face respirator equipped with a combination organic vapor/P-100 prefilter.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of pain debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL & CHEMICAL HAZARDS: Flammable. Keep away from heat and open flame.

STORAGE & DISPOSAL:

PROHIBITIONS: Do not contaminate water, food or feed by storage or disposal.

PESTICIDE STORAGE: Do not allow paint to freeze. Store in cool, dry condition. Keep away from sparks and open flames.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Open dumping is prohibited. Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

CONTAINER DISPOSAL: triple rinse (or equivalent) and dispose of in an approved landfill. Consult Federal, State or local disposal authorities for approved alternative procedures.

ACCEPTED
with COMMENTS
in EPA Letter Dated:
JUL 19 2006
Under the Federal Insecticide,
Fungicide, and Rodenticide Act
amended, for the pesticide,
registered under EPA Reg. No.
48302-13

JUL 19 2006

Sea Grand Prix 500-US Part B
Draft label
03-07-06
Page 3 of 4

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

DIRECTIONS FOR USE

(FOR COMMERCIAL USE ONLY BY PROFESSIONAL APPLICATORS)

48302-13

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

FIRST STEP: -- MIX (POUR) the contents of Part B with Part A and stir thoroughly. Do not apply until after PART A and PART B have been thoroughly mixed then proceed with following directions.

PRODUCT DESCRIPTION -- SEA GRANDPRIX 500 (A + B) is a self-polishing antifouling paint, based on zinc acrylate resin. It is suitable for application to wood, fiberglass, or metal vessels subject to attack by barnacles, algae, tubeworms, and other marine organisms. SEA GRANDPRIX 500 (A + B) may be used on vessels in both salt and fresh water. It is a very high performance antifouling paint for worldwide service with extended drydocking intervals up to 60 months.

APPLICATION METHOD & LIMITATIONS: -- SEA GRANDPRIX 500 (A + B) may be applied by spray, brush or roller. It may be used over suitable existing coatings. Preferable preceding coatings include: BANNOH 500, SILVAX SQ-K, VINYL AC-HB, RAVAX AC-HB and HIPER AC.

Airless spray is strongly recommended, if spray is chosen. Application by brush or roller may require more than one coat and should be considered for small surfaces only. Apply in good weather when air and surface temperatures are above 35°F (2°C). Surface temperature must be at least 5°F (3°C) above dew point. For optimum application conditions, paint should be between 70-80°F (21 - 27°C) before mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 35-95°F (2-38°C) with a minimum of 0°C.

Apply 6.3-12.6 mils (160-320 microns) wet film to yield about 3 - 6 mils (75-150 microns) dry film thickness. Consult the following equipment recommendations or use a suitable equivalent. For Airless Spray: Tip No. Graco 621-723; paint output pressure 117-140 Kgf/cm²; viscosity 60 sec (Ford Cup No. 4); and theoretical spreading rate 6 m²/l (at 75 microns) are recommended.

MIXING: -- This paint is a one-pack coating for vessels. Always stir thoroughly preferably with a power agitator before use.

THINNING: -- Paint is formulated at spray viscosity and normally does not need to be thinned. If thinning is necessary, thin up to a maximum of 5% (by volume) with a recognized paint thinner such as RAVAX Thinner or seek assistance from CMP Coatings.

THEORETICAL COVERAGE: -- 192 sq. ft/gal at 4.0 mils or 960 sq. ft per container.

ACCEPTED
with COMMENTS
in EPA Letter Dated:
JUL 19 2006
Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.
48302-13

PREPARATION OF SURFACE – The surface must be clean and dry prior to paint application. Remove all dirt, grease, oil, soluble contaminants and other detrimental “foreign” matter by cleaning. For unpainted surfaces, prepare surface and apply recommended primer, according to manufacturers specifications. A suitable anticorrosive coating should be applied to metals and a primer is recommended for wood or fiberglass before applying this product. To re-apply SEA GRAND PRIX 500 (A + B) use controlled close high-pressure fresh-water washing to clean the entire area and to remove any “leached” layer on the existing surface. Exercise care not to damage preceding coats. Repair corroded areas with the recommended anticorrosive primer.

COATING DATA: Airless spray. Thinning not recommended, but if necessary use a recognized thinner as specified above.

Conditions	Temperature	5°C	10°C	20°C	30°C
Drying time: (at DFT 100µ)	Surface dry	3 hrs.	2 hrs.	1 hr.	30 min.
	Hard dry	12 hrs.	8 hrs.	5 hrs.	4 hrs.
Overcoating interval (at DFT 100µ)	Minimum	12 hrs.	8 hrs.	5 hrs.	4 hrs.
	Maximum	30 days	30 days	30 days	30 days
Dry to launch (at DFT 100µ)	Minimum	24 hrs.	18 hrs.	12 hrs.	10 hrs.
	Maximum	30 days	30 days	30 days	30 days

DFT = Dry Film Thickness

Vessel may be launched after recommended drying time.

CLEANUP – Clean all equipment immediately after use with a recognized paint thinner. Spray equipment must be flushed with this solvent. Periodically flush-out spray equipment during the working day. Frequency of cleaning/flushing will depend on such factors as amount sprayed, temperature and elapsed time including breaks. The condition of the equipment needs to be monitored continuously.

PAINT SYSTEMS AND COMPATIBILITY: CMP Coatings should be consulted for detailed application suggestions, recommendations about specifications and suitability of specific products on individual vessels.

End

**ACCEPTED
with COMMENTS
EPA Letter Dated:**

JUL 19 2006

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

48302-13