

Contents: LIQUID

Active Ingredients:

beta-Bromo-beta-Nitrostyrene 10.0%

Inert Ingredients*: 90.0%

Total 100.0%

*Inert ingredients include solubilizing and dispersing agents.

EPA Reg. No. 48525-9

WEIGHT PER GALLON OF PRODUCT

7.9 Pounds (61F)

NET WEIGHT OR VOLUME
AS MARKED ON CONTAINER

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

In case of contact with skin, wash immediately with plenty of soap and water. Immediately contact physician.

In case of contact with eyes, flush promptly and thoroughly with clear water for at least 15 minutes. Immediately contact physician.

In case of inhalation, remove affected person from contaminated area to fresh air. Immediately contact physician.

In case of ingestion, immediately contact physician. Never give anything by mouth to an unconscious person.

A Material Safety Data Sheet containing more detailed information relative to this product is available upon request.

See left panel for additional Precautionary Statements.

This product may be added to the systems either continuously or intermittently as needed. The frequency of feeding and duration of the treatment will depend upon the severity of the problem.

BADLY FOULED SYSTEMS must be cleaned before treatment is begun.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, add BETZ EnChem 41-J4 at the rate of 10 to 100 pounds (30 to 300 ppm) per 1000 barrels of water intermittently for 4 to 8 hours per day and from 1 to 4 times per week or as needed. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add BETZ EnChem 41-J4 at the rate of 10 to 50 pounds (30 to 150 ppm) per 1000 barrels of water every 3 days or as needed to maintain control.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, add BETZ EnChem 41-J4 at the rate of 10 to 100 pounds (30 to 300 ppm) per 1000 barrels of water in the system.

SUBSEQUENT DOSE: Continuously feed BETZ EnChem 41-J4 to maintain a dosage of 3 to 50 pounds (10 to 150 ppm) per 1000 barrels of water in the system.

PACKER FLUIDS AND DRILLING MUDS

Add BETZ EnChem 41-J4 directly to the packer fluid or drilling mud at the rate of 50 to 500 pounds (80 to 800 ppm) per 1000 barrels. The dosage rate will depend upon the severity of the problem.

ACCEPTED
SEP 19 1984
48525-9

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND ROVIDENTICIDE ACT
FOR EQUIPMENT POISON REGISTERS
ED UNDER NO.

STORAGE AND DISPOSAL

STORAGE: Keep container tightly closed. Protect from freezing. Store in a dry place. Do not store at elevated temperatures.

DISPOSAL: Do not contaminate water, food or feed by storage or disposal.

Pesticide wastes are acutely hazardous and/or toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Metal and Plastic Containers: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incinerate or burn, if allowed by state and local authorities. If burned, stay out of smoke.

Fiber Drums with Liners: Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then dispose of liner and drum in a sanitary landfill or incinerate if allowed by state and local authorities. Do not reuse empty drum or liner.

FOR INDUSTRIAL USE ONLY. Technical advice regarding specific site problems is available from BETZ Energy Chemicals, Inc.

BETZ ENERGY CHEMICALS, INC., Carpinteria, CA 93013

Phone: 805-684-6991 — Emergency (Health or Accident): 215-355-3300

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND
DOMESTIC ANIMALS**

DANGER

HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN. Causes eye burns and skin irritation. Do not get into eyes, on skin or on clothing. Avoid breathing vapor or mist. Use with adequate ventilation. Wear rubber gloves, goggles and face shield when handling.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not apply in marine and/or estuarine oil fields. Do not discharge into lakes, streams, ponds or public water unless in accordance with a NPDES permit. For guidance contact your Regional Office of the EPA. Do not contaminate water by cleaning of container and equipment or disposal of wastes. Apply this pesticide only as specified on this label.

PHYSICAL AND CHEMICAL HAZARDS

Combustible. Do not use, pour or store near heat or open flame.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For the control of slime forming bacteria, fungi, algae and sulfide-producing bacteria in oil field water, polymer, or mycellar floods, water disposal systems or other field water systems, packer fluids and drilling muds.

(Directions for Use continued on third panel.)

Contents: LIQUID

Active Ingredients:

beta-Bromo-beta-Nitrostyrene 10.0%

Inert Ingredients*: 90.0%

Total 100.0%

*Inert ingredients include solubilizing and dispersing agents.

EPA Reg. No. 48525-9

WEIGHT PER GALLON OF PRODUCT
7.9 Pounds (61F)

NET WEIGHT OR VOLUME
AS MARKED ON CONTAINER

**KEEP OUT OF REACH OF CHILDREN
DANGER**

STATEMENT OF PRACTICAL TREATMENT

In case of contact with skin, wash immediately with plenty of soap and water. Immediately contact physician.

In case of contact with eyes, flush promptly and thoroughly with clear water for at least 15 minutes. Immediately contact physician.

In case of inhalation, remove affected person from contaminated area to fresh air. Immediately contact physician.

In case of ingestion, immediately contact physician. Never give anything by mouth to an unconscious person.

A Material Safety Data Sheet containing more detailed information relative to this product is available upon request.

See left panel for additional Precautionary Statements.

This product may be added to the systems either continuously or intermittently as needed. The frequency of feeding and duration of the treatment will depend upon the severity of the problem.

BADLY FOULED SYSTEMS must be cleaned before treatment is begun.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, add BETZ EnChem 41-J4 at the rate of 10 to 100 pounds (30 to 300 ppm) per 1000 barrels of water intermittently for 4 to 8 hours per day and from 1 to 4 times per week or as needed. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add BETZ EnChem 41-J4 at the rate of 10 to 50 pounds (30 to 150 ppm) per 1000 barrels of water every 3 days or as needed to maintain control.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, add BETZ EnChem 41-J4 at the rate of 10 to 100 pounds (30 to 300 ppm) per 1000 barrels of water in the system.

SUBSEQUENT DOSE: Continuously feed BETZ EnChem 41-J4 to maintain a dosage of 3 to 50 pounds (10 to 150 ppm) per 1000 barrels of water in the system.

PACKER FLUIDS AND DRILLING MUDS

Add BETZ EnChem 41-J4 directly to the packer fluid or drilling mud at the rate of 50 to 500 pounds (80 to 800 ppm) per 1000 barrels. The dosage rate will depend upon the severity of the problem.

ACCEPTED
SEP 19 1984
48525-9
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND ROENTICIDE ACT
FOR REGISTRATION PURPOSES
ED UNDER NO.

ENGCH023 8406

BETZ ENERGY CHEMICALS, INC., Carpinteria, CA 93013
Business Phone: 805-684-6991 — Emergency (Health or Accident): 215-