

CX-30 will control algae and bacterial slimes found in recirculating cooling tower waters, oil field water flood and crude oil pipelines and storage facilities

CX-30 helps clean and loosen slime debris from cooling and flooding system surfaces. When used in slug doses, no other microbiocide is required.

CX-30 is economical to use because it is concentrated. It should be handled with care.

Precautionary Statements

Hazards to Humans and domestic animals

DANGER:

Keep Out of Reach of Children. Corrosive. Causes severe eye and skin damage. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not discharge treated effluent into lakes, streams, ponds, or public waters unless in accordance with a NPDES permit. For guidance contact your Regional Office of the Environmental Protection Agency.

PHYSICAL HAZARDS

DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME

STORAGE AND DISPOSAL

-DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL
-OPEN DUMPING IS PROHIBITED
-DO NOT REUSE EMPTY CONTAINER

PESTICIDE DISPOSAL

PESTICIDE THAT CANNOT BE USED OR CHEMICALLY REPROCESSED SHOULD BE DISPOSED OF IN A LANDFILL APPROVED FOR PESTICIDES OR BURIED IN A SAFE PLACE AWAY FROM WATER SUPPLIES

CONTAINER DISPOSAL

DISPOSE OF IN AN INCINERATOR OR LANDFILL APPROVED FOR PESTICIDE CONTAINERS. BURY IN A SAFE PLACE OR RETURN TO DRUM RECONDITIONER

GENERAL

CONSULT FEDERAL, STATE OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES

BEST DOCUMENT AVAILABLE

CX-30

Water Treatment Microbiocide for the effective control of a broad spectrum of microorganisms in building and industrial recirculating cooling towers, oil field flood or salt water disposal systems and crude oil pipelines and storage facilities

Active Ingredient

1-Hydroxyethyl-1-benzyl-2-alkyl*
Imidazolium chloride 50%

Inert Ingredients

50%

100%

*Alkyl as in fatty acids of coconut oil

KEEP OUT OF REACH OF CHILDREN

DANGER

Statement of Practical Treatment

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.

If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression, and convulsion may be needed.

SEE LEFT PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA Registration No.

EPA Establishment No.

Net Volume

49766-CA-1

55 gals

EDFRED CHEMICAL CORPORATION

1775 SOUTH FIRST STREET SAN JOSE CA 95112

FOR SALE FOR USE AND STORAGE BY MAINTENANCE PERSONNEL ONLY

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

For controlling Algae, fungi, and a broad spectrum of bacteria and bacterial slime forming organisms that cause inefficient operating of building and industrial recirculating cooling towers, oil field water flood and crude oil pipeline and storage facilities, use CX-30 as directed. For best results, slug feed. The frequency of addition of microbiocides needed depends on many factors. To optimize your use of CX-30 follow this procedure:

Recirculating Cooling Towers

1. Initially use 7 fluid ounces per 1000 gallons of water to be treated (25 ppm active quaternary). Should the above dosage not give satisfactory results, use 13 fluid ounces per 1000 gallons of water. Repeat the initial dose every seven days or increase the frequency if needed.
2. When the above treatment level is successful, use 3 to 4 fluid ounces per 1000 gallons of water to maximize efficiency. Repeat weekly as needed. Should slime develop again, go back to initial dosage.

Recirculating cooling tower waters that are inherently low in algae growth and bacteria count may be adequately controlled by the lower range of these dosages, slug feed every seven days.

Dilute the appropriate amount of CX-30 in 1 or 2 gallons of water, then add to the sump of the tower. Note this product weighs 7.76 lbs per gallon (at 20°C).

Should tower be heavily fouled, a precleaning is required.

Oil Field Water Flood or Salt Water Disposal Systems: (Do not apply in Marine and Estuarine Oil Fields)

1. For the control of slime forming and sulfate reducing bacteria in oil field water flood or salt water disposal systems, add 35-50 ppm (active) CX-30 (9 1/2 - 13 gallons per 3000 barrels of water) continuously. Levels for effective control will vary depending on conditions at the site.
2. For intermittent use, dose at a rate of 35-70 ppm (active) CX-30 (9 1/2 - 18 gallons per 3000 barrels of water) for 4-8 hours per day, one to four times a week as needed to maintain control.

Crude Oil Pipeline and Storage Facilities

1. For the control of sulfate reducing bacteria, heterotrophic bacteria and corrosion in crude oil pipelines, slug dose with 0.5-3 gallons of CX-30 per 3/4 inch diameter per mile of pipeline. Apply the appropriate dosage in slug form in front of the pipeline pig as required by the system.
2. For continuous pipeline feed applications, add 9.5-13 gallons of CX-30 per 3000 barrels of crude oil. CX-30 is added to the pipeline directly behind the pig.
3. For the treatment of crude oil storage facilities, add CX-30 at the rate of 9.5-13 gallons per 3000 barrels of crude oil. Add CX-30 directly from the drum with the proper type of metering equipment. This product weighs 7.76 lbs/gallon (at 20°C). Since crude oil pipeline and storage facilities differ in the metering and application methods, the recommended dosages may require adjustment based on practical experience.

In EPA Labeling

JUL 25 1984

49766-3

