

Hydro-Klear 300

ACTIVE INGREDIENT:

Potassium dimethyldithiocarbamate 12.5%

INERT INGREDIENTS 87.5%

This product contains 1.1 lb. of active ingredient per gallon and weighs 8.77 lb. per gallon.

**KEEP OUT OF REACH OF CHILDREN
DANGER**

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes eye and skin damage. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Avoid contamination of food. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly after handling.

STATEMENT OF PRACTICAL TREATMENT: *In case of skin contact, wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. If product gets in the eyes, flush immediately with copious amounts of clean, cool water for at least 15 minutes. Get medical attention immediately. If product is swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician. Never induce vomiting or give anything by mouth to an unconscious person.*

Note to physician: Probable mucosal damage may contraindicate gastric lavage.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not discharge effluent containing this active ingredient into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Manufactured by:
Specialty Chemical Mfg., Inc.
115 W. Clark St.
Quincy, Fl. 32351

EPA REG. NO. 50584-1 EPA EST. NO. 50584-FL-01

NET CONTENTS _____


DIRECTIONS FOR USE

10FL
PM 5/1
50584-1

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Hydro-Klear 300 is used in industrial and/or commercial recirculating cooling tower systems and industrial air-washing systems to control microbiological slime. Prior to the use of Hydro-Klear 300 in industrial and/or commercial recirculating cooling tower systems, systems should be cleaned to remove algal growth, microbiological slime, and other deposits. Then make an initial slug addition of 9.5 to 14.2 fl. oz. of Hydro-Klear 300 per 1000 gal. of water to provide 80 to 120 ppm of Hydro-Klear 300, based on total weight of water in the system. Repeat initial dosage until control is evident. Make subsequent slug addition of 4.7 to 14.2 fl. oz. of Hydro-Klear 300 per 1000 gal. of water (40 to 120 ppm Hydro-Klear 300) every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of recirculating cooling tower systems.

Hydro-Klear 300 is used in industrial air-washing systems which maintain effective micro-eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 22.2 to 28.4 fl. oz. of Hydro-Klear 300 per 1000 gal. of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 16.5 to 28.4 fl. oz. of Hydro-Klear 300 per 1000 gallons of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump, or the water collection trays of the airwash system.



STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Do not expose to extreme temperatures. Do not stack more than four drums high. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL:

- PLASTIC: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.
- METAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.