

PM 31 51647-14

1944

US ENVIRONMENTAL PROTECTION AGENCY  
OFFICE OF PESTICIDES PROGRAMS  
REGISTRATION DIVISION (TS-767)  
WASHINGTON, DC 20460

EPA REGISTRATION NO.  
51647-14

DATE OF ISSUANCE  
MAY 6 1994

NOTICE OF PESTICIDE:  REGISTRATION  
 REREGISTRATION  
(Under the Federal Insecticide, Fungicide,  
and Rodenticide Act, as amended)

NAME OF PESTICIDE PRODUCT  
Copper Paint No. 6  
Rappoxy 45 Red

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

Rappahannock Copper Paint Company, Inc.  
1200 George Wood Drive  
Elizabeth City, NC 27909

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an endorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.

2. Make the labeling changes listed below before you release the product for shipment:

- a. Add the phrase "EPA Registration No. 51647-14"
- b. Delete the heading "Directions For Use" on the left panel of your label. Move the statement "It is a violation of federal law to use this product in a manner inconsistent with its labeling." so that it appears immediately below the heading "Directions For Use" on the right panel.
- c. Please note that based upon your Confidential Statement of Formula (CSF), you may declare no more than 44.7% Cuprous oxide for the basic and the alternate black formulas.

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL

DATE

- d. Change "Active Ingredients" to "Active Ingredient". Also place the metallic copper equivalency statement outside the ingredient statement, below Inert Ingredients, and enter the correct percentage of metallic copper.
- e. In the substatement "This product contains petroleum distillates" the word petroleum should be spelled with a capital "P" for consistency.
- f. Under the Physical and Chemical Hazards heading use the complete statement "Do not use or store near heat or open flame."
- g. Remove the parentheses from the statement "& Domestic Animals."
- h. Include the following product descriptor below your product name "An Antifoulant Boat Bottom Paint."
- i. Revise the "If Swallowed" statement to read "If swallowed, drink promptly a large quantity of water. Avoid Alcohol. Get medical attention."
- j. Revise your storage and disposal statement to read as follows:

**STORAGE AND DISPOSAL**

Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited.

**PESTICIDE DISPOSAL**

Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

**CONTAINER DISPOSAL**

Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved State and local procedures. If burned stay out of smoke.

The heading "STORAGE AND DISPOSAL" must be of the same type size as the child hazard warning statement.

- k. On the center panel, the words "MFD By" must be spelled out to read "Manufactured By".


3. Submit a revised Confidential Statement of Formula using EPA Form 8570-4 (Rev. 2-85) which includes columns for certified limits. A copy of a correct CSF form is enclosed for your use.

4. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



John H. Lee  
Product Manager (31)  
Antimicrobial Program Branch  
Registration Division (H7505C)

Enclosures

)

QUALITY PRODUCTS  
FOR THE COMMERCIAL WATERM

**RAPPAHANNOCK**

Copper Paint  
No. 6  
RAPPOXY (45)

**RED**

ACTIVE INGREDIENTS  
CUPROUS OXIDE

45.2% 44

(Copper as Metallic) 39.8%

INERT INGREDIENTS

54.8% 55

100.00%

This Product Contains petroleum Distillates\*

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS  
(& DOMESTIC ANIMALS)**

• WARNING •

**CAUSES EYE IRRITATION.** Harmful if absorbed through skin. Avoid contact with skin, eyes, or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist while spraying paint or sanding boat surface. Wear a mask or respirator jointly approved by The Mining Enforcement and Safety Administration and The National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

**ENVIRONMENTAL HAZARDS**

This Material is Toxic to Fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

**PHYSICAL or CHEMICAL HAZARDS**  
Do Not Use or Store Near An Open Flame.

**DIRECTIONS FOR USE**

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

**STORAGE AND DISPOSAL**

**STORAGE**

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Store in a cool, dry area away from heat or open flame.

**DISPOSAL**

Pesticide spray mixture or rinse water that cannot be used according to label instructions must be disposed of according to applicable Federal, state or local procedures.

Container—Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

ACCEPTED  
with COMMENTS  
to EPA Letter Dated  
MAY 06 1994  
Under the Federal Fungicide, and Rodenticide Act, amended, for the pesticide registered under EPA Reg. No. 51647-14

Keep Out of Reach of Children

• WARNING •

STATEMENT OF PRACTICAL TREATMENT

**IF SWALLOWED:** Drink promptly a large quantity of milk, egg whites, or these are not available, drink large quantities of water. Avoid Alcohol. Get Medical Attention.

**IF INHALED:** Remove victim to fresh air. If not breathing, give artificial respiration mouth-to-mouth. Get Medical Attention.

**IF ON SKIN:** Wash with plenty of soap and water. Get Medical Attention.

**IF IN EYES:** Flush with plenty of water. Get Medical Attention.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

MFD. BY: Rappahannock Copper Paint Co., Inc.  
Elizabeth City, NC 27909

Establishment No. 51647-NC-01  
EPA Registration No. 51647-

**NET CONTENTS — ONE GALLON**

475

especially to prevent the attachment of both plant and animal fouling on vessel immersed in both seawater and "brackish" water.

When used over steel or aluminum surfaces, a primer coating is required to prevent accelerated corrosion. This coating requires no primer when used directly over fiberglass or wood. For optimum performance, two (2) coats are recommended. The theoretical coverage of this product is at least 400 square feet per gallon, when applied to the recommended dry film thickness.

To prepare the surface for coating, remove all old coating and fouling residue by either washing with high pressure water, scraping or by disc sanding. Be sure to use the proper protective equipment to prevent inhalation or ingestion of the paint dust generated.

A clean dry surface, free of scale, corrosion, dirt, grease, oil, marine fouling, or other foreign matter will provide the optimum performance of this coating, when used for either complete coating or for touch-up. Inadequate surface preparation will result in unsatisfactory performance. Be sure to remove all dust, debris and other surface contaminations that are generated by the cleaning process, prior to painting.

Mix the coating with either a high speed mixer, or a paint shaker for a minimum of five (5) minutes to insure complete pigment reincorporation. Thin in the event that the coating is too thick to apply easily. Thin with mineral spirits or kerosene. Clean up with mineral spirits or kerosene.

Apply by either brush, roller, or spray. Be sure to follow mixing instructions and apply the correct thickness. Allow a minimum of four (4) hours between coats and a minimum of two (2) hours before undocking vessel.