

ACTIVE INGREDIENTS: Disodium cyanodithioimidocarbonate	<u>3.68</u> %
Potassium N-methyldithiocarbamate	5.07 %
INERT INGREDIENTS	91.25 %
TOTAL	
This product contains 0.77 lb. of active ingredient 8.81 lb. per gallon.	ts per gallon and weighs

KEEP OUT OF REACH OF CHILDREN

WARNING

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed, Avoid contamination of food.

STATEMENT OF PRACTICAL TREATMENT: In case of contact, immediately faish ever or skin with plenty of water for at least 15 minutes. For eyes, call a physician, itemms and wash contaminated clothing before rause. If awallowed, call a physician or Poison Control Center, Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.

ENVIRONMENTA: HAZARIDS: This pesticide is toxic to fish. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with

DIRECTIONS FOR USE GENERAL CLASSIFICATION

ē

EPA REG. NO. __51661-2

It is a violation of Federal law to a sistent with its labeling.	use this product in a manner income.	
w C 610	h used to control place and becasio	
Is used to contro! algae and bacteria in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological alime, and other deposits. An initial slug addition of \$\frac{6.9}{6.9}\$ to \$\frac{13.9}{13.9}\$ fluid ounces of \$\frac{\text{W C 610}}{\text{U C 610}}\$ per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent alug additions of \$\frac{2.3}{2.3}\$ to \$\frac{13.9}{13.9}\$ fluid ounces of \$\frac{\text{W C 610}}{\text{W C 610}}\$ per 1000 gallons of water should be amplied at \$\text{W C 610}\$ per 1000 gallons of water should be amplied at \$\text{W C 610}\$ per 1000 gallons of water should be amplied at \$\text{W C 610}\$ per 1000 gallons of water should be amplied at \$\text{W C 610}\$ per 1000 gallons of water should be amplied at \$\text{W C 610}\$ per 1000 gallons of water should be amplied at \$\text{W C 610}\$ per 1000 gallons of water should be amplied addition should be made in the sump of water cooling towers.		
STORAGE AND DISPOSAL		
PROHIBITIONS: Do not contaminate water, food, or feed by storage to disposal. Open dumping is prohibited. PESTICIDE DISPOSAL: Pesticide, spray mixture, or rinsate that cannot used or chemically reprocessed should be disposed of in a landfill approved for pesticides, or buried in a safe place away from water supplies.		
CONTAINER DISPOSAL: METAL: Triple rinse (or equivalent) and offer for recycling, reconditioning, or disposal in an approved landfill or bury in a safe place. Containers over (x) gallons should be resealed before offering for reconditioning		
rinsed and disposed of in an incine tainers or buried in a safe place. Co and offered for reconditioning or t	ons must not be reused but should be trade rator or landfill approved for pesticide constitutions over 30 gallons are to be rescaled triple rinsed (or equivalent) and offered for salin an approved landfill or buried in a salin	
GENERAL: Consult Federal, State, or Local disposal authorities for appending alternative procedures.		

Manufactured by:
WC Chemical Engineering
1641 Princeton Avenue
Modesto, CA 95350
EPAEST NO 915.