

U.S. ENVIRONMENTAL PROTECTION AGENCY
OFFICE OF PESTICIDES PROGRAMS
REGISTRATION DIVISION (IS 262)
WASHINGTON, DC 20460

EPA REGISTRATION NO.

DATE OF ISSUANCE

01EC 2 1988

TERM OF ISSUANCE

NOTICE OF PESTICIDE REGISTRATION

NAME OF PESTICIDE PRODUCT

NAME OF APPLICANT (PRINT NAME AND ADDRESS)

NOTE: This notice is issued to inform you that a pesticide registered with this Agency in this State is being registered in this State. If you are a registrant in this State, you should be advised that the pesticide is being registered in this State. In any event, you should be advised that the pesticide is being registered in this State.

If the pesticide is not registered in this State, you should be advised that the pesticide is being registered in this State. If you are a registrant in this State, you should be advised that the pesticide is being registered in this State.

A copy of this notice is being sent to the Registrant. If you are a registrant in this State, you should be advised that the pesticide is being registered in this State.

Registration of a pesticide in this State is subject to approval of the pesticide by the Agency. In order to protect health and the environment, the Agency may require additional information or testing of the pesticide. If you are a registrant in this State, you should be advised that the pesticide is being registered in this State. A copy of this notice is being sent to the Registrant. If you are a registrant in this State, you should be advised that the pesticide is being registered in this State.

BEST AVAILABLE COPY

ATTACHMENT AVAILABLE

SIGNATURE OF APPLICANT (PRINT NAME)

DATE

100-100

INDUSTRIAL MICROBICIDE

ACTIVE INGREDIENTS

Methylene bis(4-chloroanil)

2.5%

2,4-Dichloro-methylthio-benzothiazole

2.5%

INERT INGREDIENTS

95.0%

This product weighs 7.99 pounds per gallon

KEEP OUT OF REACH OF CHILDREN DANGER

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage and causes skin damage. Harmful or fatal if swallowed or absorbed through the skin. This product is a potential skin sensitizer. Workers handling this product or treated material should wear impervious gloves, goggles or face shield, and protective clothing. All protective clothing, work shoes or boots, and equipment must be left at the work site at the end of the day. Eating, drinking, or smoking during use of this product is prohibited.

FIRST AID: In case of skin contact, wash promptly and thoroughly with soap and water and finally with glycerin. If product gets in the eyes, flush immediately with copious amounts of clean, cool water for 15 to 30 minutes. Get medical attention immediately. If product is swallowed, call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply directly to water or wetlands. Permits may be required for discharges containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS: Do not expose to extreme temperatures.

STORAGE & DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Do not expose to extreme temperatures. Do not stack more than five drums high. Drums should be opened in well-ventilated areas. Leaking or damaged drums should be placed in one pack drum for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or residue is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

COOLING TOWERS

wood against soft or surface rot and internal or dry rot. It is applied as a surface treatment to wood containing 2.0 to 2.8% moisture. The amount applied should provide 2.4 to 3.2 lb of active ingredient per 1000 ft² of wood surface. Soft or surface rot can also be treated by applying this product to the recirculating cooling water. The dosage should provide 5.0 lb of active ingredient per 1000 gal of water and the bleed-off should be stopped for 4 to 6 hr after treatment. Repeat every four months.

COOLING WATER

and fungi in industrial recirculating cooling water systems. Bleed-off should be cleared thoroughly to remove mild algal growth, microorganisms. System should then be drained, flushed, refilled with water, and treated with this product at a rate of 0.8 to 4.8 fl oz per 1000 gal water, depending on the severity of microbiological fouling.

DRILLING FLUIDS: To inhibit bacterial and fungal degradation of drilling fluids, apply this product at a concentration of 0.2 to 1.0% based on the total wet weight of the fluid.

PETROLEUM SECONDARY RECOVERY: To control sulfate-reducing bacteria, slime-forming bacteria, and other oil field water contaminants, apply this product at a rate of 15.6 to 52.0 fl oz per 1000 gal of water. Apply continuously or intermittently by means of a metering pump, after injection pumps and injection well headers. Continuous feed method: add 15.6 to 52.0 fl oz per 1000 gal of water continuously until desired degree of control is achieved. The intermittent or slug method: When system is noticeably fouled, add 15.6 to 52.0 fl oz per 1000 gal of water and 1 to 4 times per week, or as needed to maintain control.

CRUDE AND REFINED OILS

valuable for the control of bacteria and fungi that cause the degradation of oil during storage. It should be added to the oil as it is being transferred to storage tank at the rate of 2.4 to 24.0 fl oz per 1000 gal of oil. Addition should be made batchwise where mixing occurs or continuously where transfer pump.

Manufactured by:

LANE CHEMICAL CO.
1000 N. W. 10th St.
Miami, FL 33136

EPA REG. NO. _____

EPA EST. _____

NET CONTENTS _____